

ND-R176 983


PROJECT BIDDING UNDER CHANCE TIME ESTIMATES(U) AIR
FORCE INST OF TECH WRIGHT-PATTERSON AFB ON
R S VOGTMANN 1986 AFIT/CI/NR-87-32T


1/2

UNCLASSIFIED

F/G 5/1

ML





MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS - 1961

AD-A176 909

(1)

Project Bidding Under Chance
Time Estimates

by
Russell S. Vogtmann

DTIC
ELECTED
FEB 18 1987
S D
[Handwritten mark: a checkmark next to S and a circle next to D]

A thesis submitted to the Graduate Faculty
North Carolina State University
in partial fulfillment of the
requirements for the Degree of
Master of Science

Department of Operations Research

Raleigh
1986

DISTRIBUTION STATEMENT A
Approved for public release;
Distribution Unlimited

Approved by:


John Bish *[Signature]*
Chairman of Advisory Committee

87 2 17 095
87 2 17 095

DTIC FILE COPY

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER AFIT/CI/NR 87-32T	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Project Bidding Under Cahnce Time Estimates		5. TYPE OF REPORT & PERIOD COVERED THESIS/DISSERTATION
7. AUTHOR(s) Russell S. Vogtmann		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS AFIT STUDENT AT: North Carolina State Univ		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
11. CONTROLLING OFFICE NAME AND ADDRESS AFIT/NR WPAFB OH 45433-6583		12. REPORT DATE 1986
14. MONITORING AGENCY NAME & ADDRESS(if different from Controlling Office)		13. NUMBER OF PAGES 179
		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, If different from Report)		
18. SUPPLEMENTARY NOTES APPROVED FOR PUBLIC RELEASE: IAW AFR 190-1		 LYNN E. WOLAYER 30 JAN 89 Dean for Research and Professional Development AFIT/NR
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) ATTACHED		

52

Abstract

VOGTMANN, RUSSELL S. 2nd Lt., U.S. Air Force, 1987. Project Bidding Under Chance Time Estimates (Under the direction of Salah E. Elmaghhraby.) 76pp. Master of Science, North Carolina State University.

The bidding for the contract of a project is a very important phase in the life of the project. In today's competitive market for a project contract, it is essential to have accurate information in order to make a bid that will yield a profit and still win the contract.

In this thesis, we examine projects that can be modeled by directed acyclic networks under probabilistic activity durations and costs (the PERT model). For a successful bid, the contractor must recognize that there are two streams of cash flow: an "outflow" caused by the undertaking of the activities of the project, and an "inflow" due to income received at the time of realization of pre-designated "key events". Under the PERT model of activity networks, both streams of cash flow are subject to uncertainty. The contractor's problem then becomes that of the estimation of these two streams at sufficient confidence to realize a reasonable profit for him.

A Monte Carlo simulation is developed for solution of the problem, and a computer package has been constructed to assist project managers in the determination of the bid package.

Accession For	
NTIS CRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Jurisdiction	
By _____	
Distribution / _____	
Availability Codes	
Dist	Avail and/or Special
A-j	

Table of Contents

1. INTRODUCTION.....	1
2. PROBLEM STATEMENT.....	4
3. A DETERMINISTIC EXAMPLE.....	7
4. METHODOLOGY.....	17
4.1 Cost Separation of Common Activities.....	17
4.2 Method of Separating Costs of Common Activities...	25
4.3 An Alternative Cost Separation Method.....	27
4.4 Distributions Associated With Key Events.....	29
4.4.1 Realization Time Distribution.....	30
4.4.2 Cost Distribution.....	32
4.4.2.1 Activity Cost.....	32
4.4.2.2 Cost of Subgraph.....	34
4.4.2.3 Dependency of Cost Random Variables.	36
4.5 Determination of Cash Flow.....	38
5. SOLUTION PROCEDURE.....	40
6. COMPUTER PROGRAM.....	43
6.1 Program Explanation.....	43
6.2 Program Assumptions.....	44
6.3 Program Usage.....	47
6.4 Example.....	48
6.5 Discussion of Program.....	72
7. CONCLUSION AND DIRECTION FOR FUTURE RESEARCH.....	73
8. REFERENCES.....	75
9. APPENDIX (Program Listings).....	77
9.1 ANC-IN.....	78
9.2 Logic of Program AN-COST.....	100
9.3 AN-COST.....	102
9.4 CASH.....	149

1. INTRODUCTION

The process of bidding for the contract of a particular project is a very important phase in the life of that project. And although bidding (and its precursor, cost estimation) has been a topic of research for decades, it has been largely overlooked in the area of activity networks (ANs). This fact seems odd since from the very beginnings of PERT (Program Evaluation and Review Technique), the Department of Defense has demanded the use of the PERT model of the project in any proposal submitted to it [6]. If the contractor, in his proposal, must submit a network detailing the method by which he plans to complete the project, then it would make sense that he use that information in the preparation of his bid on the project. Presently, for both the contractor and the owner of a project, project bids are typically determined on the basis of 'averages' based on past performance. As a consequence, a project that represents a novel undertaking in either its technological content or in its scope poses a dilemma to both sides, with the blind leading the blind in the ensuing negotiations. And yet, it is precisely these unique features that gave rise to the concept of 'project management' in the first place! [7].

Clearly this method fails to use the information provided in the network model of the project. The reason for this discrepancy, however, does not lie in the hands of the

project manager. The research in the theory of ANs (specifically, directed acyclic networks), since their inception in 1959, has been mainly directed in the following areas [5]: 1) optimal project "compression", 2) optimal planning and acquisition of resources, 3) optimal scheduling under constrained availability of scarce resources, and 4) analysis and synthesis of projects under conditions of uncertainty. Of these four areas, only the first has dealt with cost considerations, and then only in the deterministic case. So we see the theory has not yet evolved sufficiently to be successfully applied to the area of project bidding.

The literature of activity networks has long recognized the need to somehow account for the cost incurred due to the activities. In 1971, Kleindorfer [10] discussed three money flow problems due to an activity: 1) Flows that accrue at the start or end of an activity, 2) Time-varying flows that accrue during the execution of an activity, and 3) Time-varying flows that begin at the start or end of an activity and continue thereafter. These cost considerations, however, have mainly manifested themselves in cost control [5] rather than in determining a project bid prior to the inception of the project. There have been few instances in which an attempt has been made to utilize AN theory to determine that bid.

In 1972, Case [2], in a paper titled "On the Consideration of Variability in Cost Estimating", made an attempt to

determine a cost distribution by using a three estimate approach to estimate activity cost similar to a PERT estimate of activity duration. Then the project cost is the sum of these activity cost random variables (which by appealing to the Central Limit Theorem is approximately normally distributed), from which a mean and variance of project cost could be determined and various probabilistic statements could be made. Unfortunately, this simplistic method falls far short of providing any realistic help in dealing with the problem at hand. In 1974, in a paper titled "Interrelating Project Estimates to CPM Schedules", Badger [1] discussed a method of cross referencing estimate accounts to network activities to provide compatibility between the two project control documents. The approach goes into detail on the allocation of the project resources to the specific activities that require them. This appears to be the first place in the literature that directly uses the project network when making project estimates. The remaining literature effectively ignores the relationship between the project network and project bidding.

It is obvious that the process of infusing the theory of activity networks into the formulation of a project bid has not been adequately addressed to this date, especially in the case of PERT networks.

2. PROBLEM STATEMENT

When faced with preparing a bid to submit to the owner of a project, the contractor must analyze the project to determine how he will complete the project. Included in this analysis is the formulation of a project network and the determination of the resources (and consequently costs) that are required to complete it. The contractor will often define various key events in the project at which he will require the owner to make partial payments for work that has been completed, and often requires an initial payment before the work on the project begins.

Farid and Boyer [8] indicate that the bid that results should be the total cost of the project multiplied by a "fair and reasonable markup" (FaRM) of the project cost. The FaRM is viewed as the smallest markup which satisfies the Required-Rate-of-Return (RRR) of the contractor for the particular project at hand. A FaRM of a project, given a RRR, can be obtained via AN theory by analyzing the two streams of cash flow inherent in any project. These streams are: 1) "outflow": payments made by the contractor in executing the project, and 2) "inflow": receipts from the owner of the project at various key events (i.e., those events at which payments are made to the contractor). In the case where all activities in the network can be modeled deterministically (in duration and cost), there is no problem in defining the cost of an activity, and subsequently

the cost of the project. The two streams of cash flow can then be easily obtained given a particular schedule of the network activities, and a FaRM determined. An illustration of this process is presented in section 3.

Russell [13] has formulated a mathematical program to determine the schedule of activities that maximizes the net present value of a deterministic network given cash flows and resource restrictions. Several heuristics were compared for solution of the nonlinear program. The contractor will then have an optimal schedule by which he performs the activities of the project.

Unfortunately, when we are dealing with PERT-type stochastic networks (characterized by activity durations and costs that are both probabilistic), the realization time of a key event as well as the costs of the activities leading to the realization of the key event can only be determined in a probabilistic sense. At this point, the manager of the project must make a decision on the amount of risk he wants to take in the process of setting a delivery date and the cost of the subgraph of the key event. Further complicating the issue of obtaining a FaRM in PERT networks is the problem of scheduling the activities necessary to calculate the stream of cash "outflow".

When these problems are adequately addressed in the case of a PERT network, we will have a logical and theoretically sound method of determining a bid package for projects

that can be modeled as directed acyclic networks. This method would appear to be superior to methods that are presently used to determine bids in industry. Whether it will be practical in real-life situations has yet to be determined.

Purpose of Research

The purpose of this research is to address the problem of determining a bid package -- i.e., the payment amounts and dates, for projects that can be modeled by a directed acyclic network.

3. A DETERMINISTIC EXAMPLE

The simplest form of the bidding problem in the context of ANs lies in the deterministic (CPM) model. This model is a first step to solving the more general probabilistic model. In this case, it is easy to determine the two streams of cash flow, and consequently calculate the FARM given a RRR. The following example will introduce some necessary concepts of the bidding problem, which will then be generalized to the probabilistic model that is the main concern of this thesis.

Assume it is desired to bid on a project that is modeled with the data in Table 1 and the network in Figure 1.

Table 1. Activity Durations and Costs for CPM Example.

Activity	Duration	Cost/day	Fixed Cost
1. Excavate	2	100	500
2. Foundation	4	300	1000
3. Rough wall	10	250	1000
4. Rough ext. plumbing	4	150	200
5. Roof	6	250	1000
6. Rough interior plumbing	5	150	200
7. Rough electrical work	7	100	200
8. Exterior siding	7	75	200
9. --dummy--	0	0	0
10. Exterior painting	9	40	50
11. Wall board	8	40	25
12. Interior painting	5	40	50
13. Flooring	4	75	100
14. --dummy--	0	0	0
15. Exterior fixtures	2	200	100
16. Interior fixtures	6	100	300




Figure 1. Network for Deterministic Example.

Table 2. Bar Chart and Cash "Outflow" for CPM Example.

Act	Dur
1	2		--									
2	4		----									
3	10			-----								
4	4				---							
5	6					---						
6	5						---					
7	7							---				
8	7								---			
9	0									-----		
10	9										---	
11	8										-----	
12	5											---
13	4											---
14	0											
15	2											--
16	6											----

"outflow" | 2600| 2300| 1250| 3650| 2175| 615| 700| 1390| 400|

The key events of the project have been pre-determined to be 4, 10, and 13, and for this example assume that all activities are scheduled to begin at their earliest start times. (The implications of activity float in the deterministic model of this problem will be discussed near the end of the example). The bar chart in Table 2 shows when each activity is scheduled to be performed, as well as the cost incurred per period (assume a 'period' length of 5 'units'; e.g., a period represents a week of 5 days). Note that in this deterministic example, the activity schedule is very well defined. The cost incurred in a period is calculated by adding the fixed costs of activities that begin in the period plus the cost/day of the activities performed in the period times the number of days that they are performed in that period. To illustrate, the calculations for the cash "outflow" in periods 1 and 7 are shown.

period 1

activity	fixed cost	cost/day	# days	total cost
1	500	100	2	700
2	1000	300	3	1900
<hr/>				
cost incurred in period 1 = 2600				

period 7

activity	fixed cost	cost/day	# days	total cost
10	---	40	5	200
11	---	40	3	120
12	50	40	2	130
13	100	75	2	250
<hr/>				
cost incurred in period 7 = 700				

To calculate the cash "inflow" of the project, we must determine two elements: (i) the cost associated with the subgraph of each key event, which is then multiplied by some 'markup' to obtain the cash "inflow", and (ii) the time of realization of the key event. The cost of the subgraph to the key event is the sum of the costs of the activities in the subgraph. These calculations are displayed below and summarized in Table 3.

key event 4

activity	fixed cost	cost/day	# days	total cost
1	500	100	2	700
2	1000	300	4	2200
3	1000	250	10	3500

				cost of subgraph = 6400

key event 10

activity	fixed cost	cost/day	# days	total cost
4	200	150	4	800
5	1000	250	6	2500
8	200	75	7	725
9	0	0	0	0
10	50	40	9	410

				cost of subgraph = 4435

key event 13

activity	fixed cost	cost/day	# days	total cost
6	200	150	5	950
7	200	100	7	900
11	25	40	8	345
12	50	40	5	250
13	100	75	4	400
14	0	0	0	0
15	100	200	2	500
16	300	100	6	900

				cost of subgraph = 4245

Table 3. Cost of Subgraphs and Realization Times for CPM Example.

Key event	cost of subgraph	realization time
4	6400	16
10	4435	38
13	4245	44

Table 4 displays the cash flows for the project given a zero markup of cost for the cash "inflow".

Table 4: Cash Flows for CPM Example (assuming a zero cost markup, and the percentage of the project cost that we require at the beginning of the project is 0%).

Period	1	2	3	4	5	6	7	8	9
"outflow"	2600	2300	1250	3650	2175	615	700	1390	400
"inflow"				6400				4435	4245

Now, given this information, we should be able to calculate the FaRM for this project for a given RRR. For the sake of this example, let RRR=20%, initial capital=\$500, interest rate on money deposited=10%, interest rate on money borrowed=15%, and the retention percentage=12%. Then if we perform the required calculations of simple financial management (i.e. paying the cash "outflow", receiving the cash "inflow", depositing money at an interest rate, and borrowing money at an interest rate when applicable), we obtain a FaRM=1.2051. The pertinent results of the calculations are displayed in table 5 where it is assumed that the cash "out-

flow" is incurred at the beginning of the period and the cash "inflow" occurs at the end of the period (e.g., the cash "outflow" in period 5 and the cash "inflow" in period 4 occur simultaneously in the calculations at the beginning of period 5) This would indicate that we make a bid of \$18,247.22 in this project which has a cost of \$15,141.17.

The progress payments can be easily determined using the FaRM and the cost of the subgraphs. These progress payments are \$7721.80, \$5371.18, \$5153.65, respectively.

Table 5. FaRM Calculations for Deterministic Example

FaRM (Activity Worth / Activity Cost) = 1.2051

<u>Period</u>	<u>Interest*</u>	<u>Cash Balance**</u>	<u>Retention#</u>	<u>Cum Ret. ##</u>
0	-----	500.00	-----	-----
1	(4.02)	-2104.02	0.00	0.00
2	(8.45)	-4415.62	0.00	0.00
3	(10.86)	-5679.91	0.00	0.00
4	(17.91)	-9362.82	0.00	0.00
5	(9.11)	-4763.44	926.65	927.86
6	(10.32)	-5392.97	0.00	929.07
7	(11.69)	-7528.14	0.00	931.50
9	(6.14)	-3211.87	644.56	1578.12
10	1.73	1325.21	618.46	2199.45
11	1.73	1326.94	0.00	2202.32

Terminal Cash Position### = 3529.26
Profit = .200

* Interest on money borrowed is in parenthesis.

** Cash balance at end of period.

Amount retained at beginning of period.

Cumulative retention at end of period.

Terminal cash = cash balance + cum.retention.

Activity Float Considerations

The above FaRM was obtained assuming that all activities begin at their earliest start times. Of course, in the deterministic model, all activities that are not contained in the critical path have float. Therein lies the only possible flexibility in the bidding strategy for the deterministic model. Logic dictates that the contractor would want to start all activities as late as possible (thereby delaying his disbursements) without causing a delay in the realization times of the key events (and subsequently delaying his cash "inflow"); see Russell [13].

Note that if the contractor has overhead that is incurred from the beginning to the end of the project, he can simply add another arc in the network from the start node to the terminal node indicating the appropriate cost/unit time. This process of adding arcs to the network can be used to model costs that are inherent in the execution of any project (be it overhead cost or otherwise). The network of Figure 2 illustrates this point. If we add an arc from node 1 to node 13 with a duration of 44, a fixed cost of zero and a cost/day of 25.00 for administration plus 35.00 for overhead cost, and a zero duration arc from node 13 to node 14 to model some fixed cost of 500.00 incurred at the conclusion of the project, the network in Figure 2 results. Assuming the same values for capital, RRR, etc., one obtains a FaRM= 1.2055. This would result in a bid of \$22,061.70 for the

project that has a cost of \$18,300.79.

This deterministic example displays the cash flow concepts involved in the bidding problem. When we generalize this model to include activities and costs that are probabilistic in nature, we introduce complications in the realization time and cost of subgraphs of key events, as well as in determining the cash "outflow" of the project.




Figure 2. Network of Fig.1 with Added Costs

4. METHODOLOGY


From this point on, when referring to the bidding problem, we assume the structure of the AN is known. From a theoretical point of view, the major problem is the determination of the appropriate method of separation of cost of activities that belong to more than one key event. To this end, we examine the subgraphs of the various key events of a project. Define a subgraph of a node in a network as the subnetwork terminating at that node. If we define $S(i) = \{\text{set of activities belonging to the subgraph of key event } i\}$, then for key events i and j , either (a) $S(i)$ and $S(j)$ are disjoint (no common activities), (b) $S(i)$ is a subset of $S(j)$ or $S(j)$ is a subset of $S(i)$, or (c) $S(i)$ and $S(j)$ overlap (i.e. they have elements in common, but neither is a subset of the other). Figure 3 graphically displays these situations.

4.1 Cost Separation of Common Activities


When $S(i)$ and $S(j)$, for all $i \neq j$, are disjoint, the cost of each activity is assigned to its respective key event.

When $S(i)$ is a subset of $S(j)$, the cost of the subgraph of $S(i)$ is assigned to key event i , and the cost of the remaining activities is assigned to key event j .


If $S(i)$ and $S(j)$ overlap, a situation exists in which an activity is in the subgraph of more than one key event



(a)



(b)



(c)

Figure 3: Relationships between Subgraphs of Key Events

and neither is a subset of the other. The simple network example in Figure 4 (with key events 4, 5, and 6) will illustrate these concepts: activity 'a' is common to all key events, activity 'c' is common to key events 4 and 6, activities 'b', 'd', and 'e' are common to key events 5 and 6, and activities 'f' and 'g' are unique to key event 6. Since activities 'f' and 'g' are unique to key event 6, their cost is attributed to that key event. The costs of the remaining activities are assigned to either key event 4 or 5. Clearly, the cost of activity 'c' is assigned to key event 4, and the costs of activities 'b', 'd', and 'e' are assigned to key event 5.




Figure 4: Network Illustrating Common Activities

Since activity 'a' is common to 4 and 5, we must either assign the cost of activity 'a' to one of the key events or divide its cost, attributing a percentage of its cost to each key event in such a manner so there is no "double costing" for the same activity. The contractor would want to receive the payment for common activities as early as possible, thereby maximizing his profit, and the owner would rather pay as late as possible, thus minimizing his expense. We wish to address this issue objectively and obtain a logical and consistent method of separating the costs of the common activities.

There are many heuristics that could be used to address this problem. The following are just a few:

Heuristic 1. Separate costs based on the probability of the earliest realization of the key events.

Heuristic 2. Separate costs based on the activity criticality index in each key event subnetwork.

Heuristic 3. Separate costs based on the relative cost of the subgraphs of the key events.

Heuristic 4. Separate costs based on the criticality index of the key events themselves.

In section 4.3 we criticize heuristics 2-4, but we first develop an argument supporting heuristic 1. Since the key event that is realized first requires the common activities to be completed by its realization time, it is reasonable to assign the cost of the common activities (or a large

portion of it) to that key event. In mathematical terms, it seems reasonable to attribute a greater share of the cost of common activities to those key events having the greatest probabilities of being realized first. Note that in a deterministic network, this would translate into attributing the entire cost of common activities to the key event that is realized at the earliest time.

To illustrate, we continue the analysis of the network in Figure 4. The subgraphs of key events 4 and 5 are shown in Figure 5. Assume that all activity durations are distributed as a Gamma random variable with parameters ($t=2$, $\lambda=1$). Then, the realization time distributions, means, and variances are as listed in Table 6. The calculations required to determine the distribution functions are summarized in table 7.




Figure 5: Subgraphs of Key Events 4 and 5

Table 6: Parameters of key events 4 and 5 of Figure 4.

Node 4: $T_4 = Y_a + Y_b$

$$F_4(t) = 1 - \exp(-t) * (1 + t + t^2/2 + t^3/6)$$

Mean = 4
Variance = 4

Node 5: $T_5 = \max \{ Y_a + Y_d ; Y_b + Y_e \}$

$$F_5(t) = 1 - 2 * \exp(-t) * (1 + t + t^2/2 + t^3/6)$$

$$+ \exp(-2*t) * (1 + t + t^2/2 + t^3/6)^2$$

Mean = 5.46
Variance = 4.17

Table 7: Realization Time Distribution Calculations for Example Network

Random Variable	Representation	Probability Distribution Function
T_1	0	
T_2	y_a	$1 - \exp(-t) * (1-t)$
T_3	y_b	$1 - \exp(-t) * (1-t)$
T_4	$T_2 + y_c$	$1 - \exp(-t) * (1+t+t^2/2+t^3/6)$
w_1	$y_a + y_d$	$1 - \exp(-t) * (1+t+t^2/2+t^3/6)$
w_2	$y_b + y_e$	$1 - \exp(-t) * (1+t+t^2/2+t^3/6)$
T_5	$\max(w_1, w_2)$	$1 - 2 * \exp(-t) * (1+t+t^2/2+t^3/6)$ $+ \exp(-2*t) * (1+t+t^2/2+t^3/6)^2$

The probability density functions of the node realization times are graphed in Figure 6.




Figure 6: Density Functions of Key Events 4 and 5

If we let Y_4 denote the realization time of key event 4 and Y_5 denote the realization time key event 5, then from the data it is clear that $\Pr(Y_4 \leq Y_5)$ will be relatively high (the allocation calculations will be presented in section 4.2). Therefore, we will allocate a greater percentage of the cost of activity 'a' to key event 4.

In general, the allocation percentage of key event i would be calculated as follows: let Y_i denote the realization time of key event i (the key event for which we desire to determine the cost allocation percentage), and Y_j denote the realization time of key event j , for $j \in H(i)$, where $H(i)$ is the set of key events that share activities with key event i , and let N denote the number of key events in $H(i)$.

Furthermore, let A_j denote the event $[Y_i \leq Y_j]$ (i.e. key event i is realized before key event j), for $j \in H(i)$, and let $Prop(i)$ denote the proportion of the cost of common activities allocated to key event i . Then,

$$Prop(i) = \Pr \{ A_1, \dots, A_N \}. \quad (1)$$

This yields the probability that key event i is realized first. Unfortunately, this probability statement is not immediately amenable to solution since the A_j 's are not independent. To resolve this, we assume independence of the elements in $H(i)$ and condition on the random variable Y_i . Let B_j denote the event $[Y_j \geq y]$ (i.e. node j is realized after time y), for $j \in H(i)$. Then since we assume that the Y_j 's are independent,

$$Prop(i) = \int^{\infty} \Pr \{ B_1, \dots, B_N \} * dF_Y(y) \quad (2)$$

$$= \int^{\infty} \Pr \{ B_1 \} * \dots * \Pr \{ B_N \} * dF_Y(y) \quad (3)$$

Therefore, when we know the forms of the distribution functions of the realization times of the key events, we can use the above equation to solve for the cost allocation percentages.

4.2 Method of Separating Costs of Common Activities

The algorithm presented next is based on the above argument. To facilitate the computations, we make the following assumptions: 1) realization times of key events are normally distributed (or can be thus approximated), and 2) the events A_j can be considered independent.

The computer software developed uses either this method, or permits the user to assign proportions as he sees fit.

Cost Separation Algorithm:

- 1) Denote the key event with the smallest mean by key event s , then determine the probability, $p(i)$, that key event s is realized before key event i , for $i \in H(s)$.

$$p(i) = \Pr \{ Y_s \leq Y_i \} \quad (4)$$

---if $p(i)$ is greater than or equal to 0.9, assign a proportion of zero to key event i . This is an arbitrary cut-off point.

- 2) all remaining key events are given percentages as follows:

---let $w(i) =$

$$= \Pr \{ Y_i \leq Y_1 \} * \dots * \Pr \{ Y_i \leq Y_N \} \quad (5)$$

---then, let the proportion $\text{Prop}(i) = w(i) / \sum_i w(i)$

Applying the above algorithm to the example network in Figure 4 yields:

$$p(5) = \Pr \{ Y_4 \leq Y_5 \} = .695$$

Therefore,

$$w(4) = .695, \text{ or } \text{Prop}(4) = .695,$$

$$\text{and } w(5) = .305, \text{ or } \text{Prop}(5) = .305.$$

Therefore, we allocate 69.5% of the cost of activity 'a' to key event 4, and 30.5% of the cost to key event 5.

To show the limiting case when the probability of realizing one key event earlier than another is very high, let

the network in Figure 4 be modified as follows: activity 'c' is distributed as a Gamma ($t=20$, $\lambda=1$). The resulting distribution parameters are:

node 4: mean = 22, variance = 22,

and node 5: mean = 5.46, variance = 4.17.

The cost separation algorithm results in the following:

$$p(4) = \Pr \{ Y_5 \leq Y_4 \} = .999$$

Therefore,

$$\text{Prop}(4) = 0.0, \text{ and } \text{Prop}(5) = 100.0$$

The algorithm assigns the entire cost of activity 'a' to key event 5, as intended.

4.3 An Alternative Cost Separation Method

Heuristic 2 suggests an alternate method of cost separation that considers the importance of the common activities to their respective key events. We examine it here to display a problem that it shares with heuristics 3 and 4. To illustrate, consider the network of Figure 7. Then the activities that are common to key events 4 and 5 are 'a', 'b', and 'd'. The criticality index of an activity is defined as the probability that the activity is on the critical path; see Elmaghraby [5], p. 277. Now, if we define the importance of the activity as the criticality of the activity in the subgraph of the key event, we can determine a percentage to assign to the key events.




Figure 7: Network Example for Alternative Cost Separation Method

Figure 8 shows the key event subgraphs and the approximate activity criticality indices for the given activity duration distributions.




Figure 8: Subgraphs of Key Events 4 and 5 of Fig. 7

Activity 'b' has a criticality index of .035 in the subgraph of node 4, and .502 in the subgraph of node 5. This gives us an indication of the relative importance of activity 'b' to its key events from which we can determine a percentage of the cost allocation. Thus, according to the logic of this heuristic, the overwhelming majority of the cost of activity 'b' should be allocated to key event 5.

Although this method of separating costs is intuitively appealing, it ignores the fact that the total activity cost is incurred long before the key event, to which we have attributed a majority of the common activity cost, is realized. The network in Figure 7 illustrates this problem. We expect to realize node 4 before time 20.1 with probability .95, and expect to realize node 5 after time 23.1 with probability .95. Therefore, the total cost of activity 'b' is expected to be expended long before node 5 is realized, yet we do not account for most of it until node 5 is realized because of the method of cost allocation. Clearly, this is not in the best interest of the contractor who is trying to maintain liquidity. Also, in a PERT network, determining the criticality index of an activity, or even approximating it, is a difficult problem; see Dodin and Elmaghraby [4].

4.4 Distributions Associated With Key Events

Before a bid proposal can be submitted, the contractor

needs to know how much he is going to bid at the various key events and the dates at which he is going to promise delivery of various portions of the project. If we are dealing with a deterministic network (in both duration and cost), there is no ambiguity as to either of these quantities. The completion date takes on a value that has probability 1, as does the cost. In this case, then, a bid can be prepared and submitted with no risk to the contractor, and hence, his profit is secure.

More realistically, however, one cannot assume that all quantities in the model are deterministic. We must assume that activity duration is only defined in a probabilistic sense as a random variable, and cost is some function of the duration (and subsequently a random variable itself), or is conditional on the observed duration. This results in the realization times and costs at key events being defined as random variables.

4.4.1 Realization Time Distribution

In a given project, a contractor may have many different key events at which he must deliver a product, or a portion of a product, to the owner of the project. The contractor, in his proposal, will give target dates by which he must deliver these products, and in the case of an overrun he will assume some penalty for being late. Since there is most likely competition for the project, a contractor must

submit a competitive delivery date for any chance of getting the contract. If this is the case, the contractor will be assuming a risk of observing realization times of the key events beyond those at which he promised delivery. To clarify this, the contractor's bid options include two extreme strategies: 1) Very conservative -- in this case, he will bid a long duration and correspondingly high cost which may well result in not receiving the contract and therefore making no money, and 2) Very optimistic, in which case he will bid an early completion time and corresponding low cost resulting in high probability of not fulfilling his promises, and consequently he will have heavy penalties and make no money either! Because of this environment, it is essential that he have accurate information on the distribution of realization time in order to properly assess his risk.

The problem of determining the pdf of the realization time of a node in a directed acyclic network has been one of the main areas of work in the area of activity networks since the very beginnings of the PERT model. Elmaghraby [6] discusses various methods of determining the pdf of a node (key event) in the PERT model, which include analytical approaches, approximations, bounding approaches, and Monte Carlo sampling. Once the pdf is determined by any one of these methods, the contractor can estimate the risk he is taking when giving a delivery date.

Notice that if we determine the realization time dis-

tributions of different key events in the network that have common activities, the resulting random variables are not independent. Because of this, at least in theory, when we are determining delivery dates for these dependent key events, we should consider them simultaneously. In practice, however, when approximating the realization time distributions of these nodes, we normally assume independence of paths to each node. Under this assumption, the resulting realization time distributions are independent. Consequently, we can consider the delivery dates independently from each other.

4.4.2 Cost Distribution

Similarly, when a competitive bid is submitted, the contractor will assume a risk that the actual realization of the network cost is greater than his bid, thus incurring a loss. For this reason, it is essential also that a pdf of cost for the subgraph of a key event be determined. We now address the problem of determining the cost of an activity, and subsequently will examine the cost of a subgraph of a key event.

4.4.2.1 Activity Cost

As was mentioned previously, there are different costs that can be incurred due to an activity. In this thesis, we will consider only the following two costs: 1) Fixed cost

incurred at the inception of the activity, and 2) Variable cost incurred during the execution of the activity that is either a function of the activity duration or is a random variable whose pdf is conditional upon the activity duration. If the cost is a function of the duration (e.g., a linear function in the form of $\text{Cost} = a + (b * \text{duration})$), then it is fairly straightforward to determine the pdf of the cost of the activity. But if the cost is a random variable that is conditional upon the actual activity duration, then to determine the cost pdf of the activity we must appeal to basic probability theory. Let C denote the cost of the activity, and Y denote its duration. Then we have the following relationship on the joint density of cost and duration, the conditional density of cost given duration, and the unconditional density on duration:

$$f_{C|Y}(c,y) = f(c,y)/f_Y(y) \quad (6)$$

To determine the unconditional cost density we must integrate the joint density with respect to duration. The following example will illustrate this procedure, along with the difficulties associated with it.

Let the duration be distributed exponentially with mean 10 ($f_Y(y) = 1/10 * \exp(-y/10)$), and cost, conditional on the activity duration, be distributed exponentially with mean $100 * \text{duration}$ ($f_{C|Y}(c,y) = 1/100*y * \exp(-c/100*y)$). Then the unconditional distribution of cost is:

$$\int_0^{\infty} 1/1000y * \exp(-y/10 - c/100*y) dy \quad (7)$$

Clearly, this is not easy to evaluate. With many distributions, the unconditional distribution of cost could not be evaluated analytically.

4.4.2.2 Cost of Subgraphs

The cost of the subgraph of a key event is the sum of the costs of the individual activities of the subgraph. If we assume that the costs of activities are independent (although in actuality this may not necessarily be the case), then the distribution function of the cost of the subgraph will be the convolution of the individual activity cost distribution functions. This does not pose any theoretical problems, but an analytical solution for a given network poses definite computational problems. This is due to the fact that only in very rare cases will the pdf's of the costs of individual activities be amenable to mathematical manipulation (e.g., normal, in which case the convolution is easily determined since the sum of normal r.v.'s is itself normal). More likely is the case where we need to sum random variables that assume different pdf's. An analytical solution would involve multiple integration, which is a formidable computational problem.

To bypass this difficulty in analytically determining the cost pdf's, we can appeal to approximating the cost distribution by the following methods: 1) Central Limit Theorem, and 2) Monte Carlo Sampling.

By the Central Limit Theorem, we know that, subject to mild assumptions, as the number of activities in the subgraph of a key event goes to infinity, the cost distribution of the key event may be approximated by the normal distribution with mean = $\sum_i \text{mean}(i)$ and variance = $\sum_i \text{var}(i)$. Unfortunately, we know that the number of activities in the subgraph of a key event is oftentimes not very large, and hence the application of the Central Limit Theorem can result in erroneous probability statements (remember that determining the cost distributions of the key events is something we want to do as accurately as possible, especially in the context of project bidding where poor approximation of the cost distribution can lead to a large monetary loss).

If we are unwilling to apply the Central Limit Theorem, we can approximate the cost pdf by Monte Carlo sampling. This method is straightforward population sampling and has some distinct advantages. First, the individual cost densities need not be determined, which, as was stated earlier, can be a difficult task. The only knowledge of the cost density necessary is the form relative to the duration of the activity (e.g., a linear function of duration, a normal distribution about a constant times the duration, etc.). Another advantage of Monte Carlo sampling is that when approximating the cost distribution we can guarantee that our approximate cost distribution is within a certain tolerance level from the true distribution (see sample size discus-

sion). Monte Carlo sampling will be discussed further in section 5.

4.4.2.3 Dependency of Cost Random Variables

As discussed previously, in the cases of (i) either $S(i)$ or $S(j)$ is a subset of the other, and (ii) $S(i)$ and $S(j)$ are disjoint, the cost of activities are unambiguously assigned to their respective key events. But when $S(i)$ and $S(j)$ partially overlap (neither is a subset of the other), difficulties arise in allocating the cost of the common activities to the key events. That problem was resolved by partitioning the cost of the common activities. Unfortunately, the act of dividing the cost of a common activity and assigning percentages of the cost to different key events results in cost allocations that are not independent r.v.'s. To illustrate this point, we use the network in Figure 4 with all durations Gamma distributed with $t=2$, $\lambda=1$. As was previously discussed, the cost of activity 'a' is allocated to the two key events 4 and 5. The resulting cost values are:

$$\text{node 4: } C(4) = \text{prop}(4) * \text{cost}(a) + \text{cost}(c) \quad (8)$$

$$\begin{aligned} \text{node 5: } C(5) = & \text{prop}(5) * \text{cost}(a) + \text{cost}(b) \\ & + \text{cost}(d) + \text{cost}(e) \end{aligned} \quad (9)$$

where $\text{prop}(i) =$ proportion of the cost of activity 'a'
assigned to node i,

$C(i) =$ cost of key event i, and

cost(i) = cost of activity i.

It is then clear that the costs at nodes 4 and 5 are not independent because both r.v.'s include the cost of activity 'a'.

Because of this fact, when we have determined the cost pdf's of the key events under specific allocation strategies and are deciding what the bid should be at each key event, we should not consider the key events independently of each other. We can define the joint cumulative probability distribution by:

$$F(c_1, \dots, c_n) = \Pr\{ C(1) \leq c_1, \dots, C(n) \leq c_n \} \quad (10)$$

The marginal distribution of the cost at a key event can then be shown [12] to be:

$$F(c_i) = \Pr\{ C(1) \leq \infty, \dots, C(i) \leq c_i, \dots, C(n) \leq \infty \} \quad (11)$$

Given this marginal distribution, we can determine a bid at one key event independently from the costs at other key events. Theoretically, this is a straightforward application of elementary probability theory. The application of this theory, though, is difficult to carry out because of its computational complexity.

Fortunately, in practice, it would be consistent to assume that the cost r.v.'s can be treated as independent r.v.'s, as was done in the approximation of the realization times of the key events.

4.5 Determination of Cash Flow

When confronted with a potential project, the contractor must know if he will maintain liquidity throughout the project. To this end, we need to determine the expected cash "outflow" for the duration of the project. When activity duration and cost are defined as random variables, the problem of scheduling activities becomes very complex, and therefore determining the expected disbursements for the duration of the project is also complex. There are two methods to which we can resort in solving this problem, both of which require extensive computing effort. These methods are: 1) Monte Carlo simulation, and 2) analytical approach. Monte Carlo simulation is a straightforward method of determining the expected costs incurred in given intervals over many realizations of the network. This will be discussed in section 5.

The analytical approach to solving this problem, although conceptually fairly simple, is no trivial exercise. It is outlined here to display the difficulty associated in determining the exact expected cash "outflow".

Denote the start time of activity 'i' by ST_i , and let $E[C(m,i)]$ denote the expected cost incurred in period 'm' due to activity 'i'. Clearly, $E[C(m,i)]$ is dependent on three elements: the df of the cost of the activity as a function of its duration, the start time of the activity, and the probability that it is 'in progress' in period 'm'.

The total expected disbursement in period 'm' could then be the sum of the individual expected costs; the sum extending over all activities that may be in progress in period 'm'.

It is evident that the determination of $E[C(m,i)]$ is no minor feat, even when using the approximation method of Dardin [3] to determine the df of ST_i . Consequently, the analytical determination of the expected cash "outflow" was abandoned, and attention was diverted to the use of MCS methods.

5. SOLUTION PROCEDURE

The procedure adopted in solving the bidding problem is Monte Carlo simulation (MCS). The main reason for the adoption of this approach is to allow the calculation of the cash "outflow" discussed in the previous section. As Elmaghraby states [5], "whenever analytical approaches fail, or appear to overwhelm one's capacity to obtain numerical answers, one turns to population sampling and statistical techniques." Also, since the application of ANs to the bidding of a project for PERT networks has never been addressed before, MCS seems to be a logical first step in the solution of the problem.

The MCS technique generates a duration for each arc in the network from its distribution, and then calculates the realization times for the key events in the network. This is considered one sample. The result over many of these samples is a realization time distribution for each key event in the network. In addition, for the bidding problem, we must generate a cost for each activity according to its distribution (thus resulting in a cost distribution over many samples), as well as calculate the cash "outflow" in each period for each sample (resulting in an expected cash "outflow" over many samples), and calculate the cash "inflow" in each period for each sample (resulting in an expected cash "inflow" over many samples).

There are two theoretical concerns involved with MCS:

1) Size of the sample to guarantee a pre-assigned confidence, and 2) Use of variance-reduction techniques to increase precision (or minimize sample size). A discussion of sample size follows. The use of variance-reduction techniques is discussed by Elmaghraby [5] and [6], and will not be addressed in this thesis.

Sample Size

The main objective of the bidding problem is the determination of the distribution functions of realization times and costs of the key events in the network. If we use MCS to determine these df's, we have to make the sample size sufficient to estimate them with a given precision. This sample size can be determined by means of the Kolmogorov-Smirnov statistic as discussed by Elmaghraby [5] and tabulated by Hoel [9] and Massey [11] for limited values of sample size and confidence. For completeness, these concepts are discussed next.

If we assume the true distribution function, F_n , is continuous, we can make statements concerning the greatest absolute difference between the sample distribution function and the true distribution function. Let $G_{nK}(t)$ denote the sample df derived from a sample of size K , and $D_{nK} = \sup_t |G_{nK}(t) - F_n(t)|$. Then the probability that D_K is less than a specified d/\sqrt{K} is asymptotically given by

$$\lim_{K \rightarrow \infty} \Pr\{ D_{nK} \leq d/\sqrt{K} \} = \sum_{i=-\infty}^{\infty} (-1)^i * \exp(-2*i^2*d^2) \quad (14)$$

The values of d for different confidence levels have been

tabulated by Smirnov [14] and the asymptotic probability of $\sqrt{K} * D_{nK} \leq d$ can then be obtained. As an example, suppose we wish to estimate F_n by G_{nK} such that the maximum deviation between the two functions does not exceed 0.01 in absolute value more than 5% of the time. For the asymptotic probability $\Pr\{\sqrt{K} * D_{nK} \leq d\} = .95$, we have $d = 1.36$. Since $D_{nK} = .01$, we solve for $\sqrt{K} * 0.01 \geq 1.36$ to obtain $K \geq 18,496$.

Of course, in the bidding problem, we are concerned with estimating many df's simultaneously. This does not, however, introduce any complications even though some of the random variables whose df's we are estimating are not independent (specifically, cost and duration at key events). This is because, for each df we are estimating, the samples are independent and identically distributed. Therefore, we can estimate all of the df's simultaneously using the sample size determined above, and we can be confident that our Monte Carlo approximations to the distribution functions are accurate enough to make statements on the realization times and costs of key events.

6. COMPUTER PROGRAM

Software has been developed, written in Microsoft FORTRAN77, that allows the user to interactively determine a bid for a project that can be modeled by a directed acyclic network. The program listings are in the appendix, and an example will be presented section 6.4.

6.1 Program Explanation

The computer software developed is divided into three main programs: ANC-IN, AN-COST, and CASH, and an optional program DOD1TRNS.

Program ANC-IN prepares the data necessary for the Monte Carlo simulation. It also has the capability to randomly generate an AN if desired for research purposes. This program is a modification of the input program used by Dodin [3] to approximate the realization time distributions of nodes in a directed acyclic network. This provides the capability to use Dodin's program using the same data file, which allows comparison of the Monte Carlo-generated realization time distributions and the approximate distributions provided by Dodin.

Program DOD1TRNS, written by Dodin [3], calculates the means and standard deviations of the key events which are required by program AN-COST for use in the sharing of costs of common activities as well as in determining the endpoints of the empirical distributions. The means and standard de-

viations are then placed in a data file which is read by program AN-COST. If these values are available from another source, they can simply be placed in the data file and DOD1TRNS need not be run.

Program AN-COST actually performs the Monte Carlo simulation to determine the realization time distributions and cost distributions of the key events, the expected cash "inflow", and the expected cash "outflow". To do this, it determines the cost separation percentages of the common activities and calculates the required sample size before the simulation begins. The results of the run are sent to various data files for perusal.

Program CASH allows cash flow calculations to be performed, as well as allowing the user to view the results of the Monte Carlo simulation. It reads a data file created by AN-COST, and interactively assists the user in determining a bid package.

6.2 Program Assumptions

The following assumptions were made in implementing the computer program.

- General:
- 1) Directed acyclic networks only.
 - 2) The network has at most 100 activities
 - 3) The network has at most 50 nodes (this is a limitation of DOD1TRNS(see 6, below), not of AN-COST).
 - 4) Maximum project duration is 100 periods.
 - 5) All activities begin at their earliest start times.
 - 6) The means and std. dev.s of the key nodes are

known prior to running program AN-COST. (If these parameters are not known, they can be obtained by running program DOD1TRNS.)

Duration: --Activity duration is distributed as one of the following:

- 1) Uniform
- 2) Triangular
- 3) Normal
- 4) Exponential
- 5) Gamma
- 6) Beta
- 7) Discrete (user defined as ordered pairs)

Cost: Activity cost consists of a fixed cost assessed at the start of the activity, and a cost that is either a linear function of the duration or a cost that follows a density conditional on the realized duration. The following cost functions are available:

- 1) Constant * Duration
- 2) Normal (mean=constant*duration, var.=given)
(see discussion, below)
- 3) Uniform (the endpoints of the uniform dist.
are [constant*duration-given val.,
constant*duration+given val.])
(see discussion, below)
- 4) Triangular (mode=constant*duration, min=mode-given, max=mode+given)
(see discussion, below)

Cost functions 2, 3, and 4 are illustrated in Figure 10. For a normal cost function, the mean is a user-specified constant times the activity duration, and the variance is a user-specified constant.


For a uniform cost function, the endpoints of the distribution are a user-specified constant, k1, times the activity duration minus another user-specified value, k2, and k1 times the activity duration plus another user-specified value, k3. Therefore, the distribution does not have to be symmetric about $k1 * \text{duration}$.



a) normal cost distribution



b) uniform cost distribution



c) triangular cost distribution

Figure 9: Illustration of Cost Functions

For a triangular cost function, the mode of the distribution is a user-specified value, k_1 , times the activity duration. The minimum is the mode minus another user-specified value, k_2 , and the maximum is the mode plus another user-specified value, k_3 . Again, the distribution is not necessarily symmetric.

6.3 Program Usage

To use the programs to make bid packages, the following steps must be taken:

- 1) Create a data file containing the duration and cost information of the network. This can be done using program ANC-IN. This program is an alteration of the input program for program DODIN1, which determines the PDF of realization time of nodes in a network. The data is put in the file in such a manner that DODIN1 can be run using the same data file.
- 2) Put the means and standard deviations of the key events in a data file named TRNS.ANC in increasing order of node number. If the means and std. dev.s are not known a priori, a run of program DOD1TRNS will determine them and place them in the data file. Program DOD1TRNS, which can be used to do all the calculations of DODIN1 with the exception of generation of a network and MCS, is a skeleton version of DODIN1.
- 3) Run program AN-COST. This program performs the MCS to determine realization time distributions and cost distributions of the key events of the network. This program also calculates the expected cash "inflow" and "outflow" for each period in the network. The cash flow data is sent to file CASHFLOW.DAT, which is used in program CASH to perform cash flow calculations.
- 4) Run program CASH if cash flow calculations are

desired. Program CASH will allow the user to view the data from the MCS, determine a FaRM in deterministic problems, and determine the expected profit in a probabilistic problem. It allows viewing of the distribution functions, and determines the percentiles of the distributions as an aid in making decisions on the bids at the key events.

6.4 Example

Consider the network previously used in Figure 1, reproduced in Figure 10 for convenience. For this example, let the activities durations be normally distributed and the costs be linear functions of the durations with the parameters listed in Table 8. Then running program ANC-IN will yield the input data file listed in Table 9.

Table 8. Activity Distribution Parameters for Example Problem

Activity	Duration		Cost	
	Mean	Std. Dev.	Cost/day	Fixed Cost
1	2	0.5	100	500
2	4	1.0	300	1000
3	10	2.0	250	1000
4	4	1.0	150	200
5	6	1.5	250	1000
6	5	1.5	150	200
7	7	1.0	100	200
8	7	1.0	75	200
9	0	0.0	0	0
10	9	2.0	40	50
11	8	1.5	40	25
12	5	2.0	40	50
13	4	1.0	75	100
14	0	0.0	0	0
15	2	0.5	200	100
16	6	1.5	100	300




Figure 10: Network for Illustration of Computer Program

Table 9. Input Data File for Example Problem.*

	<u>#nodes</u>	<u>#arcs</u>			<u>#key events</u>	
.500	13	16	30	1	0	3
						0
	<u>key events</u>					
	4	10	13			
**	<u>start node</u>	<u>end node</u>	<u>duration dist.</u>		<u>#durations/</u>	
	<u>distribution parameters</u>					
	1	2	3	0		
	.2000E+01	.5000E+00	.5000E+00	.3500E+01		
	2	3	3	0		
	.4000E+01	.1000E+01	.2000E+01	.6000E+01		
	3	4	3	0		
	.1000E+02	.2000E+01	.5000E+01	.1500E+02		
	4	5	3	0		
	.4000E+01	.1000E+01	.2000E+01	.6000E+01		
	4	6	3	0		
	.6000E+01	.1500E+01	.3000E+01	.9000E+01		
	5	7	3	0		
	.5000E+01	.1500E+01	.2000E+01	.8000E+01		
	4	7	3	0		
	.7000E+01	.1000E+01	.5000E+01	.9000E+01		
	6	8	3	0		
	.7000E+01	.1000E+01	.5000E+01	.9000E+01		
	5	8	7	1		
	.0000E+00	.1000E+01				
	8	10	3	0		
	.9000E+01	.2000E+01	.5000E+01	.1300E+02		
	7	9	3	0		
	.8000E+01	.1500E+01	.5000E+01	.1100E+02		
	9	12	3	0		
	.5000E+01	.2000E+01	.1000E+01	.9000E+01		
	9	11	3	0		
	.4000E+01	.1000E+01	.2000E+01	.6000E+01		
	11	12	7	1		
	.0000E+00	.1000E+01				
	10	13	3	0		
	.2000E+01	.5000E+00	.1000E+01	.3000E+01		
	12	13	3	0		
	.6000E+01	.1500E+01	.3000E+01	.9000E+01		

*Numbers not labeled are used only by program DOD1TRNS in the determination of the mean and standard deviation of the key events (for more info. see Dodin [3]).

**See program listing for more details.

Table 9 (Continued)

<u>*cost distribution/</u>	<u>fixed cost</u>	<u>variable cost</u>	<u>distribution parameters</u>		
1	.5000E+03	.1000E+03	.0000E+00	.0000E+00	.0000E+00
1	.1000E+04	.3000E+03	.0000E+00	.0000E+00	.0000E+00
1	.1000E+04	.2500E+03	.0000E+00	.0000E+00	.0000E+00
1	.2000E+03	.1500E+03	.0000E+00	.0000E+00	.0000E+00
1	.1000E+04	.2500E+03	.0000E+00	.0000E+00	.0000E+00
1	.2000E+03	.1500E+03	.0000E+00	.0000E+00	.0000E+00
1	.2000E+03	.1000E+03	.0000E+00	.0000E+00	.0000E+00
1	.2000E+03	.7500E+02	.0000E+00	.0000E+00	.0000E+00
1	.0000E+00	.0000E+00	.0000E+00	.0000E+00	.0000E+00
1	.5000E+02	.4000E+02	.0000E+00	.0000E+00	.0000E+00
1	.2500E+02	.4000E+02	.0000E+00	.0000E+00	.0000E+00
1	.5000E+02	.4000E+02	.0000E+00	.0000E+00	.0000E+00
1	.1000E+03	.7500E+02	.0000E+00	.0000E+00	.0000E+00
1	.0000E+00	.0000E+00	.0000E+00	.0000E+00	.0000E+00
1	.1000E+03	.2000E+03	.0000E+00	.0000E+00	.0000E+00
1	.3000E+03	.1000E+03	.0000E+00	.0000E+00	.0000E+00

*See program listing for more details.

If the means and standard deviations of the key events are not known, we next run program DOD1TRNS, which will place them in data file TRNS.ANC. Table 10 displays the file for this network.

Table 10: File TRNS.ANC for Example Problem

Key Event	Mean	Std. Dev.
4	.1600E+02	.2290E+01
10	.3800E+02	.3530E+01
13	.4400E+02	.6000E+01

The MCS, performed by program AN-COST, using a sample size of 18,496 (this sample size guarantees a tolerance of no more than .01 with a confidence of 95%) yields the output files shown in Tables 11, 12, 13, and 14. Table 11 contains the distribution information of duration of the key events as well as the criticality indices of the activities. Table 12 contains the distribution information of cost of the key events and total project cost. Table 13 displays a data file produced with some general information used by the simulation, and table 14 lists the data file CASHFLOW.DAT, produced by AN-COST for use by program CASH.

Table 11. Empirical Distributions of Durations and Activity Criticality Indices.

---- KEY EVENT 4 -----

Pr { X <= 10 } =	.0000
Pr { 10.000 < X <= 10.550 } =	.0006
Pr { 10.550 < X <= 11.100 } =	.0019
Pr { 11.100 < X <= 11.650 } =	.0042
Pr { 11.650 < X <= 12.200 } =	.0098
Pr { 12.200 < X <= 12.750 } =	.0167
Pr { 12.750 < X <= 13.300 } =	.0305
Pr { 13.300 < X <= 13.850 } =	.0481
Pr { 13.850 < X <= 14.400 } =	.0735
Pr { 14.400 < X <= 14.950 } =	.0917
Pr { 14.950 < X <= 15.500 } =	.1140
Pr { 15.500 < X <= 16.050 } =	.1169
Pr { 16.050 < X <= 16.600 } =	.1224
Pr { 16.600 < X <= 17.150 } =	.1105
Pr { 17.150 < X <= 17.700 } =	.0902
Pr { 17.700 < X <= 18.250 } =	.0670
Pr { 18.250 < X <= 18.800 } =	.0444
Pr { 18.800 < X <= 19.350 } =	.0268
Pr { 19.350 < X <= 19.900 } =	.0149
Pr { 19.900 < X <= 20.450 } =	.0092
Pr { 20.450 < X <= 21.000 } =	.0044
Pr { X > 21 } =	.0022
Pr { X <= 10.000 } =	.0000
Pr { X <= 10.550 } =	.0006
Pr { X <= 11.100 } =	.0025
Pr { X <= 11.650 } =	.0068
Pr { X <= 12.200 } =	.0165
Pr { X <= 12.750 } =	.0333
Pr { X <= 13.300 } =	.0638
Pr { X <= 13.850 } =	.1119
Pr { X <= 14.400 } =	.1853
Pr { X <= 14.950 } =	.2770
Pr { X <= 15.500 } =	.3911
Pr { X <= 16.050 } =	.5080
Pr { X <= 16.600 } =	.6304
Pr { X <= 17.150 } =	.7409
Pr { X <= 17.700 } =	.8311
Pr { X <= 18.250 } =	.8981
Pr { X <= 18.800 } =	.9425
Pr { X <= 19.350 } =	.9693
Pr { X <= 19.900 } =	.9842
Pr { X <= 20.450 } =	.9934
Pr { X <= 21.000 } =	.9978

Table 11 (Continued)

THE MEAN OF THE DIST. =	16.0044
THE VARIANCE OF THE DIST. =	3.1521
THE STD. DEV. OF THE DIST. =	1.7754

Table 11 (Continued)

----- KEY EVENT 10 -----

Pr { X <= 29 } =	.0000
Pr { 29.000 < X <= 29.850 } =	.0009
Pr { 29.850 < X <= 30.700 } =	.0020
Pr { 30.700 < X <= 31.550 } =	.0045
Pr { 31.550 < X <= 32.400 } =	.0106
Pr { 32.400 < X <= 33.250 } =	.0203
Pr { 33.250 < X <= 34.100 } =	.0362
Pr { 34.100 < X <= 34.950 } =	.0527
Pr { 34.950 < X <= 35.800 } =	.0831
Pr { 35.800 < X <= 36.650 } =	.0955
Pr { 36.650 < X <= 37.500 } =	.1159
Pr { 37.500 < X <= 38.350 } =	.1269
Pr { 38.350 < X <= 39.200 } =	.1213
Pr { 39.200 < X <= 40.050 } =	.1027
Pr { 40.050 < X <= 40.900 } =	.0865
Pr { 40.900 < X <= 41.750 } =	.0602
Pr { 41.750 < X <= 42.600 } =	.0377
Pr { 42.600 < X <= 43.450 } =	.0203
Pr { 43.450 < X <= 44.300 } =	.0122
Pr { 44.300 < X <= 45.150 } =	.0061
Pr { 45.150 < X <= 46.000 } =	.0025
Pr { X > 46 } =	.0019
Pr { X <= 29.000 } =	.0000
Pr { X <= 29.850 } =	.0009
Pr { X <= 30.700 } =	.0029
Pr { X <= 31.550 } =	.0074
Pr { X <= 32.400 } =	.0180
Pr { X <= 33.250 } =	.0383
Pr { X <= 34.100 } =	.0746
Pr { X <= 34.950 } =	.1272
Pr { X <= 35.800 } =	.2103
Pr { X <= 36.650 } =	.3058
Pr { X <= 37.500 } =	.4218
Pr { X <= 38.350 } =	.5487
Pr { X <= 39.200 } =	.6700
Pr { X <= 40.050 } =	.7727
Pr { X <= 40.900 } =	.8592
Pr { X <= 41.750 } =	.9193
Pr { X <= 42.600 } =	.9570
Pr { X <= 43.450 } =	.9773
Pr { X <= 44.300 } =	.9895
Pr { X <= 45.150 } =	.9956
Pr { X <= 46.000 } =	.9981

Table 11 (Continued)

THE MEAN OF THE DIST. =	38.0164
THE VARIANCE OF THE DIST. =	7.2432
THE STD. DEV. OF THE DIST. =	2.6913

Table 11 (Continued)

---- KEY EVENT 13 -----

Pr { X <= 35 } =	.0002
Pr { 35.000 < X <= 35.850 } =	.0007
Pr { 35.850 < X <= 36.700 } =	.0014
Pr { 36.700 < X <= 37.550 } =	.0044
Pr { 37.550 < X <= 38.400 } =	.0087
Pr { 38.400 < X <= 39.250 } =	.0167
Pr { 39.250 < X <= 40.100 } =	.0301
Pr { 40.100 < X <= 40.950 } =	.0465
Pr { 40.950 < X <= 41.800 } =	.0675
Pr { 41.800 < X <= 42.650 } =	.0866
Pr { 42.650 < X <= 43.500 } =	.1090
Pr { 43.500 < X <= 44.350 } =	.1165
Pr { 44.350 < X <= 45.200 } =	.1171
Pr { 45.200 < X <= 46.050 } =	.1043
Pr { 46.050 < X <= 46.900 } =	.0926
Pr { 46.900 < X <= 47.750 } =	.0680
Pr { 47.750 < X <= 48.600 } =	.0512
Pr { 48.600 < X <= 49.450 } =	.0338
Pr { 49.450 < X <= 50.300 } =	.0195
Pr { 50.300 < X <= 51.150 } =	.0128
Pr { 51.150 < X <= 52.000 } =	.0064
Pr { X > 52 } =	.0061
Pr { X <= 35.000 } =	.0002
Pr { X <= 35.850 } =	.0009
Pr { X <= 36.700 } =	.0023
Pr { X <= 37.550 } =	.0067
Pr { X <= 38.400 } =	.0154
Pr { X <= 39.250 } =	.0321
Pr { X <= 40.100 } =	.0622
Pr { X <= 40.950 } =	.1087
Pr { X <= 41.800 } =	.1761
Pr { X <= 42.650 } =	.2627
Pr { X <= 43.500 } =	.3717
Pr { X <= 44.350 } =	.4882
Pr { X <= 45.200 } =	.6053
Pr { X <= 46.050 } =	.7096
Pr { X <= 46.900 } =	.8022
Pr { X <= 47.750 } =	.8702
Pr { X <= 48.600 } =	.9214
Pr { X <= 49.450 } =	.9552
Pr { X <= 50.300 } =	.9748
Pr { X <= 51.150 } =	.9875
Pr { X <= 52.000 } =	.9939

Table 11 (Continued)

THE MEAN OF THE DIST. =	44.4840
THE VARIANCE OF THE DIST. =	8.3119
THE STD. DEV. OF THE DIST. =	2.8830

Table 12. Empirical Distributions of Costs

----- PROJECT COST -----

Pr { X <= 13273 }	=	.0003
Pr { 13273.000 < X <= 13459.900 }	=	.0032
Pr { 13459.900 < X <= 13646.800 }	=	.0050
Pr { 13646.800 < X <= 13833.700 }	=	.0094
Pr { 13833.700 < X <= 14020.600 }	=	.0192
Pr { 14020.600 < X <= 14207.500 }	=	.0297
Pr { 14207.500 < X <= 14394.400 }	=	.0487
Pr { 14394.400 < X <= 14581.300 }	=	.0667
Pr { 14581.300 < X <= 14768.200 }	=	.0930
Pr { 14768.200 < X <= 14955.100 }	=	.1055
Pr { 14955.100 < X <= 15142.000 }	=	.1170
Pr { 15142.000 < X <= 15328.900 }	=	.1174
Pr { 15328.900 < X <= 15515.800 }	=	.1066
Pr { 15515.800 < X <= 15702.700 }	=	.0922
Pr { 15702.700 < X <= 15889.600 }	=	.0663
Pr { 15889.600 < X <= 16076.500 }	=	.0522
Pr { 16076.500 < X <= 16263.400 }	=	.0317
Pr { 16263.400 < X <= 16450.300 }	=	.0174
Pr { 16450.300 < X <= 16637.200 }	=	.0104
Pr { 16637.200 < X <= 16824.100 }	=	.0048
Pr { 16824.100 < X <= 17011.000 }	=	.0018
Pr { X > 17011 }	=	.0015
Pr { X <= 13273.000 }	=	.0003
Pr { X <= 13459.900 }	=	.0035
Pr { X <= 13646.800 }	=	.0085
Pr { X <= 13833.700 }	=	.0179
Pr { X <= 14020.600 }	=	.0371
Pr { X <= 14207.500 }	=	.0668
Pr { X <= 14394.400 }	=	.1155
Pr { X <= 14581.300 }	=	.1821
Pr { X <= 14768.200 }	=	.2751
Pr { X <= 14955.100 }	=	.3806
Pr { X <= 15142.000 }	=	.4976
Pr { X <= 15328.900 }	=	.6150
Pr { X <= 15515.800 }	=	.7216
Pr { X <= 15702.700 }	=	.8139
Pr { X <= 15889.600 }	=	.8802
Pr { X <= 16076.500 }	=	.9324
Pr { X <= 16263.400 }	=	.9641
Pr { X <= 16450.300 }	=	.9815
Pr { X <= 16637.200 }	=	.9919
Pr { X <= 16824.100 }	=	.9966
Pr { X <= 17011.000 }	=	.9985

Table 12 (Continued)

THE MEAN OF THE DIST. = 15145.6822
THE VARIANCE OF THE DIST. = 390349.5940
THE STD. DEV. OF THE DIST. = 624.7796

Table 12 (Continued)

---- KEY EVENT 4 -----

Pr { X <= 5070 }	=	.0004
Pr { 5070.000 < X <= 5203.800 }	=	.0024
Pr { 5203.800 < X <= 5337.600 }	=	.0048
Pr { 5337.600 < X <= 5471.400 }	=	.0097
Pr { 5471.400 < X <= 5605.200 }	=	.0192
Pr { 5605.200 < X <= 5739.000 }	=	.0298
Pr { 5739.000 < X <= 5872.800 }	=	.0504
Pr { 5872.800 < X <= 6006.600 }	=	.0679
Pr { 6006.600 < X <= 6140.400 }	=	.0922
Pr { 6140.400 < X <= 6274.200 }	=	.1080
Pr { 6274.200 < X <= 6408.000 }	=	.1163
Pr { 6408.000 < X <= 6541.800 }	=	.1181
Pr { 6541.800 < X <= 6675.600 }	=	.1069
Pr { 6675.600 < X <= 6809.400 }	=	.0914
Pr { 6809.400 < X <= 6943.200 }	=	.0684
Pr { 6943.200 < X <= 7077.000 }	=	.0475
Pr { 7077.000 < X <= 7210.800 }	=	.0293
Pr { 7210.800 < X <= 7344.600 }	=	.0187
Pr { 7344.600 < X <= 7478.400 }	=	.0103
Pr { 7478.400 < X <= 7612.200 }	=	.0049
Pr { 7612.200 < X <= 7746.000 }	=	.0020
Pr { X > 7746 }	=	.0014
Pr { X <= 5070.000 }	=	.0004
Pr { X <= 5203.800 }	=	.0028
Pr { X <= 5337.600 }	=	.0075
Pr { X <= 5471.400 }	=	.0172
Pr { X <= 5605.200 }	=	.0364
Pr { X <= 5739.000 }	=	.0663
Pr { X <= 5872.800 }	=	.1167
Pr { X <= 6006.600 }	=	.1846
Pr { X <= 6140.400 }	=	.2768
Pr { X <= 6274.200 }	=	.3848
Pr { X <= 6408.000 }	=	.5011
Pr { X <= 6541.800 }	=	.6192
Pr { X <= 6675.600 }	=	.7262
Pr { X <= 6809.400 }	=	.8176
Pr { X <= 6943.200 }	=	.8860
Pr { X <= 7077.000 }	=	.9335
Pr { X <= 7210.800 }	=	.9628
Pr { X <= 7344.600 }	=	.9815
Pr { X <= 7478.400 }	=	.9918
Pr { X <= 7612.200 }	=	.9966
Pr { X <= 7746.000 }	=	.9986

Table 12 (Continued)

THE MEAN OF THE DIST. = 6407.0008
THE VARIANCE OF THE DIST. = 198487.0996
THE STD. DEV. OF THE DIST. = 445.5189

Table 12 (Continued)

----- KEY EVENT 10 -----

Pr { X <= 3448 } =	.0001
Pr { 3448.000 < X <= 3548.800 } =	.0011
Pr { 3548.800 < X <= 3649.600 } =	.0037
Pr { 3649.600 < X <= 3750.400 } =	.0094
Pr { 3750.400 < X <= 3851.200 } =	.0187
Pr { 3851.200 < X <= 3952.000 } =	.0325
Pr { 3952.000 < X <= 4052.800 } =	.0497
Pr { 4052.800 < X <= 4153.600 } =	.0704
Pr { 4153.600 < X <= 4254.400 } =	.0925
Pr { 4254.400 < X <= 4355.200 } =	.1031
Pr { 4355.200 < X <= 4456.000 } =	.1180
Pr { 4456.000 < X <= 4556.800 } =	.1114
Pr { 4556.800 < X <= 4657.600 } =	.1076
Pr { 4657.600 < X <= 4758.400 } =	.0902
Pr { 4758.400 < X <= 4859.200 } =	.0712
Pr { 4859.200 < X <= 4960.000 } =	.0526
Pr { 4960.000 < X <= 5060.800 } =	.0323
Pr { 5060.800 < X <= 5161.600 } =	.0201
Pr { 5161.600 < X <= 5262.400 } =	.0091
Pr { 5262.400 < X <= 5363.200 } =	.0043
Pr { 5363.200 < X <= 5464.000 } =	.0015
Pr { X > 5464 } =	.0003
Pr { X <= 3448.000 } =	.0001
Pr { X <= 3548.800 } =	.0012
Pr { X <= 3649.600 } =	.0049
Pr { X <= 3750.400 } =	.0143
Pr { X <= 3851.200 } =	.0330
Pr { X <= 3952.000 } =	.0655
Pr { X <= 4052.800 } =	.1152
Pr { X <= 4153.600 } =	.1856
Pr { X <= 4254.400 } =	.2781
Pr { X <= 4355.200 } =	.3812
Pr { X <= 4456.000 } =	.4992
Pr { X <= 4556.800 } =	.6107
Pr { X <= 4657.600 } =	.7183
Pr { X <= 4758.400 } =	.8085
Pr { X <= 4859.200 } =	.8796
Pr { X <= 4960.000 } =	.9323
Pr { X <= 5060.800 } =	.9646
Pr { X <= 5161.600 } =	.9847
Pr { X <= 5262.400 } =	.9938
Pr { X <= 5363.200 } =	.9982
Pr { X <= 5464.000 } =	.9997

Table 12 (Continued)

THE MEAN OF THE DIST. = 4458.9100

THE VARIANCE OF THE DIST. = 110690.6299

THE STD. DEV. OF THE DIST. = 332.7020

Table 12 (Continued)

---- KEY EVENT 13 -----

Pr { X <= 3464 } =	.0002
Pr { 3464.000 < X <= 3545.300 } =	.0028
Pr { 3545.300 < X <= 3626.600 } =	.0039
Pr { 3626.600 < X <= 3707.900 } =	.0095
Pr { 3707.900 < X <= 3789.200 } =	.0191
Pr { 3789.200 < X <= 3870.500 } =	.0309
Pr { 3870.500 < X <= 3951.800 } =	.0486
Pr { 3951.800 < X <= 4033.100 } =	.0700
Pr { 4033.100 < X <= 4114.400 } =	.0882
Pr { 4114.400 < X <= 4195.700 } =	.1038
Pr { 4195.700 < X <= 4277.000 } =	.1167
Pr { 4277.000 < X <= 4358.300 } =	.1196
Pr { 4358.300 < X <= 4439.600 } =	.1058
Pr { 4439.600 < X <= 4520.900 } =	.0897
Pr { 4520.900 < X <= 4602.200 } =	.0723
Pr { 4602.200 < X <= 4683.500 } =	.0514
Pr { 4683.500 < X <= 4764.800 } =	.0316
Pr { 4764.800 < X <= 4846.100 } =	.0187
Pr { 4846.100 < X <= 4927.400 } =	.0108
Pr { 4927.400 < X <= 5008.700 } =	.0044
Pr { 5008.700 < X <= 5090.000 } =	.0017
Pr { X > 5090 } =	.0005
Pr { X <= 3464.000 } =	.0002
Pr { X <= 3545.300 } =	.0030
Pr { X <= 3626.600 } =	.0070
Pr { X <= 3707.900 } =	.0164
Pr { X <= 3789.200 } =	.0356
Pr { X <= 3870.500 } =	.0664
Pr { X <= 3951.800 } =	.1150
Pr { X <= 4033.100 } =	.1850
Pr { X <= 4114.400 } =	.2732
Pr { X <= 4195.700 } =	.3770
Pr { X <= 4277.000 } =	.4937
Pr { X <= 4358.300 } =	.6133
Pr { X <= 4439.600 } =	.7191
Pr { X <= 4520.900 } =	.8088
Pr { X <= 4602.200 } =	.8811
Pr { X <= 4683.500 } =	.9324
Pr { X <= 4764.800 } =	.9640
Pr { X <= 4846.100 } =	.9826
Pr { X <= 4927.400 } =	.9935
Pr { X <= 5008.700 } =	.9978
Pr { X <= 5090.000 } =	.9995

Table 12 (Continued)

THE MEAN OF THE DIST. =	4279.7714
THE VARIANCE OF THE DIST. =	73074.0281
THE STD. DEV. OF THE DIST. =	270.3221

Table 13. General Output File for Example Problem

THE PERIOD LENGTH = 5

THE PERC. REQUIRED AT START = .000

THE INFLATION RATE = .10000

THE INITIAL RANDOM NUMBER SEED = 123454.00

VALUES OF ENDPOINTS FOR EMPIRICAL DIST.'S ARE:

	LEFT-END	RIGHT-END	INT.-WIDTH
KEY EVENT 4			
REAL. TIME DIST.	10	21	.55
COST FUNC.	5070	7746	133.80
KEY EVENT 10			
REAL. TIME DIST.	29	46	.85
COST FUNC.	3448	5464	100.80
KEY EVENT 13			
REAL. TIME DIST.	35	52	.85
COST FUNC.	3464	5090	81.30
TOTAL PROJECT COST	13273	17011	186.90

Table 14. File CASHFLOW.DAT for Example Problem.

```

period length
    5
max. periods
    14
expected cash outflow per period
    .277648E+04 .212517E+04 .173647E+04 .325721E+04 .197417E+04
    .746016E+03 .746758E+03 .107538E+04 .606587E+03 .973920E+02
    .374120E+01 .952881E-02 .000000E+00 .000000E+00
#key events
    3
key events
    4    10    13
expected cash inflow for key event 4
    .000000E+00 .132299E+01 .169048E+04 .461520E+04 .999844E+02
    .000000E+00 .000000E+00 .000000E+00 .000000E+00 .000000E+00
    .000000E+00 .000000E+00 .000000E+00 .000000E+00
expected cash inflow for key event 10
    .000000E+00 .000000E+00 .000000E+00 .000000E+00 .000000E+00
    .454279E+01 .542953E+03 .281885E+04 .106864E+04 .239204E+02
    .000000E+00 .000000E+00 .000000E+00 .000000E+00
expected cash inflow for key event 13
    .000000E+00 .000000E+00 .000000E+00 .000000E+00 .000000E+00
    .000000E+00 .116708E+01 .229862E+03 .219535E+04 .170776E+04
    .144858E+03 .772703E+00 .000000E+00 .000000E+00

$received at proj.start    money received at proj. start
    .000000E+00    .000000E+00

mean      std.dev.      (duration/cost of key events)
    .160044E+02 .177541E+01
    .640700E+04 .445518E+03
    .380164E+02 .269132E+01
    .445891E+04 .332702E+03
    .444840E+02 .288304E+01
    .427977E+04 .270322E+03

mean      std.dev.      (total proj. cost)
    .151456E+05 .624779E+03

empirical distribution functions

lower endpt.    upper endpt.    #cells    cell width
    10            21            20            .55000
    .000000E+00 .594723E-03 .194636E-02 .421712E-02 .978590E-02
    .167063E-01 .305471E-01 .480644E-01 .734753E-01 .916955E-01
    .114024E+00 .116944E+00 .122404E+00 .110456E+00 .902357E-01
    .670415E-01 .443879E-01 .268166E-01 .148680E-01 .919117E-02
    .437932E-02 .221669E-02
        5070        7746        20        133.80000
    .378460E-03 .237889E-02 .475778E-02 .973183E-02 .191933E-01
    .298442E-01 .503892E-01 .679065E-01 .921820E-01 .108023E+00

```

Table 14 (Continued)

.116349E+00	.118079E+00	.106942E+00	.914251E-01	.684472E-01
.474697E-01	.293036E-01	.187067E-01	.102724E-01	.486591E-02
.200043E-02	.135164E-02			
29	46	20	.85000	
.000000E+00	.919117E-03	.200043E-02	.448745E-02	.105468E-01
.203287E-01	.362240E-01	.526600E-01	.830990E-01	.955341E-01
.115917E+00	.126892E+00	.121323E+00	.102670E+00	.865051E-01
.601751E-01	.376838E-01	.202746E-01	.122188E-01	.605536E-02
.254109E-02	.189230E-02			
3448	5464	20	100.80000	
.540657E-04	.113538E-02	.367647E-02	.940743E-02	.187067F-01
.324935E-01	.497404E-01	.703936E-01	.925064E-01	.103103E+00
.118025E+00	.111429E+00	.107590E+00	.902357E-01	.711505E-01
.526059E-01	.323313E-01	.201124E-01	.913711E-02	.432525E-02
.151384E-02	.324394E-03			
35	52	20	.85000	
.162197E-03	.702854E-03	.140570E-02	.443339E-02	.870458E-02
.166522E-01	.301146E-01	.464965E-01	.674740E-01	.865592E-01
.108996E+00	.116511E+00	.117052E+00	.104346E+00	.926146E-01
.679606E-01	.512002E-01	.338451E-01	.195177E-01	.127595E-01
.643382E-02	.605536E-02			
3464	5090	20	81.30000	
.216263E-03	.281141E-02	.394679E-02	.946150E-02	.191392E-01
.308715E-01	.485510E-01	.700151E-01	.882353E-01	.103752E+00
.116673E+00	.119647E+00	.105752E+00	.896950E-01	.722859E-01
.513624E-01	.315743E-01	.186526E-01	.108131E-01	.437932E-02
.167603E-02	.486591E-03			
13273	17011	20	186.90000	
.324394E-03	.318987E-02	.497404E-02	.940743E-02	.191933E-01
.297361E-01	.486591E-01	.666630E-01	.929930E-01	.105482E+00
.116998E+00	.117376E+00	.106617E+00	.922361E-01	.663386E-01
.521734E-01	.317365E-01	.174091E-01	.103806E-01	.475778E-02

sample corr. coef. (ρ) least squares estimators ($C = \beta_0 + \beta_1 Y + \epsilon$)

<u>cost vs. duration -- key event 4</u>			
.972125E+00	.250284E+04	.243942E+03	
<u>cost vs. duration -- key event 10</u>			
.531348E+00	.196178E+04	.656853E+02	
<u>cost vs. duration -- key event 13</u>			
.543696E+00	.201204E+04	.509784E+02	
<u>total project cost vs. project duration</u>			
.750275E+00	.791297E+04	.162591E+03	

fraction of total project cost received at key events

<u>key event 4</u>	<u>key event 10</u>	<u>key event 13</u>
.422863E+00	.294404E+00	.282732E+00

Program CASH is then run to determine an expected profit when given a particular bid strategy. Table 15 shows an output file from program CASH displaying a possible bid and its associated expected profit.

Table 15. Output File from Program CASH for Example 15.1.1

<u>Period</u>		<u>Interest*</u>	<u>Cash Balance**</u>
I = 1		IBA = 4.363	CASH = -1.781847
I = 2		IBA = 8.444	CASH = -4414.447
I = 3		IBA = 11.785	CASH = -6111.147
I = 4		IBA = 14.617	CASH = -7411.447
I = 5		IBA = 9.059	CASH = -4414.447
I = 6		IBA = 10.299	CASH = -51184.632
I = 7		IBA = 11.741	CASH = -61184.632
I = 8		IBA = 12.719	CASH = -6645.818
I = 9		IBA = 7.715	CASH = -4414.447
I = 10		IBA = 1.288	CASH = -6111.447
I = 11		IAF = 1.509	CASH = 1156.367
I = 12		IAF = 1.711	CASH = 1311.577
I = 13		IAF = 1.715	CASH = 1314.115
I = 14		IAF = 1.717	CASH = 1315.822

TERMINAL CASH POSITION = 3525.580

*IBA -- interest on money borrowed,
IAF -- interest on money deposited.

**Cash balance at end of period.

-----BID PACKAGE-----

0.00 RECEIVED AT PROJECT START

KEY EVENT 4
 BID LEVEL = 7715.31
 DELIVERY DATE = 21.00
 LATE PENALTY = .00

Table 15 (Continued)

KEY EVENT 10
BID LEVEL = 5369.42
DELIVERY DATE = 46.00
LATE PENALTY = .00

KEY EVENT 11
BID LEVEL = 5153.71
DELIVERY DATE = 47.00
LATE PENALTY = 10.00

EXPECTED PROFIT = -1200

EXPECTED PROFIT COMBINED = -1200

UNDER THE NEW CONSTRAINTS:

INITIAL CAPITAL = 500.00

INTEREST RATE ON MONEY DEPOSIT = 1.00%

INTEREST RATE ON MONEY BORROWED = 1.50%

RETENTION RATE = .1200*

6.5 Discussion of Program

A question often raised about problem solutions is the efficiency of the procedure. Obviously, a Monte Carlo simulation, for a network of practical size, will have a long run time. Yet, considering that the program will be run only once for a particular project, the cost incurred will most likely be outweighed by the information obtained from the run.

The example problem (13 nodes, 16 activities, and a sample size of 18,496) ran for approximately 270 minutes on an AT&T PC 6300. This was slightly more than 1 sample per second. Obviously, a more powerful computer would reduce run time considerably.

Programs AN-IN, AN-COST, and CASH have storage requirements of 94,264, 124,816, and 92,196 bytes, respectively, and were programmed on a PC with 640K RAM.

7. CONCLUSION AND DIRECTION FOR FUTURE RESEARCH

In the arena of project bidding, it is essential to submit a bid that will be competitive yet gainful to the bidder. For this reason, it is important that the manager have accurate and complete information on the project on which he is bidding. The computer package developed in this work gives the manager the distributions of duration and cost at the key events of the project, as well as the expected cash flow arising from the project execution. It also will assist him in cash flow calculations, and in the preparation of a bid package.

Application of AN theory to project bidding is an area of research that has been mostly ignored to this date. This work represents only the beginning of research in the area and needs empirical evidence to validate many of the assumptions of the model. A logical next step would be to approach the problem via analytical approximation as opposed to approximation by Monte Carlo simulation.

Further down the road, once the question of the determination of a bid has been satisfactorily investigated, is the problem of investment of additional resources in the project to yield earlier delivery dates for one or more of the key events of the project. This may be necessary in order to obtain the contract in a competitive environment if the delivery date is the overriding consideration. This problem goes deeper than the problem of optimal time-cost

trade-offs in directed acyclic networks because of the cash flow problem when determining a bid. The time-cost trade-off problem has not, to this date, been satisfactorily addressed in the case of probabilistic ANs.

Finally, a complete model of bidding should be cast in a game-theoretic framework, which has not been addressed in this thesis (here, we assumed a one-against-all model). This would take into account many factors such as the number of competitors bidding for the project, potential profit and loss functions, as well as multiple projects. The end result would be an overall bid strategy for the entire scope of many projects.

8. REFERENCES

1. Badger, Albert A. (1974). "Interrelating Project Estimates to CPM Schedules." AACE Transactions of the 18th National Meeting, 18, 38-42.
2. Case, Kenneth E. (1972). "On the Consideration of Variability in Cost Estimating." IEEE Transactions on Engineering Management, 19, No. 4, 114-118.
3. Dodin, Bajis M. (1982). "On the Completion Time of Stochastic PERT Networks." Unpublished Ph.D. Dissertation, N.C. State University.
4. Dodin, Bajis M., and Salah E. Elmaghraby (1985). "Approximating the Criticality Indices of the Activities in PERT Networks." Management Science, 31, No. 2, 207-223.
5. Elmaghraby, Salah E. (1977). Activity Networks: Project Planning and Control by Network Models, John Wiley & Sons, New York.
6. Elmaghraby, Salah E. (1986). "The Estimation of Some Network Parameters in the PERT Model of Activity Networks: Review and Critique", OR Report No. 207, North Carolina State Univ., Raleigh, NC.
7. Elmaghraby, Salah E. (1986). "Optimal Bidding Strategies in Project Activities", Research Proposal, North Carolina State University, Raleigh, NC.
8. Farid, Foad, and L. T. Boyer. (1985). "Fair and Reasonable Markup (FaRM) Pricing Model." Journal of Construction Engineering and Management, 111, No. 4, 374-390.
9. Hoel, Paul G. (1954). Introduction to Mathematical Statistics, third edition, John Wiley & Sons, New York.
10. Kleindorfer, G.B. (1971). "Bounding distributions for a stochastic acyclic network," Operations Research, 19, 1596-1601.
11. Massey, Frank, J, Jr. (1951). "The Kolmogorov-Smirnov Test for Goodness of Fit." Journal of the American Statistical Association, 46, 68-78.
12. Ross, Sheldon (1984). A First Course in Probability, Macmillan Publishing Company, New York.

13. Russell, Robert A. (1986). "A Comparison of Heuristics for Scheduling Projects With Cash Flows and Resource Restrictions," Management Science, 32, 1291-1300.
14. Smirnov, N. (1948). "Table for Estimating the Goodness of Fit of Empirical Distributions," Annals of Mathematical Statistics, 19, 279-281.

9. Appendix

Appendix 9.1. Program Listing of ANC-IN

```

C
C
      CALL  REED8(NOI)
      DO  6 I=1,NOI
      CALL  REED9(I,NULT(I),NDS(I),NT(I))
C
      DO  7 I=1,NOI
      IF(NDS(I).NE.7)      THEN
          CALL  REED10(I,NDS(I),AA(I),BB(I),CC(I),DD(I))
      ELSE
          DO 12 J=1,NT(I)
          CALL  REED11(I,J,T(I,J),PT(I,J))
      ENDIF
      7    CONTINUE
C
      K=0
      DO  8 I=1,NOI
          IF(I.GT.1)      K=NULT(I-1)
      DO  9 II=K+1,NULT(I)
          WRITE(3,203)    NS(II),NE(II),NDS(II),NT(II)
          IF(NDS(II).NE.7)      THEN
              WRITE(3,205)AA(II),BB(II),CC(II),DD(II)
          ELSE
              WRITE(3,205)(T(II,J),PT(II,J),J=1,NT(II))
          ENDIF
      9    CONTINUE
      8    CONTINUE
C
C ****
C       OBTAIN DURATION INFO. IF NETWORK IS NOT GENERATED
C ****
C
      ELSE
          DO 22 I=1,M
          CALL  REED12(I,NS(I),NE(I),NDSTT(I),NR(I))
          IF(NDSTT(I).NE.7)      THEN
              CALL  REED14(I,NDSTT(I),EX(I),STDX(I),VMIN(I),VMAX(I))
          ELSE
              DO 11 J=1,WR(I)
              CALL  REED15(I,J,R(I,J),PR(I,J))
          ENDIF
          22    CONTINUE
          DO 102 I=1,M
          WRITE(3,203)    NS(I),NE(I),NDSTT(I),NR(I)
          IF(NDSTT(I).NE.7)      THEN
              WRITE(3,205)EX(I),STDX(I),VMIN(I),VMAX(I)
          ELSE
              WRITE(3,205)(R(I,J),PR(I,J),J=1,WR(I))
          ENDIF
          102   CONTINUE
C
C ****
C      WHAT ACT
C      WHAT THIS PROGRAM WILL ASK YOU FOR DATA TO RUN '.,.

```

&5X,'AN-COST. IT DOES SOME PRELIMINARY CHECKS AND PUTS THE '.,/
&5X,'DATA INTO A FILE.',//,
&5X,'GIVE A NAME FOR THAT FILE',//,
&5X,'THE NAME SHOULD BE OF FOUR CHARACTERS AND THERE SHOULD',//,
&5X,'BE TWO ADDITIONAL CHARACTERS AT THE BEGINNING ',//,
&5X,'SPECIFYING THE DRIVE.',//,
&5X,'AN EXAMPLE IS B:PRES',//,
&5X,'HOPE THE FILE DOES NOT ALREADY EXIST')
201 FORMAT(11)
202 FORMAT(F5.3,10I5)
203 FORMAT(14I5)
205 FORMAT(6E11.4)
C
C *****
C PROGRAM AREA TO OBTAIN DATA ON ACTIVITY COST
C *****
C
C WRITE(*,303)
303 FORMAT(5(/),5X,'NOW YOU WILL BE ASKED FOR INFORMATION ON THE',
&5X,'COST DISTRIBUTIONS OF THE ACTIVITIES IN THE NETWORK',
IF (NANG.NE.1) THEN
C
C *****
C --CASE WHEN ACTIVITY NETWORK IS NOT GENERATED BY PRE-GEN
C *****
C
DO 33 I=1,M
CALL REFD16 (NSCL,NE,N1,N2,M1,M2,N1A,N2A)
CALL REFD17 (F1,F2,VN,N,VNA)
33 CONTINUE
C
C *****
C *****

```

        WRITE(3,205)    FC(I),DM(I),P1(I),VMIN(I),VMAX(I)
99      CONTINUE
98      CONTINUE
C
ENDIF
C
CLOSE(3,STATUS='KEEP')
STOP
END
C ****
C **** SUBROUTINE INFORM ****
C ****
C
WRITE(*,1)
PAUSE
WRITE(*,2)
PAUSE
WRITE(*,4)
PAUSE
FORMAT(5X,'THIS PROGRAM PREPARES THE INPUT FILES FOR PROGRAM //',
65X,'AN COST WHICH DETERMINES BID PRICES FOR PROJECTS //',
65X,'THAT CAN BE MODELED WITH DIRECTED ACYCLIC NETWORKS //',
65X,'THIS PROGRAM HAS THE ADDITIONAL FACILITY FOR //',
610X,1 RANDOM GENERATION OF A NETWORK //,
610X,2 LINKING WITH DODDINS PROGRAM TO DETERMINE DISTRIBUTION,
610X,3 BUTTONS OF NODE REALIZATION TIMES //,
610X,4 DURATION OF ACTIVITIES //,
610X,5 RUN AN COST.EXE, YOU MUST //,
610X,6 CREATE DATA FILE CONTAINING GENERAL INFORMATION,
610X,7 AND DURATION/LOSS INFORMATION USING THIS PROGRAM //,
610X,8 RUN DODDINS.EXE TO DETERMINE MEAN AND VARIANCE
610X,9 OF KEY EVENTS WHICH ARE PUT IN FILE THRE AND
610X,10 THIS WILL ALSO GIVE REAL TIME LIST OF KEY
610X,11 EVENTS //,
610X,12 RUN AN COST.EXE //,
FURMA COST PROGRAM                      AN INPUT //,
65X,B7
610X,13 USESE                         VOLTMANN //,
65X
65X,14 ADVISOR OR S E E.MAGHRABY //,
FORMAT(5X,'IMITATIONS OF THE PROGRAM //',
610X,1 MAX 100 ARCS //,
610X,2 MAX 50 NODES //,
610X,3 MAX 30 DURATIONS FOR AN ACTIVITY //,
610X,4 DIRECTED ACYCLIC NETWORKS ONLY //)
RETURN
END
C

```

```

C ****
C
C      SUBROUTINE      REED2(NANG)
C
C ****
C      CHARACTER      ISTOP*1
C      WRIT(E*,1)
1      FORMAT(5X,'WOULD      YOU      LIKE      TO      GENERATE      A      RANDOM      NETWORK      ?',//,
85X,'IF      SO,      TYPE      IN      Y      ',/,,
85X,'IF      NOT,      TYPE      IN      N      .THIS      MEANS      YOUR      NETWORK      IS      READY.',/,,
85X,'TO      STOP,      TYPE      IN      S      ')
      READ(*,2)ISTOP
2      FORMAT(A1)
      IF(ISTOP.EQ.'S'.OR.ISTOP.EQ.'s')                      STOP
      IF(ISTOP.EQ.'Y'.OR.ISTOP.EQ.'y')                      NANG=1
      IF(ISTOP.EQ.'N'.OR.ISTOP.EQ.'n')                      NANG=0
      RETURN
      END
C
C
C ****
C
C      SUBROUTINE      REED3(NCONT)
C
C ****
C
C      CHARACTER      ISTOP*1
C      WRITE(*,1)
1      FORMAT(5X,100,'YOU      HAVE      ACTIVITIES      WITH      CONTINUOUS      DISTRI      ',/,,
85X,'BUTTONS      ?',//,
85X,'IF      SO,      TYPE      IN      Y      ',/,,
85X,'IF      NOT,      TYPE      IN      N      ',/,,
85X,'TO      STOP,      TYPE      IN      S      ')
      READ(*,2)ISTOP
2      FORMAT(A1)
      IF(ISTOP.EQ.'S' .OR. ISTOP.EQ.'s')                      NCONT=1
      IF(ISTOP.EQ.'Y' .OR. ISTOP.EQ.'y')                      NCONT=2
      IF(ISTOP.EQ.'N' .OR. ISTOP.EQ.'n')                      NCONT=3
      RETURN
      END
C
C ****
C
C      SUBROUTINE      REED5(N,M)
C
C ****
C
C      CHARACTER      ISTOP*1
C      WRITE(*,1)
1      FORMAT(5X,'TYPE      IN      THE      #      OF      NODES      AND      THE      #      OF      ARCS      ')
      READ(*,2)N,M
      IF(N.LE.50 .AND. N.GE.2)          GO TO 3

```

```

      WRITE(*,2)
2      FORMAT(5X,'THE      # OF NODES IS OUT OF RANGE.',/,
     &5X,'WOULD YOU LIKE TO TYPE IN THE # OF NODES AND THE',/,
     &5X,'# OF ARCS AGAIN ?',/,
     &5X,'IF SO, TYPE IN Y ',/,
     &5X,'IF NOT, TYPE IN S AND THE PROGRAM WILL STOP.')
      READ(*,6)  ISTOP
6      FORMAT(A1)
      IF(ISTOP.EQ.'Y'.OR.ISTOP.EQ.'y')           THEN
          GO TO 7
      ELSE
          STOP
      ENDIF
3      IF(M.GE.N-1.AND.M.LE.N*(N-1)/2.AND.M.LE.100)      GO TO 8
      WRITE(*,4)
4      FORMAT(5X,'THE      NUMBER OF ARCS IS OUT OF RANGE.',/,
     &5X,'WOULD YOU LIKE TO TYPE IN THE # OF NODES AND THE ',/,
     &5X,'# OF ARCS ?',/,
     &5X,'IF SO, TYPE IN Y ',/,
     &5X,'IF NOT, TYPE IN S AND THE PROGRAM WILL STOP.')
      READ(*,6)  ISTOP
      IF(ISTOP.EQ.'Y'.OR.ISTOP.EQ.'y')           THEN
          GO TO 7
      ELSE
          STOP
      ENDIF
8      RETURN
      END

C
C
C ****
C
      SUBROUTINE REED6(SCAL)
C
C ****
C
      CHARACTER ISTOP*1
      WRITE(*,1)
1      FORMAT(5X,'TYPE      IN THE INTERVAL WIDTH TO BE USED IN THE',
     &5X,'DISCRETIZATION FOR OBTAINING MEAN AND VAR.',/,
     &5X,'A TYPICAL VALUE IS 0.01 TO 1.0')
      READ(*,2)  SCAL
      IF(SCAL.LT.0.01)  THEN
          WRITE(*,2)
          FORMAT(5X,'SCAL      VALUE IS NOT POSITIVE')
          &5X,'WOULD YOU LIKE TO ENTER A CORRECT VALUE ?'
          &5X,'IF YES, TYPE ON Y '
          &5X,'IF NOT, TYPE ON S AND THE PROGRAM WILL STOP.')
          READ(*,3)  SCAL
          IF(SCAL.LT.0.01)  THEN
              FORMAT(5X,'SCAL      VALUE IS NOT POSITIVE')
              &5X,'WOULD YOU LIKE TO ENTER A CORRECT VALUE ?'
              &5X,'IF YES, TYPE ON Y '
              &5X,'IF NOT, TYPE ON S AND THE PROGRAM WILL STOP.')
          ENDIF
      ENDIF
      END

```

```

STOP
ENDIF
ELSE
ENDIF
RETURN
END

C
C
C ****
C
SUBROUTINE REED7(KEY,KEYN,NRR,N)
C
C ****
C
DIMENSION KEYN(50)
CHARACTER ISTOP*1,OK*1
4 WRITE(*,1)
1 FORMAT(5X,'TYPE      IN THE NUMBER OF ORDERED PAIRS IN THE ',/,
&5X,'APPROXIMATE DISTRIBUTION.',/)
READ(*,*)NRR
IF(NRR.GT.30.OR.NRR.LE.0)      THEN
WRITE(*,8)
8 FORMAT(5X,'VALUE OF NRR OUT OF RANGE',/,
&5X,'WOULD YOU LIKE TO INPUT CORRECTED VALUE ?',/,
&5X,'IF SO TYPE IN Y ',/,
&5X,'IF NOT, TYPE IN N AND THE PROGRAM WILL STOP.')
READ(*,7)ISTOP
7 FORMAT(A1)
IF(ISTOP.EQ.'Y'.OR.ISTOP.EQ.'y')      THEN
GO TO 4
ELSE
STOP
ENDIF
ELSE
ENDIF

C
5 WRITE(*,2)
2 FORMAT(5X,'TYPE      IN THE # OF MILESTONES OR KEY NODES IN',/,
&5X,'THE PROJECT.')
READ(*,*)KEY
IF(KEY.LT.1.OR.KEY.GT.N.OR.KEY.GT.50)      THEN
WRITE(*,9)
9 FORMAT(5X,'VALUE OF KEY OUT OF RANGE',/,
&5X,'WOULD YOU LIKE TO TYPE IN CORRECTED VALUE ?',/,
&5X,'IF SO, TYPE IN Y ',/,
&5X,'IF NOT, TYPE IN N AND THE PROGRAM WILL STOP.')
READ(*,7)ISTOP
IF(ISTOP.EQ.'Y'.OR.ISTOP.EQ.'y')      THEN
GO TO 5
ELSE
STOP
ENDIF
ELSE

```

```

        ENDIF
C
6      WRITE(*,3)
3      FORMAT(5X,'TYPE      IN THE LIST OF KEY NODES IN ASCENDING ORDER.',/)
READ(*,*)(KEYN(I),I=1,KEY)
OK='Y'
IF(KEYN(1).LE.0)      OK='N'
IF(KEYN(KEY).NE.N)    OK='N'
DO 11 I=2,KEY
J=I-1
IF(KEYN(J).GE.KEYN(I))   OK='N'
11    CONTINUE
IF(OK.EQ.'N'.OR.OK.EQ.'n')      THEN
      WRITE(*,10)
10    FORMAT(5X,'VALUES      OF KEY NODES INCORRECT',/,
&5X,'EITHER FIRST KEY NODE IS LE 0',/,
&5X,'OR LAST KEY NODE IS NE N',/,
&5X,'OR KEY NODES NOT IN ASCENDING ORDER',/,
&5X,'WOULD YOU LIKE TO INPUT THE NODES AGAIN ?',/,
&5X,'IF SO, TYPE IN Y ',/,
&5X,'IF NOT TYPE IN N AND THE PROGRAM WILL STOP.')
      READ(*,7)  ISTOP
      IF(ISTOP.EQ.'Y'.OR.ISTOP.EQ.'y')      THEN
          GO TO 6
      ELSE
          STOP
      ENDIF
      ELSE
      ENDIF
      RETURN
END
C
C
C ****
C
C      SUBROUTINE HALT
C
C ****
C
CHARACTER ISTOP*1
WRITE(*,1)
1      FORMAT(5X,'WOLUD YOU LIKE TO CONTINUE OR WOULD YOU LIKE',/,
&5X,'TO STOP ?',/,
&5X,'TO CONTINUE,TYPE IN Y ',/,
&5X,'TO STOP, TYPE IN S ')
      READ(*,2)  ISTOP
2      FORMAT(A1)
      IF(ISTOP.EQ.'S' .OR.ISTOP.EQ.'s')      STOP
      RETURN
END
C
C ****

```

```

C
      SUBROUTINE      REED8(NOI)

C ****
C
C      CHARACTER      ISTOP*1
3     WRITE(*,1)
1     FORMAT(5X,'IT      IS ASSUMED      THAT THE ACTIVITY      OF THE NETWORK',//,
&5X,'CAN      BE DIVIDED      INTO SEVERAL      PARTITIONS.      EACH PARTITION',//,
&5X,'IS      REPRESENTED      BY AN ACTIVITY      NUMBER      WHICH IS THE',//,
&5X,'UPPER      LIMIT      OF THE PARTITION.      EACH PARTITION      HAS A',//,
&5X,'DIFFERENT      TYPE      OF DISTRIBUTION',//,
&5X,'TYPE      IN THE NUMBER      OF PARTITIONS')
      READ(*,*)      NOI
      IF(NOI.LE.0)      THEN
      WRITE(*,2)
2     FORMAT(5X,'THE      NUMBER      OF PARTITIONS      IS NOT A POSITIVE     ',//,
&5X,'NUMBER',//,
&5X,'WOULD      YOU LIKE      TO RE-ENTER      THE NUMBER      OF PARTITIONS',//,
&5X,'IF      SO,      TYPE      IN Y     ',//,
&5X,'IF      NOT,      TYPE      IN S      AND      THE PROGRAM      WILL      STOP.')
      READ(*,4)ISTOP
4     FORMAT(A1)
      IF(ISTOP.EQ.'Y'.OR.ISTOP.EQ.'y')      THEN
      GO TO 3
      ELSE
      STOP
      ENDIF
      ELSE
      ENDIF
5     RETURN
      END
C
C ****
C
      SUBROUTINE      REED9(I,NULT,NDS,NT)

C ****
C
C      CHARACTER      ISTOP*1,      OK*1
4     WRITE(*,1)
1     FORMAT(5X,'NEXT      FOR EACH PARTITION,      TYPE      IN THE FOLLOWING',//,
&5X,'3      QUANTITIES      IN SERIAL ORDER',//,
&5X,'      A.      NULT:      IT      IS THE NUMBER      OF THE ACTIVITY      REPRESENT-',//,
&5X,'      ING THE UPPER      LIMIT      OF THE PARTITION',//,
&5X,'      B.      NDS :      IT      IS THE TYPE      OF DISTRIBUTION      OF THE',//,
&5X,'      ACTIVITY      DURATIONS      IN THIS PARTITION',//,
&5X,'          FOR      UNIFORM      DISTN.,      NDS=1',//,
&5X,'          FOR      TRIANGULAR      DISTN.,      NDS=2',//,
&5X,'          FOR      NORMAL      DISTN.,      NDS=3',//,
&5X,'          FOR      EXPONENTIAL      DISTN.,      NDS=4',//,
&5X,'          FOR      GAMMA      DISTN.,      NDS=5',//,

```

```

&5X,'          FOR BETA DISTN.,           NDS=6',//,
&5X,'          FOR DISCRETE DISTN.,      NDS=7',//,
&5X,'          NDS=7 FOR ANY DISTN. REPRESENTED BY',//,
&5X,'          A SET OF FINITE ORDERED PAIRS',//,
&5X,'          C. NT : IT IS THE # OF ORDERED PAIRS IF NDS=7,//,
&5X,'          IF NDS IS NOT EQUAL TO 7, NT=0)

      WRITE(*,3) I
3     FORMAT(5X,'TYPE      IN THE VALUES OF NULT, NDS AND NT',//,
&5X,'FOR THE PARTITION NO.',I2)
      READ(*,*)NULT,NDS,NT
      CALL CHECK4(NULT,OK,ISTOP)
      IF(OK.EQ.'N'.OR.OK.EQ.'n')      THEN
          IF(ISTOP.EQ.'Y'.OR.ISTOP.EQ.'y')      THEN
              GO TO 4
          ELSE
              STOP
          ENDIF
      ELSE
          ENDIF
          CALL CHECK3(NDS,NT,OK,STOP)
          IF(OK.EQ.'N'.OR.OK.EQ.'n')      THEN
              IF(ISTOP.EQ.'Y'.OR.ISTOP.EQ.'y')      THEN
                  GO TO 4
              ELSE
                  STOP
              ENDIF
          ELSE
              ENDIF
          RETURN
      END

C
C
C ****
C
C      SUBROUTINE REED10(I,IT,EX,STDX,VMIN,VMAX)
C
C ****
C
      CHARACTER ISTOP*1, OK*1
4     WRITE(*,1) I
1     FORMAT(5X,'TYPE      IN THE VALUES OF EX, STDX',//,
&5X,'VMIN, VMAX, FOR THE ACTIVITIES IN PARTITION NO. ',I2,//,
&10X,'THE PARAMETERS ARE EXPLAINED BELOW://,
&5X,'DISTRIBUTION INDEX EX STDX REMARKS',//,
&5X,' UNIFORM      1  0.0  0.0      ',//,
&5X,' TRIANGULAR    2  M  0.0      ',//,
&5X,' NORMAL        3  MEAN  S.D.      ',//,
&5X,' EXPONENTIAL   4  MEAN      ',//,
&5X,' GAMMMA        5  ALPHA  BETA      ',//,
&5X,' BETA          6  ALPHA  BETA      ',//,
&5X,'VMIN IS THE MINIMUM VALUE OF THE RANDOM VARIABLE',//,
&5X,'IT IS USUALLY DECIDED BY THE CRITERION://,
&5X,'P(Y.LE.VMIN)=0.0005.',/

```

```

&5X,'VMAX IS THE MAXIMUM VALUE OF THE RANDOM VARIABLE.',/,
&5X,'IT IS DECIDED USUALLY BY THE CRITERION:-',/,
&5X,'P(Y.GE.VMAX)=0.0005.')
READ(*,*) EX,STDX,VMIN,VMAX
CALL CHECK1(IT,EX,STDX,VMIN,VMAX,OK,ISTOP)
IF(OK.EQ.'N'.OR.OK.EQ.'n') THEN
    IF(ISTOP.EQ.'Y'.OR.ISTOP.EQ.'y') THEN
        GO TO 4
    ELSE
        STOP
    ENDIF
ELSE
ENDIF
RETURN
END

C
C
C ****
C
SUBROUTINE REED11(I,J,R,PR)
C
C ****
C
CHARACTER ISTOP*1
3 WRITE(*,1) J,I
1 FORMAT(5X,'TYPE IN THE',I2,'TH PAIR OF ACTIVITY DURATION',/,
&5X,'AND PROBABILITY FOR PARTITION NO. ',I2,/)

READ(*,*) R,PR
IF(R.LE.0.0.OR.PR.LT.0.0.OR.PR.GT.1.0) THEN
    WRITE(*,2)
2 FORMAT(5X,'THE VALUES OF DURATION AND/OR PROBABILITY',/,
&5X,'ARE OUT OF RANGE',/,

&5X,'WOULD YOU LIKE TO INPUT CORRECTED VALUES ? ',/)

&5X,'IF SO, TYPE IN Y',/
&5X,'IF NOT, TYPE IN S AND THE PROGRAM WILL STOP.')
READ(*,4) ISTOP
4 FORMAT(A1)
IF(ISTOP.EQ.'Y'.OR.ISTOP.EQ.'y') THEN
    GO TO 3
ELSE
    STOP
ENDIF
ELSE
ENDIF
RETURN
END

C
C
C ****
C
SUBROUTINE REED12(J,N,NS,NS1,NS2)
C
C ****

```

```

C
      CHARACTER    ISTOP*1,    OK*1
6     WRITE(*,1)    I
1     FORMAT(5X,'FOR      ACTIVITY   ',I2,' READ IN THE PARAMETERS',//,
&5X,'NS,    NE, NDSTT, NR IN THAT ORDER',//,
&5X,' A. NS : STARTING NODE',//,
&5X,'B.    NE : ENDING NODE',//,
&5X,'C.    NDSTT: IT IS THE TYPE OF DISTRIBUTION OF THE',//,
&5X,'          DURATION OF THE ACTIVITY',//,
&5X,'          FOR UNIFORM DISTN.,      NDSTT=1',//,
&5X,'          FOR TRIANGULAR DISTN.,    NDSTT=2',//,
&5X,'          FOR NORMAL DISTN.,      NDSTT=3',//,
&5X,'          FOR EXPONENTIAL DISTN., NDSTT=4',//,
&5X,'          FOR GAMMA DISTN.,       NDSTT=5',//,
&5X,'          FOR BETA DISTN.,        NDSTT=6',//,
&5X,'          FOR DISCRETE DISTN.,     NDSTT=7,//,
&5X,'          NDS=7 FOR ANY DISTN. REPRESENTED BY',//,
&5X,'          A SET OF FINITE ORDERED PAIRS',//,
&5X,'          C. NR : IT IS THE # OF ORDERED PAIRS IF NDSTT=7',//,
&5X,'          IF NDSTT IS NOT EQUAL TO 7, NR=0')
READ(*,*)    NS,NE,NDSTT,NR
CALL    CHECK2(NS,NE,OK,ISTOP)
IF(OK.EQ.'N'.OR.OK.EQ.'n')      THEN
  IF(ISTOP.EQ.'Y'.OR.ISTOP.EQ.'y')      THEN
    GO TO 6
  ELSE
    STOP
  ENDIF
ELSE
ENDIF
CALL    CHECK3(NDSTT,NR,OK,ISTOP)
IF(OK.EQ.'N'.OR.OK.EQ.'n')      THEN
  IF(ISTOP.EQ.'Y'.OR.ISTOP.EQ.'y')      THEN
    GO TO 6
  ELSE
    STOP
  ENDIF
ELSE
ENDIF
END

```

```

&10X,'THE PARAMETERS ARE EXPLAINED BELOW://,
&5X,'DISTRIBUTION INDEX EX STDX REMARKS',//,
&5X,' UNIFORM 1 0.0 0.0 //,
&5X,' TRIANGULAR 2 M 0.0 //,
&5X,' NORMAL 3 MEAN S.D. //,
&5X,' EXPONENTIAL 4 MEAN //,
&5X,' GAMMMA 5 ALPHA BETA //,
&5X,' BETA 6 ALPHA BETA //,
&5X,'VMIN IS THE MINIMUM VALUE OF THE RANDOM VARIABLE.//,
&5X,'IT IS USUALLY DECIDED BY THE CRITERION:-//,
&5X,'P(Y.LE.VMIN)=0.0005.//,
&5X,'VMAX IS THE MAXIMUM VALUE OF THE RANDOM VARIABLE.//,
&5X,'IT IS DECIDED USUALLY BY THE CRITERION:-//,
&5X,'P(Y.GE.VMAX)=0.0005.//
      READ(*,*) EX,STDX,VMIN,VMAX
      CALL CHECK1(IT,EX,STDX,VMIN,VMAX,OK,ISTOP)
      IF(OK.EQ.'N'.OR.OK.EQ.'n') THEN
        IF(ISTOP.EQ.'Y'.OR.ISTOP.EQ.'y') THEN
          GO TO 4
        ELSE
          STOP
        ENDIF
      ELSE
        ENDIF
      RETURN
    END

```

.....
SUBROUTINE CHECK1(I,EX,STDX,VMIN,VMAX)

```

CHARACTER STDX*10
      I=1
      EX=0.0
      STDX=' '
      VMIN=0.0
      VMAX=1.0
      OK='N'
      ISTOP=' '
      DO 100 I=1,10
        READ(*,*) I,EX,STDX,VMIN,VMAX,OK,ISTOP
        IF(I.EQ.1) THEN
          IF(OK.EQ.'N'.OR.OK.EQ.'n') THEN
            IF(ISTOP.EQ.'Y'.OR.ISTOP.EQ.'y') THEN
              GO TO 4
            ELSE
              STOP
            ENDIF
          ELSE
            ENDIF
          RETURN
        ENDIF
        IF(I.EQ.2) THEN
          IF(VMIN.LT.0.0) THEN
            WRITE(*,*) 'VMIN IS LESS THAN ZERO'
            STOP
          ENDIF
        ENDIF
        IF(I.EQ.3) THEN
          IF(VMAX.LT.0.0) THEN
            WRITE(*,*) 'VMAX IS LESS THAN ZERO'
            STOP
          ENDIF
        ENDIF
        IF(I.EQ.4) THEN
          IF(VMIN.GE.VMAX) THEN
            WRITE(*,*) 'VMIN IS GREATER THAN OR EQUAL TO VMAX'
            STOP
          ENDIF
        ENDIF
        IF(I.EQ.5) THEN
          IF(VMIN.LT.0.0) THEN
            WRITE(*,*) 'VMIN IS LESS THAN ZERO'
            STOP
          ENDIF
        ENDIF
        IF(I.EQ.6) THEN
          IF(VMAX.LT.0.0) THEN
            WRITE(*,*) 'VMAX IS LESS THAN ZERO'
            STOP
          ENDIF
        ENDIF
        IF(I.EQ.7) THEN
          IF(VMIN.GE.VMAX) THEN
            WRITE(*,*) 'VMIN IS GREATER THAN OR EQUAL TO VMAX'
            STOP
          ENDIF
        ENDIF
        IF(I.EQ.8) THEN
          IF(VMIN.LT.0.0) THEN
            WRITE(*,*) 'VMIN IS LESS THAN ZERO'
            STOP
          ENDIF
        ENDIF
        IF(I.EQ.9) THEN
          IF(VMAX.LT.0.0) THEN
            WRITE(*,*) 'VMAX IS LESS THAN ZERO'
            STOP
          ENDIF
        ENDIF
        IF(I.EQ.10) THEN
          IF(VMIN.GE.VMAX) THEN
            WRITE(*,*) 'VMIN IS GREATER THAN OR EQUAL TO VMAX'
            STOP
          ENDIF
        ENDIF
      100 CONTINUE
    END

```

```

      ELSE
      ENDIF
      RETURN
      END

C
C ****
C
C
      SUBROUTINE REED16(I,NS,NE,NDSTT,FC,DM)
C
C ****
C
C
      6  WRITE(*,1) I,NS,NE
      1  FORMAT(5X,'FOR ACTIVITY ',I2,' FROM NODE ',I3,' TO NODE ',I3,',
     &5X,'INPUT THE FOLLOWING PARAMETERS:',//,
     &5X,'A.   FC : FIXED COST FOR ACTIVITY',/,
     &5X,'B.   DM : CONSTANT MULTIPLIER ON DURATION',/,
     &5X,'C.   NDSTT: IT IS THE TYPE OF DISTRIBUTION OF THE ',/,
     &5X,'          COST ABOUT <Y*DM>.',/,
     &5X,'          FOR CONSTANT*DUR.,           NDSTT=1',/,
     &5X,'          FOR NORMAL DISTN.,          NDSTT=2',/,
     &5X,'          FOR UNIFORM DISTN.,         NDSTT=3',/,
     &5X,'          FOR TRIANGULAR DIST.,       NDSTT=4',/)
      READ(*,*) FC,DM,NDSTT
      IF (FC.LT.0.0.OR.DM.LT.0.0)          GOTO 6
      IF (NDSTT.LT.1.OR.NDSTT.GT.4)        GOTO 6
C
      RETURN
      END

C
C ****
C
C
      SUBROUTINE REED17(I,P1,VMIN,VMAX)
C
C ****
C
C
      *  WRITE(*,1) I
      *  FORMAT(5X,'TYPE IN THE VALUES OF P1',/,
     &5X,'VMIN, VMAX, FOR THE ACTIVITY NO. ',I2,',
     &5X,'THE PARAMETERS ARE EXPLAINED BELOW:',//,
     &5X,'DISTRIBUTION INDEX P1 ',//,
     &5X,'CONSTANT 1 0.0 ',//,
     &5X,'NORMAL 2 VAR ',//,
     &5X,'UNIFORM 3 0.0 ',//,
     &5X,'TRIANGULAR 4 0.0 ',//,
     &5X,'VMIN IS THE MINIMUM VALUE OF THE RANDOM VARIABLE',/,
     &5X,'P1 IS USUALLY DECIDED BY THE CRITERION ',/,
     &5X,'P1 IS 0.000000005 ',/,
     &5X,'VMAX IS THE MAXIMUM VALUE OF THE RANDOM VARIABLE',/,
     &5X,'P1 IS DECIDED USUALLY BY THE CRITERION ',/,
     &5X,'P1 IS 0.000000005 ',/
      READ(*,*) P1,VMIN,VMAX
      *  WRITE(*,1) 'VMIN <= P1 <= VMAX'

```

```

      RETURN
      END

C
C ****
C
C      SUBROUTINE      REED18(I,FC,DM,NDS)
C
C ****
C
      CHARACTER      ISTOP*1,      OK*1
      WRITE(*,1)
      1 FORMAT(5X,'NEXT      FOR EACH PARTITION,      TYPE IN THE FOLLOWING',//,
      &5X,' 3 QUANTITIES      IN SERIAL ORDER://,
      &5X,'    A. FC : FIXED COST FOR ACTIVITIES      IN THIS PAR-//,
      &5X,'          TITION.//,
      &5X,'    B. DM : CONSTANT MULTIPLIER      ON DURATION//,
      &5X,'          (DURATION*DM      IS THE MEAN OF THE COST)//,
      &5X,'          DISTRIBUTION.//,
      &5X,'    C. NDS : IT IS THE TYPE OF DISTRIBUTION      OF THE//,
      &5X,'          COST ABOUT <DM>//,
      &5X,'          FOR CONSTANT*DUR.,          NDS=1//,
      &5X,'          FOR NORMAL DIST.,          NDS=2//,
      &5X,'          FOR UNIFORM DISTN.,          NDS=3//,
      &5X,'          FOR TRIANGULAR DIST.,          NDS=4////)
      WRITE(*,3)      I
      3 FORMAT(5X,'TYPE      IN THE VALUES      OF FC, DM, AND NDS//,
      &5X,'FOR      THE PARTITION      NO.',I2)
      READ(*,*)FC,DM,NDS
      IF(NDS.GT.4.OR.NDS.LT.1)      GOTO 4
      IF(FC.LT.0.0.OR.DM.LT.0.0)      GOTO 4
      RETURN
      END

C
C ****
C
C      SUBROUTINE      REED19(I,P1,VMIN,VMAX)
C
C ****
C
      WRITE(*,1)
      1 FORMAT(5X,'TYPE      IN THE VALUES      OF P1, VMIN, VMAX//,
      &5X,'VMIN,      VMAX,      FOR THE ACTIVITY //,
      &10X,'THE      PARAMETERS      ARE EXPRESSED AS //,
      &5X,'DISTRIBUTION      INDEX      OF //,
      &5X,'    CONST*Y      '),
      &5X,'    NORMAL      '),
      &5X,'    UNIFORM      '),
      &5X,'    TRIANGULAR      '),
      &5X,'    UNIF.        '),
      &5X,'    CONST*Y      '),
      &5X,'    NORMAL      '),
      &5X,'    UNIFORM      '),
      &5X,'    TRIANGULAR      ')

```

ND-9176 909


PROJECT BIDDING UNDER CHANCE TIME ESTIMATES(U) AIR
FORCE INST OF TECH WRIGHT-PATTERSON AFB OH
R S VOGTMANN 1986 AFIT/CI/MR-87-32T


2/2

UNCLASSIFIED

F/6 5/1

NL





MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS - 1963 - A

```

&5X,'IT IS DECIDED USUALLY BY THE CRITERION:-',/
&5X,'P(Y.GE.VMAX)=0.0005.')
READ(*,*) P1,VMIN,VMAX
IF (P1.LT.0.0.OR.VMIN.LT.0.0.OR.VMAX.LT.VMIN) GOTO 4
RETURN
END

C
C ****
C
C      SUBROUTINE CHECK1(IT,EX,STDX,VMIN,VMAX,OK,ISTOP)
C ****
C
CHARACTER ISTOP*1,OK*1
OK='Y'
IF(VMIN.LE.0.0.OR.VMAX.LE.VMIN) THEN
  OK='N'
ELSE IF(IT.EQ.3) THEN
  IF(EX.LE.VMIN.OR.EX.GE.VMAX.OR.STDX.LE.0.0) THEN
    OK='N'
  ELSE
    ENDIF
  ELSE IF(IT.EQ.4) THEN
    IF(EX.LE.VMIN.OR.EX.GE.VMAX) THEN
      OK='N'
    ELSE
      ENDIF
    ELSE IF(IT.EQ.5.OR.IT.EQ.6) THEN
      IF(EX.LE.0.0.OR.STDX.LE.0.0) THEN
        OK='N'
      ELSE
        ENDIF
    ELSE
      ENDIF
    C
    IF(OK.EQ.'N'.OR.OK.EQ.'n') THEN
      WRITE(*,1)
      1 FORMAT(5X,'SOME OF THE VALUES ARE OUT OF RANGE',/,
      &5X,'WOULD YOU LIKE TO INPUT THE CORRECTED VALUES ?',/,
      &5X,'IF SO, TYPE IN Y ',/,
      &5X,'IF NOT, TYPE IN N AND THE PROGRAM WILL STOP.')
      READ(*,2) ISTOP
      2 FORMAT(A1)
      ELSE
      ENDIF
      RETURN
      END
C
C ****
C
C      SUBROUTINE CHECK2(NS,NE,OK,ISTOP)

```

```

C
C ****
C
      CHARACTER      OK*1,    ISTOP*1
      OK='Y'
      IF(NS.LE.0.OR.NE.LE.0.OR.NE.LE.NS)           THEN
          OK='N'
      ELSE
      ENDIF
C
      IF(OK.EQ.'N'.OR.OK.EQ.'n')      THEN
          WRITE(*,1)
 1     FORMAT(5X,'STARTING      AND/OR      ENDING      NODES      IS      INCORRECT',//,
 &5X,'WOULD      YOU      LIKE      TO      INPUT      THE      CORRECT      VALUES      ?',//,
 &5X,'IF      SO,      TYPE      IN      Y      ',/,
 &5X,'IF      NOT,      TYPE      IN      N      AND      THE      PROGRAM      WILL      STOP.')
          READ(*,2)    ISTOP
 2     FORMAT(A1)
      ELSE
      ENDIF
      RETURN
      END
C
C ****
C
      SUBROUTINE      CHECK3(NDS,NR,OK,ISTOP)
C
C ****
C
      CHARACTER      OK*1,    ISTOP*1
      OK='Y'
      IF(NDS.LT.1.OR.NDS.GT.7)           THEN
          OK='N'
      ELSE IF (NDS.EQ.7.AND.NR.EQ.0)      THEN
          OK='N'
      ELSE
      ENDIF
C
      IF(OK.EQ.'N'.OR.OK.EQ.'n')      THEN
          WRITE(*,1)
 1     FORMAT(5X,'VALUES      OF      DISTRIBUTION      TYPE      AND/OR      ',/,
 &5X,'NO.      OF      PAIRS      IS      INCORRECT',//,
 &5X,'WOULD      YOU      LIKE      TO      INPUT      THE      CORRECT      VALUES      ?',//,
 &5X,'IF      SO,      TYPE      IN      Y      ',/,
 &5X,'IF      NOT,      TYPE      IN      N      AND      THE      PROGRAM      WILL      STOP.')
          READ(*,2)    ISTOP
 2     FORMAT(A1)
      ELSE
      ENDIF
      RETURN
      END
C

```

```

C
C ****
C
C      SUBROUTINE      CHECK4(NULT,OK,ISTOP)
C
C ****
C
C      CHARACTER      OK*1,    ISTOP*1
C      OK='Y'
C      IF(NULT.LE.0)      THEN
C          OK='N'
C      ELSE
C      ENDIF
C
C      IF(OK.EQ.'N'.OR.OK.EQ.'n')           THEN
C          WRITE(*,1)
1       FORMAT(5X,'VALUE      OF NULT IS INCORRECT  ',/,
&5X,'WOULD YOU LIKE TO INPUT THE CORRECT VALUES ?',//,
&5X,'IF SO, TYPE IN Y ',/,
&5X,'IF NOT, TYPE IN N AND THE PROGRAM WILL STOP.')
C          READ(*,2)    ISTOP
2       FORMAT(A1)
C      ELSE
C      ENDIF
C      RETURN
C
C ****
C
C      SUBROUTINE      GNRAT
C      RANDOM ACTIVITY NETWORK GENERATOR.      THE AN HAS N NODES AND M ARCS.
C      IT IS OF TYPE ACTIVITY ON ARC.
C
C ****
C
C      REAL*8   IX
C      COMMON /PAR1/N,M,NRR,NCONT,MCS,NSIM,SCAL,NR(100),NT(50)
C      COMMON /PAR2/NS(100),NE(100),NDSTT(100),R(100,30),PR(100,30)
C      COMMON /PARS/IND(200),NCF(200),NCS(200),IIN(60),IOUT(60)
C      DIMENSION NAF(60),NBE(60),A(50,50)
C      IX=12345.000
C      WRITE(*,4)N,M
4       FORMAT('1',6X,'GENERATE      AN ACTIVITY NETWORK WITH',13,',',
*14,', ARCS')
        DO 53  I=1,N
        DO 52  J=1,N
52     A(I,J)=0.0
53     CONTINUE
        L=N*(N-1)/2
        N1=N-1
        N2=N-2
        DN=FLOAT(N)
        LM=L-M
        MF=2*N-4
        DL=FLOAT(L)/2.0+1.0

```

```

DN2=DN*(DN-1.0)
DN3=DN+0.5
IF(DL-M)10,10,20
C      THE DELETION      METHOD
10    DO 3 I=1,N1
      JJ=I+1
      DO 2 J=JJ,N
2     A(I,J)=1.0
      IIN(I)=I-1
3     IOUT(I)=N-I
      IIN(N)=N-1
48    DO 13 I=1,LM
11    CALL RAND(IX,Y)
      Y1=Y*DN2+0.25
      X=DN3-SQRT(Y1)
      NO=IFIX(X)
      IF(NO.GT.X)      NO=NO-1
      IF(IOUT(NO).LT.2)   GO TO 11
      K=0
      JJ=NO+1
      DO 22 J=JJ,N
      IF(IIN(J).LT.2)      GO TO 22
      IF(A(NO,J).EQ.0.0)      GO TO 22
      K=K+1
      NAF(K)=J
22    CONTINUE
      IF(K.EQ.0)      GO TO 11
      DEN=1.0/K
      CALL RAND(IX,X)
      DO 23 J=1,K
      UP=DEN*j
      IF(X.GT.UP)      GO TO 23
      NI=NAF(J)
      GO TO 5
23    CONTINUE
5     A(NO,NI)=0.0
      IIN(NI)=IIN(NI)-1
      IOUT(NO)=IOUT(NO)-1
13    CONTINUE
      GO TO 50
C      THE ADDITION      METHOD
20    DO 30 I=1,N1
      IOUT(I)=0
30    IIN(I)=0
      NRC=N-3
      NEM=N-3
      A(1,2)=1.0
      A(N1,N)=1.0
      NARCS=2
      IOUT(1)=1
      IOUT(N1)=1
      IIN(2)=1
      IIN(N)=1

```

```

      IF(MF.GE.M)      GO TO 40
      KK=0
31   CALL RAND(IX,Y)
      Y1=Y*DN2+0.25
      X=DN3-SQRT(Y1)
      NO=IFIX(X)
      IF(NO.GT.X)      NO=NO-1
      NN=N-NO
      IF(IOUT(NO).GE.NN)      GO TO 31
      K=0
      JJ=NO+1
      DO 32 J=JJ,N
      IF(A(NO,J).EQ.1.0)      GO TO 32
      K=K+1
      NAF(K)=J
32   CONTINUE
      DEN=1.0/K
      CALL RAND(IX,X)
      UP=0.0
      DO 33 J=1,K
      UP=UP+DEN
      IF(X.GT.UP)      GO TO 33
      NI=NAF(J)
      GO TO 34
33   CONTINUE
34   A(NO,NI)=1.0
      NARCS=NARCS+1
      IF(IOUT(NO).EQ.0)      NEM=NEM-1
      IF(IIN(NI).EQ.0)      NRC=NRC-1
      IIN(NI)=IIN(NI)+1
      IOUT(NO)=IOUT(NO)+1
      IF(NARCS.GE.M)      GO TO 50
      IF(KK.EQ.1)      GO TO 31
      MF=M-NARCS-NRC-NEM
      IF(MF.GT.0)      GO TO 31
40   IF(NRC.EQ.0)      GO TO 45
      K=0
      DO 41 I=3,NI
      IF(IIN(I).GT.0)      GO TO 41
      K=K+1
      NAF(K)=I
41   CONTINUE
      IF(K.EQ.0)      GO TO 45
      DO 42 I=1,K
      IJ=K+1-I
      NI=NAF(IJ)
      CALL RAND(IX,Y)
      X=1.0+(NI-1)*Y
      NO=IFIX(X)
      IF(NO.GT.X)      NO=NO-1
      A(NO,NI)=1.0
      NARCS=NARCS+1
      IIN(NI)=IIN(NI)+1

```

```

42    IOUT(NO)=IOUT(NO)+1
45    IF(NEM.EQ.0)      GO TO 51
      K=0
      DO 43  I=2,N2
      IF(IOUT(I).GT.0)      GO TO 43
      K=K+1
      NBE(K)=I
43    CONTINUE
      IF(K.EQ.0)      GO TO 51
      DO 44  I=1,K
      NO=NBE(I)
      CALL  RAND(IX,X)
      Y=NO+1+(N-NO)*X
      NI=IFIX(Y)
      IF(NI.GT.Y)      NI=NI-1
      IIN(NI)=IIN(NI)+1
      IOUT(NO)=IOUT(NO)+1
      NARCS=NARCS+1
44    A(NO,NI)=1.0
51    KK=1
      IF(NARCS-M)31,50,47
47    LM=NARCS-M
      GO TO 48
50    K=0
      WRITE(*,14)NARCS
14    FORMAT(6X,'THE      ACTIVITY      NETWORK      HAS      THE      FOLOWING      ',13,'      ARCS')
      WRITE(*,15)
15    FORMAT(/,5X,'           I      NS(I)      NE(I)')
      DO 17  I=1,N1
      JJ=I+1
      DO 16  J=JJ,N
      IF(A(I,J).NE.1.0)      GO TO 16
      K=K+1
      NS(K)=I
      NE(K)=J
      WRITE(*,8)K,NS(K),NE(K)
8     FORMAT(5X,517)
16    CONTINUE
17    CONTINUE
      RETURN
      END
C
C ****
C
C      SUBROUTINE      RAND(IX,D)
C
C ****
C
C      DOUBLE      PRECISION      Y,A,P,IX,B15,B16,XHI,XALO,LEFTLO,FHI,K
C
C      DATA      A/16807.00/,B15/32768.00/,B16/65536.00/,P/2147483647.00/
C
C      XHI=IX/B16

```

```
XHI=XHI-DMOD(XHI,1.D0)
XALO=(IX-XHI*B16)*A
LEFTLO=XALO/B16
LEFTLO=LEFTLO-DMOD(LEFTLO,1.D0)
FHI=XHI*A+LEFTLO
K=FHI/B15
K=K-DMOD(K,1.D0)
IX=((XALO-LEFTLO*B16)-P)+(FHI-K*B15)*B16)+K
IF(IX.LT.0.D0)IX=IX+P
Y=IX*4.656612875E-10
D=REAL(Y)
IX=IX+1.0
RETURN
END
```

```
C ****
```

Appendix 9.2. Logic of Program AN-COST

1. OBTAIN NECESSARY NETWORK INFORMATION

- 1.1 CALL subroutine INTRO containing introduction and user information.
- 1.2 Obtain input and output file names from user.
- 1.3 Initialize variables to zero.
- 1.4 Read in network/duration/cost data from input file.
- 1.5 Obtain variable values necessary for MCS from user (% project cost to receive at project start, inflation rate, random number seed, and period length).
- 1.6 Read in mean and std.dev. values of key events from file TRNS.ANC

2. DETERMINE COST ALLOCATION PROPORTIONS

- 2.1 CALL subroutine SUBNET to determine the subgraphs of key events.
 - find subnetworks of all key events
 - remove activities from subnetworks of key event i that are members of the subnetwork of key event j, where $j : i$
- 2.2 CALL subroutine SEPARATE to determine allocation Proportions, Prop(i), of common act.'s
 - DO over activities
 - IF common to more than one key event THEN
 - determine cost allocation proportions via probability method or user determined percentages.
 - IF user determined THEN
 - obtain percentages from user
 - ELSE IF probability method THEN
 - determine key event with smallest mean
 - find $p(i) = Pr \{ X(\text{smallest}) \setminus X(i) \}$
 - IF $p(i) ^ 0.9$ " set Prop(i)=0.00
 - for remaining key events, set $w(i) = Pr(Y_i \setminus Y_1) * ... * Pr(Y_i \setminus Y_N)$
 - set Prop(i) = $w(i)/\sum_j w(j)$
 - continue DO loop over activities
 - find subnetworks of all key events
 - remove activities from subnetworks of key event i that are members of the subnetwork of key event j, where $j : i$
 - DO over activities
 - IF common activity THEN
 - update matrix with cost allocation proportions
 - 2.3 CALL subroutine SUBNET to update cost allocation matrix with cost allocation proportions.
 - find subnetworks of all key events
 - remove activities from subnetworks of key event i that are members of the subnetwork of key event j, where $j : i$
 - DO over activities
 - IF common activity THEN
 - update matrix with cost allocation proportions

3. INITIALIZE VARIABLES FOR MONTE CARLO SIMULATION

- 3.1 CALL XEXPEC to determine mean and std.dev. of activities (pre-programmed for allowed density functions) for use in setting the limits of the empirical distributions.

3.2 CALL INITIALIZE

- determine mean of cost distributions
- DO over key events
 - set endpoints of duration dist.'s to be ~ 3 std.dev.'s from mean
 - allow user to change endpoints
 - obtain number of cells in distributions from user
- set endpoints of cost dist.'s to be ~ a distance from the mean by some heuristic
- allow user to change endpoints
- obtain number of cells in distributions from user
- obtain same info for TOTAL COST distribution

3.3 CALL SAMPLESIZE to determine required sample size for MCS

- present menu to either get sample size info. or proceed with calc.'s
- obtain maximum difference between sample df and true df from user
- obtain confidence level from user
- determine sample size via Kolmogorov-Smirnov statistic
- allow user to change sample size if desired

4. PERFORM MONTE CARLO SIMULATION

- DO over number of Monte Carlo samples
 - CALL RNGENERATOR
 - DO over activities
 - generate activity duration
 - generate activity cost
 - CALL CRITICAL
 - determine critical path
 - calculate early start & early finish times
 - calculate activity floats
 - DO over activities
 - IF activity is on critical path THEN
 - increment critical indices counter
 - determine realization times of all key events
 - CALL PAYMENTS
 - determine cash "outflow" for network
 - DO over activities
 - DO over periods
 - IF activity is "active" in period THEN
 - increment array for MCS
 - continue over periods and activities
 - add in any fixed costs that activities have
 - alter cash "outflow" in accordance with inflation rate
 - determine cost of subgraphs of key events
 - determine total project cost
 - CALL CDF
 - increment empirical distributions arrays of duration and cost of key events and total project cost
 - increment mean and variance variables for duration and cost of key events and total project cost (using standard computa-

tional formulas for mean and variance)

- CALL SMCORR
 - update correlation variables and regression variables (correlation and linear least squares regression between cost and duration of key events and total cost vs. proj. dur.)
 - DO over key events
 - update sum and sum of squares of duration and cost
 - update sum and sum of squares of total project cost
- CALL INCOME
 - update variables keeping track of the fractions of the total project cost that the key events comprise
 - DO over key events
 - remove fraction of cost to be received at proj. start
 - determine fraction of cost of subgraph of key event
 - update array containing fractions of key events over MCS
- CALL UPPAY
 - update cash "inflow" for project for each key event
 - DO over key events
 - determine the period that the key event was realized
 - update variables for "inflow" for MCS

Continue over DO loop

- CALL DISTMV
 - make final calculations on empirical distributions, means and variances of key events, and criticality indices of activities for MCS
- CALL KEINFO
 - output to disk file empirical distribution information and criticality indices
- CALL CORRF
 - make final calculations on sample correlation coefficients and least squares regression coefficients for MCS

5. OUTPUT ALL PERTINENT DATA TO FILE cashflow.dat FOR USE BY PROGRAM CASH
6. PRINT TERMINATION INFORMATION AND STOP PROGRAM EXECUTION.

Appendix 9.3. Program Listing of AN-COST

```

C IWIDTH( ) : Array containing the interval width of the empirical density
C functions for the key events and project cost.
C LL( ),RR( ) : Left and Right endpoints of the distributions of time to
C the key events.
C MEAN( ) : Array containing the sample means of the key events and the
C key event cost.
C NOP( ) : Number of pairs of duration and probability for discrete
C activity durations.
C NKEYEN : Number of key events.
C NODEFI(I) : The node that an activity precedes to.
C NODEST(I) : The node that an activity emanates from.
C PAY( , ) : Array (nkeyen,mxperd) containing the cost of subgraph for
C each key event during which period it was realized in.
C RATE : Retention Percentage.
C STDV( ) : Array containing the standard deviation's of the key events
C obtained from file TRNS.ANC after running DODIN's program.
C STPERC : Percentage of project cost that we want to receive at time 0.
C SUBCO( ) :
C SUBM( , ) : The matrix that contains the cost associated from an activity
C to each key event.
C SUBN( , ) : A dummy matrix used in conjunction with SUBM.
C SSUM( ) : Contains the sum of the durations and costs of the key events
C to be used in calculation of correlation/least squares info.
C SSUMSQ( ) : Contains the sum of the squares of duration and cost of
C key events.
C SUMXY( ) : Contains the sum of the duration*cost of key events.
C TDURAT : Var. of duration of node n (terminal node).
C TITLE : Title of the project.
C VAR( ) : Array of sample variances of key events and tot. project cost.
C XEXP( ) : Array containing the expected value's of the activity duration.
C XSTD( ) : Array containing the standard dev.'s of the activity duration.
C
C CDUM( ) : The number of the particular density of the duration of
C an activity.
C
C P1( ),P2( ),P3( ),P4( ) : Parameters of the density functions of
C activity durations.
C
C      DNUM   DENSITY          P1           P2           P3           P4
C      -----
C      1     UNIF.CON.        --           ..           L.END         R.END
C      2     TRIANG.          MODE         ..           L.END         R.END
C      3     NORMAL           MEAN         VAR.          L.END         R.END
C      4     EXPONENTIAL       MEAN         ..           ..           ..
C      5     GAMMA            ALPHA1       ALPHA2        ..           ..
C      6     BETA              SHAPE1      SHAPE2        L.END         R.END
C      7     DISCRETE          <<<ORDERED PAIRS>>>
C      -----
C
C CPDF( ) : Character array containing the name of the act. cost density.
C CNUM( ) : The number of the particular density of activity cost.

```

```

C
C CP1( ) : Fixed cost associated with an activity.
C CP2( ),CP3( ),CP4( ),CP5( ) : Parameters of the cost functions.
C
C
C      CDFNUM   DENSITY          CP2                  CP3          CP4          CP5
C      -----
C      1      CONST*Y          CONSTANT           ---          ---
C      2      NORMAL           MEAN=CP2*DUR.     VAR.        L.LIM        R.LIM
C      3      UNIFORM          SEE THESIS
C      4      TRIANGULAR       MODE=CP2*DUR.    ---        L.LIM        R.LIM
C
C
C      --> FOR MORE INFORMATION ON COST FUNCTIONS, SEE MASTER'S THESIS
C      BY RUSSELL S. VOGTMANN "PROJECT BIDDING UNDER CHANCE TIME
C      ESTIMATES"
C
C      MAIN+
C      SUBROUTINES:
C
C      CDF: ----- UPDATES EMPIRICAL DIST.'S IN MONTE CARLO SIM.
C      CRITICAL: ----- DETERMINES CRITICAL PATH IN MONTE CARLO SIM.
C      DISTMV: ----- DETERMINES FINAL VALUES FOR EMPIRICAL DIST.'S AND
C                      MEAN'S AND VAR.'S AFTER COMPLETION OF M.C. SIM.
C      INCOME: ----- UPDATE VARIABLE FRACTN THAT KEEPS TRACK OF THE
C                      FRACTION OF THE TOTAL PROJECT COST THAT A SUBGRAPH
C                      OF A KEY EVENT IS.
C      INITIALIZE: ----- DETERMINES REQUIRED VALUES FOR EMPIRICAL DIST.'S
C      INTRO: ----- PRINTS USER INFO
C      KEINFO: ----- OUTPUTS DATA ON EMPIRICAL DIST.'S (REAL.TIME AND COST)
C      PAYMENTS: ----- DETERMINES CASH "OUTFLOW" AND COST OF SUBGRAPH'S
C
C      RNGENERATOR: ---- OBTAINS RANDOM VALUES OF DURATION AND COST DURING
C                      MONTE CARLO SIM. FOR EACH ACTIVITY IN NETWORK. THE
C                      FOLLOWING SUBROUTINES ARE CALLED FROM RNGENERATOR
C      --BETA ----- GENERATES DURATION FROM BETA DISTRIBUTION
C      --EXPON ----- GENERATES DURATION FROM EXPONENTIAL DISTRIBUTION
C      --GAMMA ----- GENERATES DURATION FROM GENERAL GAMMA DISTRIBUTION
C      --RANDOM ----- GENERATES UNIFORM(0,1) VALUE
C      --RCOST ----- GENERATES COST FOR EACH ACTIVITY IN NETWORK ONCE GIVEN
C                      THE ACTIVITIES DURATION
C      --RNORMAL ----- GENERATES VALUE (DURATION OR COST) FROM NORMAL DIST.
C      --TRIANGULAR ----- GENERATES VALUE (DURATION OR COST) FROM TRIANGULAR DIST.
C      --UNICON ----- GENERATES VALUE (DURATION OR COST) FROM UNIFORM DIST.
C
C      SEPARATE: ----- SEPARATES ACTIVITY COST FOR COMMON ACTIVITIES IN NETWORK
C      UPPAY: ----- UPDATES THE ARRAY PAY( , ) THAT TRACKS THE CASH
C                      "INFLOW" OF THE PROJECT (PER PERIOD)
C      XEXPEC: ----- DETERMINES VALUES OF EXPECTED VALUE AND STD.DEV. FOR
C                      ACTIVITIES IN NETWORK
C
C      $LARGE

```

INTEGER ASCEND(100),DECEND(100),CYCLE,DNUM(100),LL(22),RR(22),

```

*
*          CDNUM(100),FLAGONE,FLAG2,FLAG3,CMODEL,NOP(100),
*          NCELLS(22),NODEST(100),NODEFI(100),KEYEVN(10)
REAL          LS(100),LSA(100),LF(100),DN(100),XEXP(100),XSTD(100),
*          CI(100),KEYDUR(10),IWIDTH(22),DF(22,102),SDISBUR(100),
*          PAY(10,100),PERCEN(100,10),ALPHA,BETA,RATE,POWER,
*          TWORTH,STPERC,DIST(100,30),DURA(100,30),P1(100),P2(100)
*          ,P3(100),P4(100),CP1(100),CP2(100),CP3(100),CP4(100),
*          CP5(100),AVERG(10),STDV(10),DURATN(100),ACOST(100),
*          ES(100),EF(100),EFA(100),TF(100),FF(100),SF(100),
*          SUBN(100,10),SUBM(100,10),LP(100)
DOUBLE      PRECISION     MEAN(22),VAR(22),SUM2(22),SSUM(21),SSUMSQ(21),
*                      SUMXY(11),CORR(11),BHATO(11),BHAT1(11),
*                      FRACTN(10),PCOST,SUBCO(11)
REAL*8      IX
CHARACTER*6   FNAME,OUTP
C
CALL      INTRO
C
2 FORMAT(25())
3 FORMAT(5())
C
C---OPEN FILE FOR INPUT OF NETWORK AND ACTIVITY DURATION/COST INFO.
C
        WRITE(*,*)    'TYPE FILE NAME CONTAINING DURATION/COST DATA'
        READ(*,4)      FNAME
4 FORMAT(A6)
        OPEN (UNIT=1,FILE      =FNAME,STATUS      ='OLD')
C
C---OPEN FILE FOR OUTPUT OF GENERAL INFO.
C
        WRITE(*,3)
        WRITE(*,*)    'TYPE FILE NAME TO CONTAIN GENERAL OUTPUT'
        READ(*,4)      OUTP
        OPEN (UNIT=3,FILE      =OUTP,STATUS      ='NEW')
C--OPEN FILE "KEDIST.DAT" FOR OUTPUT OF REAL. TIME DIST.'S
        OPEN (UNIT=4,FILE      = 'KEDIST.DAT' ,FORM = 'FORMATTED',
*                  ACCESS = 'SEQUENTIAL', STATUS = 'NEW')
C--OPEN FILE "CASHFLOW.DAT" FOR TESTING ONLY
        OPEN (UNIT=8,FILE      = 'CASHFLOW.DAT' ,FORM = 'FORMATTED',
*                  ACCESS = 'SEQUENTIAL', STATUS = 'NEW')
C--OPEN FILE "COSTD.DAT" FOR OUTPUT OF COST DIST.'S
        OPEN (UNIT=7,FILE      = 'COSTD.DAT' ,FORM = 'FORMATTED',
*                  ACCESS = 'SEQUENTIAL', STATUS = 'NEW')
C--OPEN FILE "TRNS.ANC" FOR INPUT OF MEAN'S AND STD. DEV.'S OF
C KEY EVENTS DETERMINED FROM DOD1TRNS.EXE
        OPEN (UNIT=9,FILE='TRNS.ANC',STATUS='OLD')
C
C---VARIABLE INITIALIZATION
C
        DO 5 I=1,100
          CI(I)=0.0
          NOP(I)=0
          XEXP(I)=0.0

```

```

      XSTD(I)=0.0
      SDISBUR(I)=0.0
  5  CONTINUE
C
      DO  6  I=1,22
      DO  7  J=1,102
          MEAN(I)=0.0
          VAR(I)=0.0
          SUM2(I)=0.0
          DF(I,J)=0.0
  7  CONTINUE
  6  CONTINUE
C
      DO  8  I=1,10
      DO  9  J=1,100
          PAY(I,J)=0.0
          FRACTN(I)=0.0
  9  CONTINUE
  8  CONTINUE
C
      DO  1  I=1,11
          SUMXY(I)=0.0
          BHATO(I)=0.0
          BHAT1(I)=0.0
          CORR(I)=0.0
  1  CONTINUE
C
      DO  19  I=1,21
          SSUM(I)=0.0
          SSUMSQ(I)=0.0
  19 CONTINUE
C-----
C     READ DATA FROM INPUT FILE
C-----
      READ(1,11)    SCAL,NODES,NACT,NRR,NCONT,MCS,NSIM,NKEYEN,NANG
  11 FORMAT(F5.3,10I5)
      READ(1,106)   ( KEYEVN(I),      I=1,NKEYEN      )
  106 FORMAT(14I5)
      DO 10  I=1,NACT
          READ(1,103)    NODEST(I),NODEFI(I),DNUM(I),NOP(I)
          IF (DNUM(I).EQ.7)      THEN
              READ(1,104)    (DURA(I,J),DIST(I,J),J=1,NOP(I))
          ELSE
              READ(1,104)    P1(I),P2(I),P3(I),P4(I)
          ENDIF
  10 CONTINUE
C
      DO 90  I=1,NACT
          READ(1,103)    CNUM(I)
          READ(1,104)    CP1(I),CP2(I),CP3(I),CP4(I),CP5(I)
  90 CONTINUE
C
  103 FORMAT(14I5)

```

```

104 FORMAT(6E11.4)
C
      WRITE(*,2)
      WRITE(*,22)
22 FORMAT(5X,'YOU      WILL      NOW      BE      ASKED      TO      INPUT      VALUES      THAT      WILL      BE',//,
*5X,'USED      IN      THE      COST      CALCULATIONS')
      WRITE(*,3)
      WRITE(*,23)
23 FORMAT(2X,'INPUT      PERIOD      LENGTH      (i.e.      5      days,      etc.      --THIS      MUST      BE      I
*NTEGER      VALUED)',//)
      READ(*,*)      CYCLE
      WRITE(3,13)      CYCLE
13 FORMAT(/1X,'THE      PERIOD      LENGTH      =      ',15)
111 WRITE(*,3)
      WRITE(*,12)
      READ(*,*)      STPERC
      IF (STPERC.GT.100)      THEN
          WRITE(*,*)      'OUT      OF      RANGE      --      TRY      AGAIN'
          GOTO 111
      ENDIF
      WRITE(3,14)      STPERC
14 FORMAT(/1X,'THE      PERC.      REQUIRED      AT      START      =      ',F6.3)
      STPERC=STPERC/100
12 FORMAT(1X,'INPUT      PERCENTAGE      OF      COST      TO      RECEIVE      AT      PROJECT      START')
112 WRITE(*,3)
      WRITE(*,*)      'INPUT      THE      INFLATION      RATE      (NOT      A      PERCENTAGE)'
      READ(*,*)      GAMMA
      IF (GAMMA.GT.1)      THEN
          WRITE(*,*)      'OUT      OF      RANGE      --      TRY      AGAIN'
          GOTO 112
      ENDIF
      WRITE(3,16)      GAMMA
16 FORMAT(/1X,'THE      INFLATION      RATE      =      ',F6.5)
      WRITE(*,3)
      WRITE(*,*)      'INPUT      RANDOM      NUMBER      SEED'
      READ(*,*)      IX
      WRITE(3,17)      IX
17 FORMAT(/1X,'THE      INITIAL      RANDOM      NUMBER      SEED      =      ',F20.2)
C
C---INPUT      MEAN      AND      VARIANCE      VALUE'S      FROM      FILE      TRNS.ANC
C
      DO 92 I=1,NKEYEN
          READ(9,104)      AVERG(I),STDV(I)
92     CONTINUE
C-----
C      DETERMINE      THE      NODES      IN      ASCENDING      ORDER      FOR      USE      CRITICAL      PATH
C      CALCULATIONS
C-----
      ASCEND(1)      =      NODEST(1)
      LDT      =1
      DO 210 I = 1,NACT
          KDT      = LDT
          DO 200 K = 1,KDT

```

```

      IF ( NODEST(I) .EQ. ASCEND(K) ) GO TO 155
200  CONTINUE
      LDT = LDT + 1
      ASCEND(LDT) = NODEST(I)
155  DO 205 K = 1,KDT
      IF ( NODEFI(I) .EQ. ASCEND(K) ) GO TO 210
205  CONTINUE
      LDT = LDT + 1
      ASCEND(LDT) = NODEFI(I)
210  CONTINUE
      LM = LDT - 1
      DO 215 I = 1,LM
          M = I + 1
          DO 215 K = M,LDT
              IF ( ASCEND(I).LE.ASCEND(K) ) GO TO 215
              KTEMP = ASCEND(I)
              ASCEND(I) = ASCEND(K)
              ASCEND(K) = KTEMP
215  CONTINUE

```

C-----
C NODES IN DESCENDING ORDER FOR SAME PURPOSE AS ABOVE
C-----

```

      DO 220 I = 1,LDT
          DECEND(I) = ASCEND(I)
220  CONTINUE
      DO 225 J = 1,LM
          L = J + 1
      DO 225 K = L,LDT
          IF ( DECEND(J).GE.DECEND(K) ) GO TO 225
          KTEMP = DECEND(J)
          DECEND(J) = DECEND(K)
          DECEND(K) = KTEMP
225  CONTINUE

```

C+++++
C

C THE FOLLOWING PROGRAM SECTION OBTAINS THE PERCENTAGES TO BE
C USED IN SPLITTING THE COSTS OF THE COMMON ACTIVITIES.

C
C HERE, I ASSIGN A COST OF 1 TO ALL ACTIVITIES TO GET THE MATRIX
C THAT ASSIGNS THE COST OF THE ACTIVITIES TO THE VARIOUS KEY EVENTS.

```

      DO 93 I=1,NACT
          ACOST(I)=1

```

93 CONTINUE

C
C 1. THE FIRST CALL TO SUBNET DETERMINES THE SUBNETWORKS ASSOCIATED
C WITH ALL THE KEY EVENTS.
C 2. THE CALL TO SEPARATE OBTAINS THE PERCENTAGES OF THE COMMON ACT.'S
C TO ASSIGN TO ITS KEY EVENTS.
C 3. THE SECOND CALL TO SUBNET THEN DETERMINES THE MATRIX OF PERCENTAGES
C THAT ASSIGNS THE COSTS OF ACTIVITIES TO KEY EVENTS.

CALL SUBNET(NKEYEN,NACT,KEYEVN,NODEFI,NODEST,ACOST,ASCEND,SUBCO,

```

*           SUBM,PERCEN,FLAGONE)
*           FLAGONE=1
CALL   SEPARATE(SUBM,I,NKEYEN,NODEST,NODEFI,KEYEVN,AVERG,STDV,
*                  PERCEN,NACT,ACOST)
CALL   SUBNET(NKEYEN,NACT,KEYEVN,NODEFI,NODEST,ACOST,ASCEND,SUBCO,
*                  SUBM,PERCEN,FLAGONE)

C
CALL   XEXPEC(XEXP,XSTD,NACT,P1,P2,P3,P4,DNUM,DIST,DURA,NOP)
C
CALL   INITIALIZE(NKEYEN,LL,RR,IWIDTH,NMCS,KEYEVN,FLAGONE,AVERG,
*                  STDV,SUBM,CP1,CP2,NACT,XEXP,XSTD,OUTP,NCELLS)
C
C+++++MONTE CARLO SIMULATION OF NETWORK
C+++++
MXPERD=0
C
WRITE(*,3)
WRITE(*,*)  'BEGIN MONTE CARLO SAMPLING'
DO 500 ICOUNT=1,NMCS
    IF (MOD(ICOUNT,50).EQ.0)      WRITE(*,*)  ICOUNT
C
    CALL   RNGENERATOR(NACT,DURATN,DNUM,P1,P2,P3,P4,ACOST,CNUM,
*                      CP1,CP2,CP3,CP4,CP5,DIST,DURA,NOP,IX)
    CALL   CRITICAL(NACT,NODEST,NODEFI,DURATN,DECEND,ASCEND,LN,LDT,
*                      NKEYEN,KEYEVN,KEYDUR,CI,ES,EF)
    CALL   PAYMENTS(KEYDUR,NACT,CYCLE,ACOST,DURATN,ES,EF,SDISBUR,
*                      NMCS,MXPERD,CP1,GAMMA,SUBCO,SUBM,NKEYEN,PCOST)
    CALL   CDF(LL,RR,IWIDTH,KEYDUR,DF,NKEYEN,MEAN,SUM2,SUBCO,PCOST)
    CALL   SMCORR(PCOST,SUBCO,KEYDUR,NKEYEN,SSUM,SSUMSQ,SUMXY)
    CALL   INCOME(NKEYEN,SUBCO,PCOST,SPERC,FRACTN,NMCS)
    CALL   UPPAY(KEYDUR,PAY,MXPERD,CYCLE,NMCS,NKEYEN,SUBCO,CAPITL)
C
500  CONTINUE
WRITE(*,*)  'MONTE CARLO SAMPLING COMPLETE'
C
C---THE NEXT TWO CALLS (DISTMV & KEINFO) FINISHES THE CALCULATIONS
C---ON THE ARRAY DF AND ON THE MEAN, VAR., AND CI, THEN SENDS
C---THE INFO. TO AN EXTERNAL DATA FILE.
C
CALL   DISTMV(DF,MEAN,SUM2,VAR,NKEYEN,NMCS,CI,NACT)
CALL   KEINFO(DF,MEAN,VAR,NKEYEN,LL,RR,IWIDTH,CI,NACT,KEYEVN)
C
C---THE NEXT CALL TO CORRF FINISHES THE CALCULATIONS ON THE SAMPLE
C---CORRELATIONS BETWEEN KEY EVENT DURATION AND COST, AS WELL AS THE
C---CALCULATIONS ON THE LEAST SQUARES FIT.
C---L.S. EQUATION ==> COST = BHATO + BHAT1*DURATION
CALL   CORRF(NKEYEN,NMCS,SSUM,SSUMSQ,SUMXY,CORR,BHATO,BHAT1)
C
C+++++MONTE CARLO SIMULATION ENDS
C+++++

```

```

C---OUTPUTTING      CASH FLOW AND OTHER PERTINENT VALUES TO FILE
C   "CASHFLOW.DAT" FOR LATER USE
C
      WRITE(8,650)    CYCLE
      WRITE(8,650)    MXPERD
      WRITE(8,651)    (SDISBUR(I),I=1,MXPERD)
      WRITE(8,650)    NKEYEN
      WRITE(8,650)    (KEYEVN(I),I=1,NKEYEN)
      DO 501 J=1,NKEYEN
          WRITE(8,651)    (PAY(J,I),I=1,MXPERD)
501  CONTINUE
      WRITE(8,651)    STPERC,CAPITL
      DO 502 J=1,NKEYEN
          WRITE(8,651)    MEAN(J),SQRT(VAR(J))
          WRITE(8,651)    MEAN(J+10),SQRT(VAR(J+10))
502  CONTINUE
      WRITE(8,651)    MEAN(22),SQRT(VAR(22))
650  FORMAT(10I5)
651  FORMAT(5E13.7)
C
      DO 660 I=1,NKEYEN
          WRITE(8,690)    LL(I),RR(I),NCELLS(I),IWIDTH(I)
          WRITE(8,651)    (DF(I,J),J=1,NCELLS(I)+2)
          WRITE(8,690)    LL(I+10),RR(I+10),NCELLS(I+10),IWIDTH(I+10)
          WRITE(8,651)    (DF(I+10,J),J=1,NCELLS(I+10)+2)
660  CONTINUE
      WRITE(8,690)    LL(22),RR(22),NCELLS(22),IWIDTH(22)
      WRITE(8,651)    (DF(22,J),J=1,NCELLS(22)+2)
690  FORMAT(I10,I10,I10,F15.5)
C
      DO 665 I=1,NKEYEN
          WRITE(8,651)    CORR(I),BHATO(I),BHAT1(I)
665  CONTINUE
      WRITE(8,651)    CORR(11),BHATO(11),BHAT1(11)
C
      DO 666 I=1,NKEYEN
          WRITE(8,651)    FRACTN(I)
666  CONTINUE
C
C---TERMINATION      COMMENTS      TO SCREEN
C
      WRITE(*,2)
      WRITE(*,653)
653  FORMAT(1X,'PROGRAM      AN-COST.EXE      IS TERMINATING      ---',//,
*10X,'1.      OUTPUT INFORMATION',//,
*10X,'2.      EXIT PROGRAM',//,
*5X,'ENTER      CHOICE',//)
      READ(*,*)  ICHOICE
      IF (ICHOICE.LT.1.OR.ICHOICE.GT.2)      THEN
          WRITE(*,*)  'OUT OF RANGE --- EXITING PROGRAM'
          GOTO 655
      ENDIF
      IF (ICHOICE.EQ.1)      CALL OUTHLP

```

```

C
 655 STOP
END
C-----
C
C      SUBROUTINE      C D F
C
C          THIS SUBROUTINE      INCREMENTS      THE DIST.  FUNC.  ARRAYS FOR
C          THE KEY EVENTS AND PROJECT COST. IT ALSO TRACKS VALUES TO
C          DETERMINE THE MEAN AND VARIANCE OF THE REALIZATION TIME OF
C          THE KEY EVENTS, AS WELL AS FOR THE PROJECT COST.
C
C-----
C
C      SUBROUTINE      CDF  (LL,RR,IWIDTH,KEYDUR,DF,NKEYEN,MEAN,SUM2,
*                      SUBCO,PCOST)
C
C      INTEGER      LL(22),RR(22),NKEYEN
C      REAL        IWIDTH(22),KEYDUR(10),DF(22,102)
C      DOUBLE      PRECISION     MEAN(22),SUM2(22),PCOST,SUBCO(11)
C
C---THIS <DO> LOOP INCREMENTS THE ARRAY DF FOR ALL KEY EVENTS.
C
      DO 7000 K=1,NKEYEN
         XX=(KEYDUR(K)-LL(K))/IWIDTH(K)
         IF (XX-INT(XX).EQ.0.0)      THEN
            MARK=INT(XX)+1
         ELSE
            MARK=INT(XX)+2
         ENDIF
         IF (MARK.LE.0)      MARK=1
         IF (KEYDUR(K).GT.RR(K))      MARK=INT((RR(K)-LL(K))/IWIDTH(K))+2
         DF(K,MARK)=DF(K,MARK)+1
    7000 CONTINUE
C
C---NOW INCREMENT FOR COST OF SUBGRAPHS OF KEY EVENTS
C
      DO 7020 K=11,NKEYEN+10
         XX=(SUBCO(K-10)-LL(K))/IWIDTH(K)
         IF (XX-INT(XX).EQ.0.0)      THEN
            MARK=INT(XX)+1
         ELSE
            MARK=INT(XX)+2
         ENDIF
         IF (MARK.LE.0)      MARK=1
         IF (SUBCO(K-10).GT.RR(K))      MARK=INT((RR(K)-LL(K))/IWIDTH(K))+2
         DF(K,MARK)=DF(K,MARK)+1
    7020 CONTINUE
C
C---NOW FOR THE TOTAL PROJECT COST
C
      XX=(PCOST-LL(22))/IWIDTH(22)
      IF (XX-INT(XX).EQ.0.0)      THEN

```

```

        MARK=INT(XX)+1
    ELSE
        MARK=INT(XX)+2
    ENDIF
    IF (MARK.LE.0)      MARK=1
    IF (PCOST.GT.RR(22))      THEN
        MARK=INT((RR(22)-LL(22))/IWIDTH(22))+2
    ENDIF
    DF(22,MARK)=DF(22,MARK)+1
C
C----UPDATING      MEAN      AND      VARIANCE      COUNTERS      ON      DURATION      AND      COST
C
DO 7005  K=1,NKEYEN
    MEAN(K)=MEAN(K)+KEYDUR(K)
    SUM2(K)=SUM2(K)+KEYDUR(K)*KEYDUR(K)
    MEAN(K+10)=MEAN(K+10)+SUBCO(K)
    SUM2(K+10)=SUM2(K+10)+SUBCO(K)*SUBCO(K)
7005  CONTINUE
C
C---UPDATE      MEAN      AND      VAR.      COUNTERS      FOR      PROJECT      COST
C
    MEAN(22)=MEAN(22)+PCOST
    SUM2(22)=SUM2(22)+PCOST*PCOST
C
    RETURN
END
C-----.
C
C      SUBROUTINE      C O R R F
C
C      THIS      SUBROUTINE      COMPLETES      THE      CALCULATIONS      FOR      SAMPLE      CORRELATION
C      AND      THE      LEAST      SQUARES      ESTIMATORS.
C
C-----.
C
SUBROUTINE      CORRF(NKEYEN,NMCS,SSUM,SSUMSQ,SUMXY,CORR,BHAT0,BHAT1)
C
    INTEGER      NKEYEN,NMCS
    DOUBLE      PRECISION      SSUM(21),SSUMSQ(21),SUMXY(11),RNUM,DEN,CORR(11),
    *                  BHAT0(11),BHAT1(11)
C
C---DETERMINE      SAMPLE      CORRELATION
C
    RNUM=0.
    DEN=0.
    DO 3700  I=1,NKEYEN
        RNUM=NMCSSUMXY(I)-SSUM(I)*SSUM(I+10)
        DEN=(NMCS*SSUMSQ(I)-SSUM(I)**2)*(NMCS*SSUMSQ(I+10)-SSUM(I+10)**2)
        IF (DEN.EQ.0.)      THEN
            CORR(I)=-.9999
        ELSE
            CORR(I)=RNUM/SQRT(DEN)
        ENDIF

```

```

3700  CONTINUE
C
      RNUM=NMCS*SUMXY(11)-SSUM(NKEYEN)*SSUM(21)
      DEN=(NMCS*SSUMSQ(NKEYEN)-SSUM(NKEYEN)**2)*(NMCS*SSUMSQ(21)-SSUM(21
      **)**2)
C
C   IF  DEN  EQUALS  ZERO,  THE  NETWORK  IS  DETERMINISTIC  AND  CORR  MAKES  NO  SENSE
C
      IF  (DEN.EQ.0.)      THEN
          CORR(11)=-9999
      ELSE
          CORR(11)=RNUM/SQRT(DEN)
      ENDIF
C
C---DETERMINE      THE      ESTIMATORS      OF      THE      LEAST      SQUARES      FIT
C
      DO 3710  I=1,NKEYEN
          RNUM=NMCS*SUMXY(I)-SSUM(I)*SSUM(I+10)
          DEN=NMCS*SSUMSQ(I)-SSUM(I)**2
          IF  (DEN.EQ.0.)      THEN
              BHAT1(I)=-9999
          ELSE
              BHAT1(I)=RNUM/DEN
          ENDIF
C
          RNUM=SSUMSQ(I)*SSUM(I+10)-SSUM(I)*SUMXY(I)
          IF  (DEN.EQ.0.)      THEN
              BHATO(I)=-9999
          ELSE
              BHATO(I)=RNUM/DEN
          ENDIF
      3710  CONTINUE
C
          RNUM=NMCS*SUMXY(11)-SSUM(NKEYEN)*SSUM(21)
          DEN=NMCS*SSUMSQ(NKEYEN)-SSUM(NKEYEN)**2
          IF  (DEN.EQ.0.)      THEN
              BHAT1(11)=-9999
          ELSE
              BHAT1(11)=RNUM/DEN
          ENDIF
C
          RNUM=SSUMSQ(NKEYEN)*SSUM(21)-SSUM(NKEYEN)*SUMXY(11)
          IF  (DEN.EQ.0.)      THEN
              BHATO(11)=-9999
          ELSE
              BHATO(11)=RNUM/DEN
          ENDIF
C
          RETURN
END
C.....-----
C
C   SUBROUTINE      CRITICAL

```

```

C
C      THIS SUBROUTINE DETERMINES THE CRITICAL PATH,INCREMENTING
C      THE CRITICAL INDICES, AND DETERMINES THE REALIZATION TIMES
C      OF THE KEY EVENTS.
C-----
C
SUBROUTINE CRITICAL (NACT,NODEST,NODEFI,DURATN,DECEND,ASCEND,
*                      LM,LDT,NKEYEN,KEYEVN,KEYDUR,C1,ES,EF)
INTEGER NACT,NODEST(100),NODEFI(100),ASCEND(100),DECEND(100),LM,
*          LDT,NKEYEN,KEYEVN(10)
REAL DURATN(100),KEYDUR(10),ES(100),LS(100),EF(100),LF(100)
*          ,TF(100),FF(100),SF(100),EFA(100),LSA(100),C1(100)
REAL TDURAT

C
C
C      CALCULATE EARLY START & EARLY FINISH
C
DO 230 I = 1,NACT
    IF ( NODEST(I).NE.ASCEND(1) ) GO TO 230
    ES(I) = 0.
    EF(I) = ES(I) + DURATN(I)
230 CONTINUE

C
LM = LDT - 1
DO 235 J = 2,LM
    BIG = 0.
    DO 240 I = 1,NACT
        IF ( NODEFI(I).NE.ASCEND(J) ) GO TO 240
        IF ( EF(I).LE. BIG ) GO TO 240
        BIG = EF(I)
240 CONTINUE
    DO 245 I = 1,NACT
        IF ( NODEST(I).NE.ASCEND(J) ) GO TO 245
        ES(I) = BIG
        EF(I) = ES(I) + DURATN(I)
245 CONTINUE
235 CONTINUE

C
TDURAT = 0.0
DO 250 I = 1,NACT
    IF ( NODEFI(I).NE.ASCEND(LDT) ) GO TO 250
    IF ( EF(I).LE.TDURAT ) GO TO 250
    TDURAT = EF(I)
250 CONTINUE

C
C---CALCULATE LATE START AND LATE FINISH
C
DO 255 I = 1,NACT
    IF ( NODEFI(I).NE.DECEND(1) ) GO TO 255
    LF(I) = TDURAT
    LS(I) = TDURAT + DURATN(I)
255 CONTINUE

```

```

DO 260 J = 2,LM
  SMALL = 2147483647.
  DO 265 I = 1,NACT
    IF ( NODEST(I).NE.DECEND(J) ) GO TO 265
    IF ( LS(I).GE.SMALL ) GO TO 265
    SMALL = LS(I)
265  CONTINUE
  DO 270 I = 1,NACT
    IF ( NODEFI(I).NE.DECEND(J) ) GO TO 270
    LFC(I) = SMALL
    LS(I) = LF(I) - DURATN(I)
270  CONTINUE
260  CONTINUE
C
C---CALCULATE FLOATS
C
  DO 271 I = 1,NACT
    DO 266 J = 1,NACT
      IF ( NODEFI(I).NE.DECEND(J) ) GO TO 280
      EFA(I) = TDURAT
      GO TO 266
280  IF ( NODEFI(I).NE.NODEST(J) ) GO TO 266
      EFA(I) = ES(J)
266  CONTINUE
  DO 275 J = 1,NACT
    IF ( NODEST(I).NE.ASCEND(J) ) GO TO 285
    LSA(I)=0
    GO TO 275
285  IF ( NODEST(I).NE.NODEST(J) ) GO TO 275
    LSA(I) = LF(J)
275  CONTINUE
    TF(I) = LF(I) - ES(I) - DURATN(I)
    FF(I) = EFA(I) - ES(I) - DURATN(I)
    SF(I) = LF(I) - LSA(I) - DURATN(I)
271  CONTINUE
C
C---INCREMENT CRITICAL INDICES
C
  DO 290 I=1,NACT
    IF (TF(I).LT.0.00001) CI(I)=CI(I)+1.0
290  CONTINUE
C
C---DETERMINE REALIZATION TIME OF KEY EVENTS
C
  DO 292 K=1,NKEYEN-1
  DO 293 I=1,NACT
    IF (KEYEVN(K).NE.NODEST(I)) GO TO 293
    KEYDUR(K)=ES(I)
    GO TO 292
293  CONTINUE
292  CONTINUE
C
C---SET REAL. TIME OF END-NODE TO TDURAT

```

```

C
      KEYDUR(NKEYEN)=TDURAT
C
      RETURN
      END
C-----.
C
C      SUBROUTINE      D I S T M V
C
C      THIS SUBROUTINE      NORMALIZES      THE VALUES      IN DF AS WELL AS
C      MAKING THE FINAL CALCULATIONS      OF THE MEAN      AND VARIANCE OF
C      THE REALIZATION      TIME OF KEY EVENTS.
C
C-----.
C
      SUBROUTINE      DISTMV(DF,MEAN,SUM2,VAR,NKEYEN,NMCS,C1,NACT)
      INTEGER      NKEYEN,NMCS,NACT
      REAL        DF(22,102),C1(100)
      DOUBLE      PRECISION     MEAN(22),SUM2(22),VAR(22)
C
      DO 3000  J1=1,NKEYEN
      DO 3005  J2=1,102
         DF(J1,J2)=DF(J1,J2)/NMCS
         DF(J1+10,J2)=DF(J1+10,J2)/NMCS
3005  CONTINUE
3000  CONTINUE
C
      DO 3006  J2=1,102
         DF(22,J2)=DF(22,J2)/NMCS
3006  CONTINUE
C
C---MAKE FINAL CALCULATIONS ON MEAN AND VARIANCE OF REALIZATION
C---TIMES AND COST OF KEY EVENTS.
C
      DO 3007  J1=1,NKEYEN
         VAR(J1)=(NMCS*SUM2(J1)-MEAN(J1)*MEAN(J1))/(NMCS*NMCs-NMCS)
         MEAN(J1)=MEAN(J1)/NMCS
         VAR(J1+10)=(NMCS*SUM2(J1+10)-MEAN(J1+10)*MEAN(J1+10))/*
                     (NMCS*NMCs-NMCS)
         MEAN(J1+10)=MEAN(J1+10)/NMCS
3007  CONTINUE
C
C---FINAL CALC.'S ON MEAN AND VAR. ON TOT. PROJECT COST
C
         VAR(22)=(NMCS*SUM2(22)-MEAN(22)*MEAN(22))/(NMCS*NMCs-NMCS)
         MEAN(22)=MEAN(22)/NMCS
C
      DO 3008  J1=1,NACT
         C1(J1)=C1(J1)/NMCS
3008  CONTINUE
C
C
      RETURN

```

```

      END
C-----
C
C      SUBROUTINE      I N C O M E
C
C      TAKE OUT THE PERCENTAGE      OF COST PREDETERMINED      TO RECEIVE AT
C      BEGINNING      OF PROJECT,      AND UPDATE OVERALL PROJECT      COST FRACTIONS.
C
C-----
C
C      SUBROUTINE      INCOME(NKEYEN,SUBCO,PCOST,STPERC,FRACTN,NMCS)
C
C      INTEGER      NKEYEN,NMCS
C      REAL        STPERC
C      DOUBLE      PRECISION     FRACTN(10),FRAC(10),SUBCO(11),PCOST
C
C      DO 3510  I=1,NKEYEN
C             FRAC(I)=SUBCO(I)/PCOST
3510  CONTINUE
C
C      SUBCO(NKEYEN+1)=STPERC*PCOST
C      DO 3520  I=1,NKEYEN
C             SUBCO(I)=FRAC(I)*(PCOST*(1-STPERC))
C             FRAC(I)=SUBCO(I)/PCOST
C             FRACTN(I)=FRACTN(I)+FRAC(I)/NMCS
3520  CONTINUE
C
C      RETURN
C      END
C-----
C
C      SUBROUTINE      I N I T I A L I Z E
C
C      THIS SUBROUTINE      OBTAINS      THE NECESSARY      INFO.      FOR THE
C      DISTRIBUTION      FUNCTIONS      USED      DURING      THE MONTE CARLO SIM.
C
C      --THE DIST. FUNCTIONS      CONTAIN      AT MOST      ONE HUNDRED      INTERVALS.
C
C      ---DF(--,102)      - ARRAY      CONTAINING      THE EMPIRICAL      DIST. FUNC.
C      ---LL(--)          - LEFT      ENDPOINT      OF A DIST. FUNC.
C      ---RR(--)          - RIGHT      "      "      "      "
C      ---IWIDTH(--)      - INTERVAL      WIDTH      OF THE DIST. FUNC.
C
C-----
C
C      SUBROUTINE      INITIALIZE      (NKEYEN,LL,RR,IWIDTH,NMCS,KEYEVN,FLAGONE,
C      *                                AVERG,STDV,SUBM,CP1,CP2,NACT,XEXP,XSTD,
C      *                                OUTP,NCELLS)
C
C      INTEGER      K,LL(22),RR(22),KEYEVN(10),FLAGONE,NCELLS(22)
C      REAL        IWIDTH(22),AVERG(10),STDV(10),CP2(100),CP1(100),
C      *                                SUBM(100,10),XEXP(100),XSTD(100)
C      CHARACTER*1    DCHAR

```

```

CHARACTER*6      OUTP
REAL   CMEAN(10),CVAR(10)

C
C---DETERMINE      SOME    LIMITS    ON    THE    COST    DISTRIBUTIONS
C
      CTOT=0.0
      CTVAR=0.0
      DO 82 I=1,NKEYEN
          CMEAN(I)=0.0
          CVAR(I)=0.0
82 CONTINUE
C
      DO 8050 I=1,NKEYEN
      DO 8051 I1=1,NACT
          CMEAN(I)=CMEAN(I)+SUBM(I1,I)*XEXP(I1)*CP2(I1)
          CMEAN(I)=CMEAN(I)+SUBM(I1,I)*CP1(I1)
          CVAR(I)=CVAR(I)+SUBM(I1,I)*XSTD(I1)*XSTD(I1)*CP2(I1)
8051 CONTINUE
8050 CONTINUE
C
      DO 8054 I=1,NKEYEN
          IF (CVAR(I).LE.0.0)           CVAR(I)=0.0
8054 CONTINUE
C
      DO 8052 I=1,NKEYEN
          CTOT=CTOT+CMEAN(I)
          CTVAR=CTVAR+CVAR(I)
8052 CONTINUE
      IF (CTVAR.LE.0.0)           CTVAR=0.0
C
C---GET      INFO      ON      EMPIRICAL      DIST.'S
C
      WRITE (*,8081)
      WRITE (*,8081)
      WRITE (*,8080)
      WRITE (*,8081)
8080 FORMAT(//1X,'THE          EMPIRICAL      DENSITY      FUNCTION'S      OF REALIZATION',//,
*5X,'TIME      OF THE KEY EVENTS      WILL      ASSUME      THE FOLLOWING      ENDPOINTS')
8081 FORMAT(2(/),'      ')
C
      DO 8000 K=1,NKEYEN
          WRITE (*,8090) KEYEVN(K)
          LL(K)=INT(AVERG(K)-3*STDV(K))
          RR(K)=INT(AVERG(K)+3*STDV(K))
          IF (LL(K).EQ.RR(K))      THEN
              LL(K)=LL(K)-10
              RR(K)=RR(K)+10
          ENDIF
          IF (LL(K).LT.0.0)      LL(K)=0.0
          WRITE (*,8091) LL(K),RR(K)
8090 FORMAT(//1X,'LOWER      AND      UPPER      ENDPOINTS      FOR      KEY      EVENT      ',14,'      ARE:')
8091 FORMAT(/10X,I10,5X,I10)
          WRITE (*,8070)

```

```

        READ(*,8074)      DCHAR
8070  FORMAT(/5X,'Are      These   Values   Acceptable?    (Y or N)')
8074  FORMAT(A1)
        IF  (DCHAR.EQ.'N'.OR.DCHAR.EQ.'n')           THEN
            WRITE(*,8071)
8071  FORMAT(/5X,'THEN      INPUT   YOUR   OWN   VALUES   (LOWER   END   THEN   UPPER)')
            READ(*,*)      LL(K),RR(K)
        ENDIF
C
8010  WRITE  (*,8081)
        WRITE  (*,8093)      KEYEVN(K)
        READ  (*,*)      NCELLS(K)
        XINUM=NCELLS(K)
        IWIDTH(K)=(RR(K)-LL(K))/XINUM
8093  FORMAT(1X,'HOW      MANY   INVTERVALS   FOR   DIST.   OF   KEY   EVENT',14,/,,
     &3X,'---recommended   value   is   no   more   than   20',/)
        IF  (XINUM.GT.100)      THEN
            WRITE  (*,8095)
            GO TO  8010
        END IF
C
C---NOW   FOR   COST   DISTRIBUTIONS   OF   KEY   EVENTS
C
        WRITE  (*,8040)      KEYEVN(K)
        LL(K+10)=INT(CMEAN(K)-18*SQRT(CVAR(K)))
        RR(K+10)=INT(CMEAN(K)+18*SQRT(CVAR(K)))
        IF  (LL(K+10).EQ.RR(K+10))           THEN
            LL(K+10)=LL(K+10)-10
            RR(K+10)=RR(K+10)+10
        ENDIF
        IF  (LL(K+10).LT.0)      LL(K+10)=0
        WRITE(*,8091)      LL(K+10),RR(K+10)
8040  FORMAT(//1X,'ENDPOINTS      FOR   COST   DIST.   OF   KEY   EVENT  ',14,' ARE')
        WRITE(*,8070)
        READ(*,8074)      DCHAR
        IF  (DCHAR.EQ.'N'.OR.DCHAR.EQ.'n')           THEN
            WRITE(*,8071)
            READ(*,*)      LL(K+10),RR(K+10)
        ENDIF
C
8045  WRITE  (*,8081)
        WRITE  (*,8043)      KEYEVN(K)
        READ  (*,*)      NCELLS(K+10)
        XINUM=NCELLS(K+10)
        IWIDTH(K+10)=(RR(K+10)-LL(K+10))/XINUM
8043  FORMAT(1X,'HOW      MANY   INVTERVALS   FOR   COST   OF   KEY   EVENT',14,/,,
     &3X,'---recommended   value   is   no   more   than   20',/)
        IF  (XINUM.GT.100)      THEN
            WRITE  (*,8095)
            GO TO  8045
        END IF
8095  FORMAT('TOO      MANY   INTERVALS   (100-MAX!).   TRY   AGAIN.')
C

```

```

8000  CONTINUE
C
C---INPUT    INFO.    FOR DIST. OF PROJECT COST (TOTAL).
C
        WRITE(*,8081)
        WRITE(*,8072)
8072  FORMAT(//5X,'LOWER      AND UPPER ENDPOINTS FOR TOTAL COST DIST.:')
        LL(22)=INT(CTOT-18*SQRT(CTVAR))
        RR(22)=INT(CTOT+18*SQRT(CTVAR))
        IF (LL(22).LT.0)      LL(22)=0
        IF (LL(22).EQ.RR(22)) THEN
            LL(22)=LL(22)-10
            RR(22)=RR(22)+10
        ENDIF
        WRITE(*,8091)      LL(22),RR(22)
        WRITE(*,8070)
        READ(*,8074)      DCHAR
        IF (DCHAR.EQ.'N'.OR.DCHAR.EQ.'n')           THEN
            WRITE(*,8071)
            READ(*,*)      LL(22),RR(22)
        ENDIF
C
8020  WRITE(*,8081)
        WRITE(*,*)      'HOW MANY INTERVALS FOR THE PROJECT COST DIST.?’
        WRITE(*,*)      ' --recommended value is no more than 20'
        READ(*,*)      NCELLS(22)
        XINUM=NCELLS(22)
        IWIDTH(22)=(RR(22)-LL(22))/XINUM
        IF (XINUM.GT.100)      THEN
            WRITE (*,8095)
            GO TO 8020
        ENDIF
C
C---ECHO    THE DISTRIBUTION    VALUES    TO    THE    GENERAL    OUTPUT    FILE
C
        WRITE(3,*)      'VALUES OF ENDPOINTS FOR EMPIRICAL DIST.'S ARE:'
        WRITE(3,8098)
        WRITE(3,*)      '          LEFT-END          RIGHT-END          INT.-WIDTH'
        DO 8015  K=1,NKEYEN
            WRITE(3,16)      KEYEVN(K)
            WRITE(3,*)      ' REAL. TIME DIST.'
            WRITE(3,8096)      LL(K),RR(K),IWIDTH(K)
            WRITE(3,*)      ' COST FUNC.'
            WRITE(3,8096)      LL(K+10),RR(K+10),IWIDTH(K+10)
            WRITE(3,8098)
8015  CONTINUE
        WRITE(3,*)      'TOTAL PROJECT COST'
        WRITE(3,8096)      LL(22),RR(22),IWIDTH(22)
16   FORMAT(1X,'KEY EVENT ',15)
8096 FORMAT(10X,I10,5X,I10,3X,F10.2)
8098 FORMAT(/)

C
        CALL SAMPLESIZE(NMCS)

```

```

C
C----INITIALIZE      FLAGONE-----
     FLAGONE=0
C
     RETURN
END
C+++++-----+
C
C      SUBROUTINE      I N T R O
C
C      THIS      SUBROUTINE      WRITES      INTRO.      INFORMATION      ON      THE      PROGRAM      AN-COST
C      TO      THE      SCREEN
C
C-----.
C
C      SUBROUTINE      INTRO
C
C      WRITE(*,10)
10   FORMAT(25(/))
      WRITE(*,1)
      PAUSE
      WRITE(*,10)
19   WRITE(*,20)
20   FORMAT(10X,'1.      GENERAL      PROGRAM      INFORMATION',//,
&10X,'2.      CONTINUE      WITH      MONTE      CARLO      SIMULATION',//,
&5X,'ENTER      CHOICE',//)
      READ(*,*)      ICH
      IF      (ICH.LT.1.OR.ICH.GT.2)      THEN
          WRITE(*,*)      'OUT      OF      RANGE'
          GOTO      19
      ENDIF
      IF      (ICH.EQ.2)      RETURN
C
      WRITE(*,6)
      PAUSE
      WRITE(*,2)
      PAUSE
      WRITE(*,3)
      PAUSE
      WRITE(*,4)
      PAUSE
      WRITE(*,5)
      PAUSE
      WRITE(*,7)
      PAUSE
      WRITE(*,10)
C
1    FORMAT(29X,'PROGRAM                      AN-COST',//),
*29X,'                  WRITTEN      BY',//,
*28X,'      RUSSELL      S.      VOGMANN',//,
*5X,'ADVISOR:      SALAH      E.      ELMAGHRABY',//)
2    FORMAT(//10X,'TO      RUN      THIS      PROGRAM,      YOU      MUST:',/,,
*10X,'                                ',/)

```

```

*10X,'      1. CREATE A FILE CONTAINING SOME GENERAL INFORMATION',/,
*10X,'      AND ACTIVITY DURATION/COST INFORMATION. (THIS CAN',/,
*10X,'      BE DONE BY RUNNING PROGRAM ANC-IN.EXE)',/,
*10X,'      2. PLACE THE MEANS AND STANDARD DEVIATIONS OF THE',/,
*10X,'      KEY EVENTS IN A DATA FILE NAMED "TRNS.ANC"',/,
*10X,'      (THIS CAN DONE BY RUNNING PROGRAM DOD1TRNS.EXE',/,
*10X,'      WHICH IS AN ALTERATION OF DODIN'S PROGRAM) ',/,
*10X,'      3. RUN AN-COST.EXE.',///
3   FORMAT(//15X,'PROGRAM ANC-IN.EXE HAS THE ADDITIONAL FACILITY',/,
*10X,'FOR RANDOMLY GENERATING ACTIVITY NETWORKS.',/,,
*15X,'THE SAME FORMAT IN THE DATA FILE ON DURATION/COST IS',/,
*10X,'USED AS IS IN DODIN'S PROGRAMS, THEREFORE DOD1TRNS.EXE',/,
*10X,'WILL GIVE THE SAME INFORMATION ON THE DISTRIBUTIONS OF',/,
*10X,'KEY EVENTS AS DOES DODIN1.EXE.',///)
4   FORMAT(//15X,'FOR FURTHER DETAILS ON PROGRAMS ANC-IN.EXE, ',/,,
*10X,'DOD1TRNS.EXE, OR AN-COST.EXE REFER TO:',/,,
*10X,'"PROJECT BIDDING UNDER CHANCE TIME CONSTRAINTS"',/,,
*10X,'Master's Thesis by RUSSELL S. VOGTMANN',///)
5   FORMAT(//15X,'LIMITATIONS ON THIS PROGRAM:',/,,
*10X,'1. MAX 100 ARCS',/,,
*10X,'2. MAX 50 NODES',/,,
*10X,'3. 30 DURATIONS FOR AN ACTIVITY',/,,
*10X,'4. DIRECTED ACYCLIC NETWORKS',///)
6   FORMAT(//10X,'THIS PROGRAM IS DESIGNED TO DETERMINE THE ',/,
*5X,'DISTRIBUTIONS OF REALIZATION TIME AND COST OF KEY EVENTS',/,,
*5X,'AND THE STREAMS OF CASH FLOW OF DIRECTED ACYCLIC NETWORKS',/,,
*5X,',',/,,
*5X,'IT DOES THIS BY MONTE CARLO SIMULATION OF THE NETWORK',///)
7   FORMAT(//10X,'ONCE THIS PROGRAM IS COMPLETE, PROGRAM CASH.EXE',/,,
*5X,'CAN BE USED TO VIEW THE DISTRIBUTION FUNCTIONS, THE CASH',/,,
*5X,'FLOW STREAMS, THE PERCENTILES OF THE DISTRIBUTIONS, AND TO',/,,
*5X,'DO CASH FLOW CALCULATIONS FOR THE PROBLEM',///)

```

```

C
  RETURN
END

```

```

C-----
C
C      SUBROUTINE K E I N F O
C
C      THIS SUBROUTINE SENDS THE INFORMATION ON THE DIST. OF
C      THE REALIZATION TIME OF THE KEY EVENTS TO AN OUTPUT FILE
C      CALLED KEDIST.DAT .
C      THE CRITICAL INDICES ARE ALSO SENT TO THE, ABOVE, FILE.
C
C-----
C

```

```

SUBROUTINE KEINFO(DF,MEAN,VAR,NKEYEN,LL,RR,IWIDTH,CI,NACT,
*                  KEYEVN)
INTEGER NKEYEN,LL(22),RR(22),NACT,KEYEVN(10)
REAL DF(22,102),IWIDTH(22),CI(100)
DOUBLE PRECISION MEAN(22),VAR(22)
C
REAL F

```

```

C
      WRITE(4,3088)
      DO 3009 J1=1,NKEYEN
C
      WRITE(4,*)
      WRITE(4,3083)      KEYEVN(J1)
3083 FORMAT(/1X,'     ---- KEY EVENT',I3,'     -----')
      KHOLD=(RR(J1)-LL(J1))/IWIDTH(J1)+2
      KHOLD=INT(KHOLD)
C
C---THE FOLLOWING <DO> LOOP SENDS THE EMPIRICAL DATA ON THE DENSITY
C---FUNCTION OF THE REALIZATION TIME OF THE KEY EVENTS TO FILE KEDIST.DAT
C
      DO 3010 J2=1,KHOLD
         IF (J2.EQ.1) THEN
            WRITE(4,3090)    LL(J1),DF(J1,1)
            GO TO 3010
         ENDIF
         IF (J2.EQ.KHOLD) THEN
            WRITE(4,3092)    RR(J1),DF(J1,KHOLD)
            GO TO 3010
         ENDIF
         X1=LL(J1)+(J2-2)*IWIDTH(J1)
         X2=X1+IWIDTH(J1)
         X3=DF(J1,J2)
         WRITE(4,3091)    X1,X2,X3
C
3010 CONTINUE
C
C---THE FOLLOWING <DO> LOOP SENDS THE DATA ON THE DISTRIBUTION FUNC.
C---TO THE FILE.
C
      SUM=0.00
      DO 3012 J2=1,KHOLD-1
         SUM=SUM+DF(J1,J2)
         X1=LL(J1)+(J2-1)*IWIDTH(J1)
         WRITE(4,3094)    X1,SUM
3012 CONTINUE
C
C---THE OBSERVED MEAN AND VARIANCE OF THE REALIZATION TIME OF THE
C---KEY EVENTS (OBTAINED FROM THE MONTE CARLO SIM.) IS ALSO SENT
C---TO THE FILE.
C
      WRITE(4,3095)      MEAN(J1)
      WRITE(4,3096)      VAR(J1)
      IF (VAR(J1).LE.0.)      VAR(J1)=0.
      WRITE(4,3099)      SQRT(VAR(J1))
C
3009 CONTINUE
C
C---NOW SEND THE DIST. INFO. ON PROJECT COST TO THE FILE.
C
      WRITE(7,*)

```

```

      WRITE(7,*)
      WRITE(7,*)
      KHOLD=(RR(22)-LL(22))/IWIDTH(22)+2
      KHOLD=INT(KHOLD)

C
C---THIS <DO> LOOP SENDS THE DATA ON THE DENSITY FUNC. OF PROJECT
C COST TO THE FILE.
C

      DO 3050 J2=1,KHOLD
      IF (J2.EQ.1) THEN
          WRITE(7,3090) LL(22),DF(22,1)
          GO TO 3050
      ENDIF
      IF (J2.EQ.KHOLD) THEN
          WRITE(7,3092) RR(22),DF(22,KHOLD)
          GO TO 3050
      ENDIF
      X1=LL(22)+(J2-2)*IWIDTH(22)
      X2=X1+IWIDTH(22)
      X3=DF(22,J2)
      WRITE(7,3091) X1,X2,X3
3050 CONTINUE
C
C---THIS LOOP SENDS THE DATA ON THE DIST. FUNC. TO THE FILE.
C

      SUM=0.00
      DO 3055 J2=1,KHOLD-1
          SUM=SUM+DF(22,J2)
          X1=LL(22)+(J2-1)*IWIDTH(22)
          WRITE(7,3094) X1,SUM
3055 CONTINUE
C
C---NOW SEND THE OBSERVED MEAN AND VAR. OF THE PROJECT COST.
C

      WRITE(7,3095) MEAN(22)
      WRITE(7,3096) VAR(22)
      IF (VAR(22).LE.0.) VAR(22)=0.
      WRITE(7,3099) SQRT(VAR(22))

C
C---SENDING COST DIST. INFORMATION TO OUTPUT FILE COSTD.DAT
C

      DO 3020 J1=1,NKEYEN
C

      WRITE(7,*)
      WRITE(7,3083) KEYEVN(J1)
      KHOLD=(RR(J1+10)-LL(J1+10))/IWIDTH(J1+10)+2
      KHOLD=INT(KHOLD)

C
C---THE FOLLOWING <DO> LOOP SENDS THE EMPIRICAL DATA ON THE DENSITY
C---FUNCTION OF THE COST OF THE KEY EVENTS TO FILE COSTD.DAT
C

      DO 3021 J2=1,KHOLD
      IF (J2.EQ.1) THEN

```

```

        WRITE(7,3090)      LL(J1+10),DF(J1+10,1)
        GO TO 3021
    ENDIF
    IF (J2.EQ.KHOLD)      THEN
        WRITE(7,3092)      RR(J1+10),DF(J1+10,KHOLD)
        GO TO 3021
    ENDIF
    X1=LL(J1+10)+(J2-2)*IWIDTH(J1+10)
    X2=X1+IWIDTH(J1+10)
    X3=DF(J1+10,J2)
    WRITE(7,3091)      X1,X2,X3
C
3021  CONTINUE
C
C---THE FOLLOWING <DO> LOOP SENDS THE DATA ON THE DISTRIBUTION FUNC.
C---TO THE FILE.
C
    SUM=0.00
    DO 3022  J2=1,KHOLD-1
        SUM=SUM+DF(J1+10,J2)
        X1=LL(J1+10)+(J2-1)*IWIDTH(J1+10)
        WRITE(7,3094)      X1,SUM
3022  CONTINUE
C
C---THE OBSERVED MEAN AND VARIANCE OF THE REALIZATION TIME OF THE
C---KEY EVENTS (OBTAINED FROM THE MONTE CARLO SIM.) IS ALSO SENT
C---TO THE FILE.
C
    WRITE(7,3095)      MEAN(J1+10)
    WRITE(7,3096)      VAR(J1+10)
    IF (VAR(J1+10).LE.0.)      VAR(J1+10)=0.
    WRITE(7,3099)      SQRT(VAR(J1+10))
C
3020  CONTINUE
C
C---THE FOLLOWING SENDS THE CRITICAL INDICES OF THE ACTIVITIES TO
C---THE, ABOVE, DATA FILE.
C
    WRITE(4,3098)
3098  FORMAT(/1X,' ---- CRITICAL INDEXES ---- ')
C
    DO 3029  J2=1,NACT
        WRITE(4,3097)      J2,CI(J2)
3097  FORMAT(1X,'ACTIVITY ',12,1X,'HAS A CRITICAL INDEX = ',F7.4)
3029  CONTINUE
C
3088  FORMAT(/1X,'DISTRIBUTION INFO. ABOUT THE KEY EVENTS.')
3090  FORMAT(1X,'Pr ( X <= ,15,') = ,F8.4)
3092  FORMAT(1X,'Pr ( X > ,15,') = ,F8.4)
3091  FORMAT(1X,'Pr ( ,F9.3,'< X <= ,F9.3,) = ,F8.4)
3094  FORMAT(1X,'Pr ( X <= ,F9.3,) = ,F8.4)
3095  FORMAT(/1X,'THE MEAN OF THE DIST. = ,F15.4)
3096  FORMAT(/1X,'THE VARIANCE OF THE DIST. = ,F15.4)

```

```

3099 FORMAT(1X,'THE      STD. DEV. OF THE DIST. =',F15.4)
C
    RETURN
END
C-----
C
C     SUBROUTINE      O U T H E L P
C
C     THIS SUBROUTINE      PROVIDES      INFORMATION      ON THE OUTPUT      OF AN-COST
C
C-----
C
C     SUBROUTINE      OUTHELP
C
        WRITE(*,1)
1 FORMAT(25(/))
        WRITE(*,2)
2 FORMAT(5X,'THE      FOLLOWING      OUTPUT      IS AVAILABLE      ON THE RUN',//,
*10X,'          FILE                      DATA',//,
*10X,'1.      KEDIST.DAT      ---      i) EMPIRICAL      DENSITY      AND DIST.',//,
*10X,'          FUNCTIONS      ON REALIZATION',//,
*10X,'          TIME OF KEY EVENTS',//,
*10X,'          ii) ESTIMATED      CRITICAL      INDICES',//,
*10X,'2.      COSTD.DAT      ---      i) EMPIRICAL      DENSITY      AND DIST.',//,
*10X,'          FUNCTIONS      ON COST      OF KEY',//,
*10X,'          EVENTS',//,
*10X,'          ii) EMPIRICAL      DENSITY      AND DIST.',//,
*10X,'          FUNCTIONS      ON TOTAL      PROJECT      COST',//,
*10X,'3.      <USER NAMED>      ---      GENERAL      INFO.      ON RUN',//,
*10X,'4.      CASHFLOW.DAT      ---      DATA      TO BE USED      BY PROGRAM      "CASH"',//)
PAUSE
C
        WRITE(*,3)
3 FORMAT(5(/),5X,'TO      VIEW      THE DISTRIBUTION      DATA,      AS WELL AS',//,
*5X,'EXAMINE      THE CASH FLOW      FOR THE PROJECT,      RUN PROGRAM      "CASH".',//,
*5X,'PROGRAM      CASH      WILL ALSO DO CASH FLOW CALCULATIONS      FOR THE',//,
*5X,'PROJECT.',//)
PAUSE
        WRITE(*,1)
C
    RETURN
END
C-----
C
C     SUBROUTINE      P A Y M E N T S
C
C     THIS SUBROUTINE      DETERMINES      THE DISBURSEMENTS      FOR EACH
C     PERIOD      AND EACH MONTE CARLO SAMPLE.      AT THE END OF THE MC
C     SIMULATION,      WE WILL HAVE AN AVERAGE      DISBURSEMENT      TO USE IN
C     THE DETERMINATION      OF PROFIT      MARGINS.
C
C-----

```

```

SUBROUTINE PAYMENTS(KEYDUR,NACT,CYCLE,ACOST,DURATN,ES,EF,SDISBUR,
*                      NMCS,MXPERD,CP1,GAMMA,SUBCO,SubM,NKEYEN,PCOST)
  INTEGER   NACT,CYCLE,NMCS,MXPERD,NKEYEN
  REAL      SDISBUR(100),TDURAT,ACOST(100),DURATN(100),ES(100),
*                  EF(100),CP1(100),GAMMA,SubM(100,10),KEYDUR(10)
  DOUBLE    PRECISION SUBCO(11),PCOST
  INTEGER   CCPER
  REAL      DISBUR(100),SUBPAY(10,100)

C
  NPERD=KEYDUR(NKEYEN)/CYCLE+3
  IF(NPERD.GT.MXPERD)      MXPERD=NPERD

C
  DO 6001 I=1,NKEYEN
  DO 6002 J=1,NPERD
    SUBPAY(I,J)=0
  6002 CONTINUE
  6001 CONTINUE

C
  DO 6003 I=1,NKEYEN+1
    SUBCO(I)=0
  6003 CONTINUE

C
  DO 6004 I=1,100
    DISBUR(I)=0.0
  6004 CONTINUE

C
  DO 6010 I=1,NACT
    IF (DURATN(I).EQ.0)          GO TO 6010
    HSTART=ES(I)
    HFINSH=EF(I)
  6150  MP=HSTART/CYCLE+1
        MR=(MP-1)*CYCLE
        MS=MP*CYLE
    IF (MS.GT.HFINSH)           GO TO 6160

C
    DISBUR(MP)=DISBUR(MP)+(MS-HSTART)*ACOST(I)/DURATN(I)
    DO 6005 I2=1,NKEYEN
      IF (SUBM(I,I2).NE.0)        THEN
        SUBPAY(I2,MP)=SUBPAY(I2,MP)+(MS-HSTART)*ACOST(I)*
*                                SUBM(I,I2)/DURATN(I)
      END IF
  6005 CONTINUE

C
    HSTART=MP*CYLE
    GO TO 6150

C
  6160  IF (MR.LT.HFINSH)       THEN
C
    IF (MR.LT.HSTART)           THEN
      DISBUR(MP)=DISBUR(MP)+(HFINSH-HSTART)*ACOST(I)/DURATN(I)
    DO 6165 I2=1,NKEYEN
      IF (SUBM(I,I2).NE.0)        THEN
        SUBPAY(I2,MP)=SUBPAY(I2,MP)+(HFINSH-HSTART)*ACOST(I)*

```

```

*                               SUBM(I,I2)/DURATN(I)
      END IF
6165    CONTINUE
C
      ELSE
        DISBUR(MP)=DISBUR(MP)+(HFINSH-MR)*ACOST(I)/DURATN(I)
        DO 6167  I2=1,NKEYEN
          IF (SUBM(I,I2).NE.0)      THEN
            SUBPAY(I2,MP)=SUBPAY(I2,MP)+(HFINSH-MR)*ACOST(I)*
              SUBM(I,I2)/DURATN(I)
        *               END IF
6167    CONTINUE
        END IF
C
      END IF
6010    CONTINUE
C
C---THE FOLLOWING <DO> LOOP ADDS IN THE COST CP1( ), WHICH IS THE
C---CONSTANT COST THAT THE ACTIVITY INCURS REGARDLESS OF DURATION
C
        DO 6020  J=1,NACT
          CCPER=INT(ES(J)/CYCLE)+1
C
          DISBUR(CCPER)=DISBUR(CCPER)+CP1(J)
          DO 6125  J2=1,NKEYEN
            IF (SUBM(J,J2).NE.0)      THEN
              SUBPAY(J2,CCPER)=SUBPAY(J2,CCPER)+CP1(J)*SUBM(J,J2)
            END IF
6125    CONTINUE
C
6020    CONTINUE
C
C --- CHECK ALGORITHM FOR FUTURE VALUE HERE!!!!
C
        DO 6040  I=1,NPERD
          DISBUR(I)=DISBUR(I)*(1+GAMMA*CYCLE*(I-1)/365)
6040    CONTINUE
C
        DO 6042  I=1,NKEYEN
        DO 6043  J=1,NPERD
          SUBPAY(I,J)=SUBPAY(I,J)*(1+GAMMA*CYCLE*(J-1)/365)
6043    CONTINUE
6042    CONTINUE
C
        DO 6028  I=1,NKEYEN
        DO 6029  J=1,NPERD
          SUBCO(I)=SUBCO(I)+SUBPAY(I,J)
6029    CONTINUE
6028    CONTINUE
C
C---DETERMINE TOTAL PROJECT COST
C
PCOST=0

```

```

        DO 3500 I=1,NKEYEN
          PCOST=PCOST+SUBCO(I)
3500  CONTINUE
C
        DO 6030 J=1,NPERD
          SDISBUR(J)=SDISBUR(J)+DISBUR(J)/NMCS
6030  CONTINUE
C
        RETURN
END
C-----.
C
C      SUBROUTINE      P C I N F O
C
C      THIS SUBROUTINE      GIVES      INFORMATION      ON      THE      ALLOCATION      OF      COST      OF
C      COMMON      ACTIVITIES.
C
C-----.
C
C      SUBROUTINE      PCINFO
C
        WRITE(*,1)
1 FORMAT(25(/))
        WRITE(*,2)
2 FORMAT(5X,'THE      COST      OF      COMMON      ACTIVITIES      CAN      BE      ALLOCATED      TO      ',/,
*5X,'ITS      KEY      EVENTS      BY      THE      FOLLOWING      METHODS:',//,
*15X,'1.      PROBABILITY      METHOD',/,,
*15X,'2.      USER      GIVEN      %'S',///,
*1X,'INPUT      INFORMATION      OPTION...OTHER      VALUES---RETURN)',//)
C
        READ(*,*)      IOPTION
        IF (IOPTION.LT.1.OR.IOPTION.GT.2)           RETURN
C
        IF (IOPTION.EQ.1)      THEN
          WRITE(*,1)
          WRITE(*,3)
3 FORMAT(5X,'THIS      COST      ALLOCATION      METHOD      DETERMINES      THE',/,
*5X,'PERCENTAGES      OF      THE      KEY      EVENTS      AS      FOLLOWS...',//,
*10X,'WEIGHT(i)      =      Pr(      X(i)<=X(j1)      ) *...*      Pr(      X(i)<=X(jN)      )      ',//,
*10X,'      --where      X(i)      denotes      the      r.v.      of      key      event      i',//,
*5X,'PERCENTAGE(i)      =      NORMALIZED      VALUE',//)
          PAUSE
          WRITE(*,4)
4 FORMAT(//5X,'FOR      MORE      INFORMATION      SEE      MASTER'S      THESIS',//,
*5X,'"PROJECT      BIDDING      UNDER      CHANCE      TIME      ESTIMATES"',//,
*5X,'by      Russell      S.      Vogtmann.',//)
          PAUSE
C
        ELSE
          WRITE(*,1)
          WRITE(*,5)
5 FORMAT(5X,'THIS      OPTION      ALLOWS      THE      USER      TO      INPUT      THE',/,
*5X,'PERCENTAGES      USING      HIS      OWN      DISCRETION.',//)

```

```

        PAUSE
      ENDIF
C
      RETURN
    END
C-----.
C
C      SUBROUTINE      R N G E N E R A T O R
C
C          THIS SUBROUTINE      GENERATES      THE RANDOM      NUMBERS      NEEDED
C          FOR      THE MONTE CARLO      SIMULATION.
C
C-----.
C
C      SUBROUTINE      RNGENERATOR      (NACT,DURATN,DNUM,P1,P2,P3,P4,ACOST,CDNUM,
*                                CP1,CP2,CP3,CP4,CP5,DIST,DURA,NOP,IX)
C
C          INTEGER      NACT,DNUM(100),CDNUM(100),NOP(100)
C          REAL      DURATN(100),P1(100),P2(100),P3(100),P4(100),CP1(100),
*                    CP2(100),CP3(100),CP4(100),ACOST(100),DIST(100,30),
*                    DURA(100,30),CP5(100)
C          REAL*8      IX
C
C---THIS LOOP OBTAINS VALUES FOR DURATN (THE DURATIONS OF ALL THE
C---ACTIVITIES IN THE NETWORK). IT ALSO CALLS SUBROUTINE RCOST TO
C---OBTAIN THE RANDOM VALUES OF THE COST OF THE ACTIVITIES.
C
      DO 9000  I=1,NACT
C
      GOTO  (9011,9012,9013,9014,9015,9016,9017),DNUM(I)
C
9011      CALL  UNICON(P3(I),P4(I),DURATN(I),IX)
      GO TO 8999
9012      CALL  TRIANGULAR(P3(I),P1(I),P4(I),DURATN(I),IX)
      GO TO 8999
9013      CALL  RNORMAL(P1(I),P2(I),P3(I),P4(I),DURATN(I),IX)
      GO TO 8999
9014      CALL  EXPON(P1(I),P2(I),P3(I),P4(I),DURATN(I),IX)
      GO TO 8999
9015      CALL  GAMMA(P1(I),P2(I),P3(I),P4(I),DURATN(I),IX)
      GO TO 8999
9016      CALL  BETA(P1(I),P2(I),P3(I),P4(I),DURATN(I),IX)
      GO TO 8999
9017      CALL  USER1(NOP,DIST,DURA,I,DURATN(I),IX)
C
C---HERE, I CALL SUBROUTINE RCOST TO OBTAIN THE RANDOM VALUES OF
C---THE COST OF THE ACTIVITIES.
C
8999      CALL  RCOST(DURATN(I),ACOST(I),CDNUM(I),CP2(I),CP3(I),CP4(I),
*                            CP5(I),IX)
C
      9000  CONTINUE
C

```

```

      RETURN
      END
C
C+++++SUBROUTINES
C
C      THE FOLLOWING PROGRAM AREA CONTAINS THE VARIOUS SUBROUTINES
C      TO GENERATE RANDOM NUMBERS FROM MANY DIFFERENT DISTRIBUTIONS.
C
C
C+++++
C
C      NORMAL DIST.          MEAN=XBAR          VARIANCE=VAR
C                      NMIN=MIN.      VALUE      NMAX=MAX.      VALUE
C+++++
C
C      SUBROUTINE RNORMAL(XBAR,VAR,NMIN,NMAX,VALUE,IX)
      REAL XBAR,VAR,NMIN,NMAX,VALUE
      REAL*8 IX
C
C---POLAR COORDINATE METHOD
C
9020 CALL RANDOM(IX,R1)
      CALL RANDOM(IX,R2)
      VALUE=XBAR+SQRT(-2*ALOG(R1)*VAR)*COS(2*3.14159*R2)
      IF (VALUE.LT.NMIN.OR.VALUE.GT.NMAX) GOTO 9020
      RETURN
      END
C+++++
C
C      UNIFORM--CONTINUOUS          A=LEFT    END    B=RIGHT    END
C
C+++++
C
C      SUBROUTINE UNICON(A,B,VALUE,IX)
      REAL A,B,VALUE
      REAL*8 IX
C
      CALL RANDOM(IX,X)
      VALUE=A+(B-A)*X
      RETURN
      END
C+++++
C
C      TRIANGULAR DIST.          A=LEFT    END    B=MODE    C=RIGHT    END
C
C+++++
C
C      SUBROUTINE TRIANGULAR(A,B,C,VALUE,IX)
      REAL A,B,C,VALUE
      REAL*8 IX
C

```

```

CALL RANDOM(IX,X)
IF(X.LE.(B-A)/(C-A))      THEN
  VALUE=A+SQRT((C-A)*(B-A)*X)
ELSE
  VALUE=C-SQRT((C-A)*(C-B)*(1-X))
ENDIF
RETURN
END
C+++++
C
C      GAMMA DIST.    --   GAMMA(ALPHA,BBETA)
C
C+++++
C
SUBROUTINE GAMMA(ALPHA,BBETA,NMIN,NMAX,DURATN,IX)
REAL BBETA,ALPHA,NMIN,NMAX,DURATN
REAL*8 IX
C
X=1.0
K=INT(ALPHA)
Q=ALPHA-K
IF (K.LE.0)  THEN
  CALL RANDOM(IX,U)
  Z=- ALOG(U)
  CALL BETA(Q,1-Q,0,1,Y,IX)
  DURATN=BBETA*(X+Y*Z)
  RETURN
ELSE
  CALL RANDOM(IX,U)
  TEMP=U
  IF (K.GT.1)  THEN
    DO 9025 I=1,K-1
      CALL RANDOM(IX,U)
      TEMP=TEMP*U
  9025 CONTINUE
  ENDIF
  X=- ALOG(TEMP)
  IF (Q.EQ.0)  THEN
    DURATN=BBETA*X
    RETURN
  ELSE
    CALL RANDOM(IX,U)
    Z=- ALOG(U)
    CALL BETA(Q,1-Q,0,1,Y,IX)
    DURATN=BBETA*(X+Y*Z)
  ENDIF
ENDIF
RETURN
END
C+++++
C
C      EXPONENTIAL   --   EX(DMEAN)
C

```

```

C+++++*****+
C
      SUBROUTINE    EXRON(DMEAN,DUMMY,NMIN,NMAX,DURATN,IX)
      REAL         DMEAN,DUMMY,NMIN,NMAX,DURATN
      REAL*8       IX
C
      9055  CALL    RANDOM(IX,X)
C
      DURATN=-ALOG(X)*DMEAN
      IF(DURATN.LT.NMIN.OR.DURATN.GT.NMAX)           GOTO  9055
      RETURN
      END
C+++++*****+
C
C     BETA DIST.      C=LEFT   ENDPOINT      D=RIGHT   ENDPOINT
C                   A=1ST    SHAPE   PAR.      B=2ND    SHAPE   PAR.
C
C+++++*****+
C
      SUBROUTINE    BETA(A,B,C,D,DURATN,IX)
      REAL         A,B,C,D,DURATN
      REAL*8       IX
      ITER=1
C
      9057  CALL    RANDOM(IX,U1)
      CALL    RANDOM(IX,U2)
      Y1=U1**(1/A)
      Y2=U2**(1/B)
      IF ((Y1+Y2).LE.1.0)      THEN
          Y=Y1/(Y1+Y2)
          DURATN=C+(D-C)*Y
          RETURN
      ELSE
          ITER=ITER+1
      ENDIF
C
      IF (ITER.LT.100)      THEN
          GOTO  9057
      ELSE
          WRITE(*,9058)
          STOP
      ENDIF
      9058  FORMAT(1X,  ' 100 INTERATIONS      OVER IN BETA WITHOUT SUCCESS')
      RETURN
      END
C+++++*****+
C
C     USER DEFINED DISCRETE DENSITIES
C
C     THESE ARE ORDERED PAIRS OF DURATIONS AND PROBABILITIES--
C     THE DURATIONS ARE STORED IN DURA, AND THE PROB.'S IN DIST
C
C+++++*****+

```

```

C
      SUBROUTINE      USER1(NOP,DIST,DURA,I,DURATN,IX)
      INTEGER         I,NOP(100)
      REAL            DIST(100,30),DURA(100,30),DURATN
      REAL*8          IX
C
      CALL    RANDOM(IX,X)
      CUMDIST=0.0
      DO 9060  II=1,NOP(I)
         CUMDIST=CUMDIST+DIST(I,II)
         IF (X.LE.CUMDIST)      THEN
            DURATN=DURA(I,II)
            RETURN
         ENDIF
9060   CONTINUE
9065   RETURN
      END
C
C+++++++
C
      RANDOM    UNIFORM(0,1)
C
C+++++++
C
      SUBROUTINE      RANDOM(IX,D)
      DOUBLE PRECISION   Y,A,P,IX,B15,B16,XHI,XALO,LEFTLO,FHI,K
      DATA   A/16807.D0/,B15/32768.D0/,B16/65536.D0/,P/2147483647.D0/
C
      XHI=IX/B16
      XHI=XHI-DMOD(XHI,1.D0)
      XALO=(IX-XHI*B16)*A
      LEFTLO=XALO/B16
      LEFTLO=LEFTLO-DMOD(LEFTLO,1.D0)
      FHI=XHI*A+LEFTLO
      K=FHI/B15
      K=K-DMOD(K,1.D0)
      IX=(((XALO-LEFTLO*B16)-P)+(FHI-K*B15)*B16)+K
      IF(IX.LT.0.D0)      IX=IX+P
      Y=IX*4.656612875E-10
      D=REAL(Y)
      IX=IX+1.0
      RETURN
      END
C+++++++
C
      SUBROUTINE      R_C_O_S_T
C
      THIS SUBROUTINE      DETERMINES      THE COST OF AN ACTIVITY
      IN A PARTICULAR      MONTE CARLO SAMPLE.      (TAKING      INTO ACCOUNT
      THE POSSIBLE      RANDOM VARIATION      OF COST).
C
C+++++++

```

```

SUBROUTINE RCOST(DURATN,ACOST,CDNUM,CP2,CP3,CP4,CP5,IX)
INTEGER CDNUM
REAL DURATN,ACOST,CP2,CP3,CP4,CP5
REAL*8 IX
C
GOTO(9071,9072,9073,9074),CDNUM
C
C---CONSTANT COST/UNIT TIME
9071 ACOST=CP2*DURATN
RETURN
C
C---COST=NORMAL R.V. ABOUT A MEAN=CONST.*DURATION AND A
C---SPECIFIED VARIANCE.
9072 CALL RNORMAL(CP2*DURATN,CP3,CP4,CP5,ACOST,IX)
RETURN
C
C---COST=UNIFORM R.V. ABOUT A MEAN=CONST.*DURATION AND SPECIFIED
C---DISTANCE BETWEEN ENDPOINTS AND MEAN.
9073 CALL UNICON(CP2*DURATN-CP3,CP2*DURATN+CP4,ACOST,IX)
RETURN
C
C---TRIANGULAR COST DIST. ABOUT A MODE=CONST.*DURATION AND SPECIFIED
C---DISTANCE BETWEEN ENDPOINTS AND MODE
9074 CALL TRIANGULAR(CP2*DURATN,CP2*DURATN-CP4,CP2*DURATN+CP5,
* ACOST,IX)
RETURN
END
C-----
C
C SUBROUTINE S A M P H E L P
C
C THIS SUBROUTINE PROVIDES INFORMATION ON THE SAMPLE SIZE DETERMINA-
C TION.
C-----
C
SUBROUTINE SAMPHHELP
C
WRITE(*,1)
1 FORMAT(25(/))
WRITE(*,2)
2 FORMAT(5X,'THIS PROGRAM IS ESTIMATING THE DISTRIBUTION FUNC-',//,
*5X,'TIONS OF DURATION AND COST AT VARIOUS KEY EVENTS. IN ',//,
*5X,'ORDER TO DO THIS WITH SUFFICIENT ACCURACY, WE MUST MAKE',//,
*5X,'THE SAMPLE SIZE LARGE ENOUGH.'//,
*5X,'THIS SAMPLE SIZE CAN BE DETERMINED VIA THE KOLMOGOROV',//,
*5X,'SMIRNOV STATISTIC FOR GOODNESS-OF-FIT. THIS PROGRAM',//,
*5X,'USES THE LIMITING STATISTICS (AS SAMPLE SIZE INCREASES',//,
*5X,'TO INFINITY) TO DETERMINE THE SAMPLE SIZE.'//,
*5X,'THESE VALUES WERE TABULATED BY N. SMIRNOV IN "TABLE FOR',//,
*5X,'ESTIMATING THE GOODNESS OF FIT OF EMPIRICAL DISTRIBUTIONS',//,
*5X,'ANNALS OF MATHEMATICAL STATISTICS, 19(1948), p.279-281',//)
PAUSE

```

```

      WRITE(*,1)
C
      RETURN
      END
C-----.
C
C      SUBROUTINE      S A M P L E S I Z E
C
C      THIS SUBROUTINE      DETERMINES      THE REQUIRED      SAMPLE      SIZE FOR THE
C      REQUIREMENTS      OF THE USER.
C
C-----.
C
C      SUBROUTINE      SAMPLESIZE(NMCS)
C
      INTEGER      NMCS
      REAL      D(11),A(11)
      CHARACTER*1      NCHAR
      DATA      D / 0.826,0.861,0.895,0.932,0.973,1.02,1.073,1.138,1.225,
      *1.36,1.63      /
      DATA      A / 0.5,0.55,0.6,0.65,0.7,0.75,0.8,0.85,0.9,0.95,0.99      /
C
      8099  WRITE(*,8100)
      8100  FORMAT(25(/))
C
      WRITE(*,8105)
      8105  FORMAT(5X,'THIS      PORTION      OF THE PROGRAM      DETERMINES      THE NECESSARY',//,
      *5X,'SAMPLE      SIZE FOR THE MONTE CARLO      SIMULATION',//,
      *10X,'1.      SAMPLE      SIZE INFORMATION',//,
      *10X,'2.      PROCEED      WITH SAMPLE      SIZE DETERMINATION',//,
      *10X,'3.      TERMINATE      PROGRAM',//,
      *5X,'ENTER      CHOICE',//)
      READ(*,*)      ICH
      IF (ICH.LT.1.OR.ICH.GT.3)      THEN
          WRITE(*,*)      'OUT OF RANGE      -- TRY AGAIN CLOWN'
          GOTO 8099
      ENDIF
C
      IF (ICH.EQ.3)      STOP
      IF (ICH.EQ.1)      THEN
          CALL  SAMPHLP
          GOTO 8099
      ENDIF
C
      WRITE(*,8100)
C
      WRITE(*,8106)
      8106  FORMAT(///,5X,'INPUT      THE MAXIMUM      DIFFERENCE      BETWEEN      THE TRUE',//,
      *5X,'PROBABILITY      DISTRIBUTIONS      AND      THE SAMPLED      DISTRIBUTIONS',//,
      *5X,'(e.g.      .01)',//)
      READ(*,*)      DK
      8109  WRITE(*,8110)
      8110  FORMAT(///,5X,'INPUT      THE ALPHA      LEVEL      (FOR      A 1-ALPHA      CONFIDENCE)',/

```

```

*,5X,'--ALLOWABLE      RANGE IS FROM .01 TO .5',//)
READ(*,*) RAL
IF (RAL.LT.0.01.OR.RAL.GT.0.5)      THEN
  WRITE(*,*) 'OUT OF RANGE'
  WRITE(*,8100)
  GOTO 8109
ENDIF

C
VAL=0.0
IF (RAL.LE.0.5.AND.RAL.GT.0.45)      THEN
  CALL SSZ(D(1),D(2),A(1),A(2),RAL,VAL)
ELSE IF (RAL.LE.0.45.AND.RAL.GT.0.40)  THEN
  CALL SSZ(D(2),D(3),A(2),A(3),RAL,VAL)
ELSE IF (RAL.LE.0.40.AND.RAL.GT.0.35)  THEN
  CALL SSZ(D(3),D(4),A(3),A(4),RAL,VAL)
ELSE IF (RAL.LE.0.35.AND.RAL.GT.0.30)  THEN
  CALL SSZ(D(4),D(5),A(4),A(5),RAL,VAL)
ELSE IF (RAL.LE.0.30.AND.RAL.GT.0.25)  THEN
  CALL SSZ(D(5),D(6),A(5),A(6),RAL,VAL)
ELSE IF (RAL.LE.0.25.AND.RAL.GT.0.20)  THEN
  CALL SSZ(D(6),D(7),A(6),A(7),RAL,VAL)
ELSE IF (RAL.LE.0.20.AND.RAL.GT.0.15)  THEN
  CALL SSZ(D(7),D(8),A(7),A(8),RAL,VAL)
ELSE IF (RAL.LE.0.15.AND.RAL.GT.0.10)  THEN
  CALL SSZ(D(8),D(9),A(8),A(9),RAL,VAL)
ELSE IF (RAL.LE.0.10.AND.RAL.GT.0.05)  THEN
  CALL SSZ(D(9),D(10),A(9),A(10),RAL,VAL)
ELSE IF (RAL.LE.0.05.AND.RAL.GE.0.01)  THEN
  CALL SSZ(D(10),D(11),A(10),A(11),RAL,VAL)
ENDIF

C
NMCS=(VAL/DK)**2
WRITE(*,8100)
WRITE(*,8115) NMCS
8115 FORMAT(5X,'THE SAMPLE SIZE NECESSARY TO SATISFY THE GIVEN',//,
&5X,'REQUIREMENTS IS ',16,'. DO YOU WANT THE MONTE CARLO',//,
&5X,'SIMULATION TO TAKE THIS MANY SAMPLES (Y or N)',//)
READ(*,8120) NCHAR
8120 FORMAT(A1)

C
IF (NCHAR.EQ.'N'.OR.NCHAR.EQ.'n')      THEN
  WRITE(*,8125)
8125 FORMAT(///,'THEN INPUT THE NUMBER YOU WANT TO TAKE',//)
  READ(*,*) NMCS
ENDIF

C
RETURN
END

C-----.
C
C      SUBROUTINE S E P A R A T E
C
C      THIS SUBROUTINE SEPARATES THE COST OF ACTIVITIES CON-
```

```

C      TAINED IN THE SUBGRAPHS OF MORE THAN ONE KEY EVENT (I.E. COM-
C      MON ACTIVITIES).
C
C      ---THE USER CAN CHOOSE THE PERCENTAGES TO ATTRIBUTE TO EACH
C      KEY ACTIVITY, OR HE CAN LET THE PROGRAM SEPARATE THE COST
C      AS FOLLOWS:
C
C          WEIGHT(i)= Pr { X(i)<=X(j1) } * ... * Pr { X(i)<=X(jN) }
C
C          **PERCENTAGE(i)=NORMALIZED VALUES OF WEIGHT(i)
C
C          --THIS METHOD ASSUMES THAT THE REALIZATION TIME PDF'S ARE
C          --NORMALLY DISTRIBUTED. --> SEE MASTER'S THESIS FOR DETAILS
C
C-----.
C
C          SUBROUTINE SEPARATE (SUBM,J2,NKEYEN,NODEST,NODEFI,KEYEVN,AVERG,
C          *                      STDV,PERCEN,NACT,ACOST)
C          INTEGER J2,NKEYEN,NODEST(100),NODEFI(100),KEYEVN(10),NACT
C          REAL    SUBM(100,10),AVERG(10),STDV(10),PERCEN(100,10),ACOST(100)
C
C          INTEGER POINTER(10),METHOD,FLAG,NUM
C          REAL    W(10),WTOT,TEMP
C
C--INITIALIZE ARRAY PERCEN TO ZERO
C
DO 2000 J3=1,NACT
DO 2001 J1=1,NKEYEN
PERCEN(J3,J1)=0.
C
C---DO HOUSEKEEPING ON MATRIX SUBM
C
IF (SUBM(J3,J1).LT.0.000001)           SUBM(J3,J1)=0.0
C
2001 CONTINUE
2000 CONTINUE
C
DO 2002 J2=1,NACT
C
DO 2025 II=1,NKEYEN
POINTER(II)=0
W(II)=0
2025 CONTINUE
C
C---DETERMINE IF ACTIVITY IS COMMON TO MORE THAN ONE KEY EVENT
C
TOTAL=0
DO 2003 J4=1,NKEYEN
TOTAL=TOTAL+SUBM(J2,J4)
2003 CONTINUE
C
C----GO TO NEXT ACTIVITY IF UNIQUE TO ONE KEY EVENT
C

```

```

      IF (TOTAL.LE.ACOST(J2))          GOTO 2002
C
2089  WRITE(*,2090)      J2,NODEST(J2),NODEFI(J2)
2090  FORMAT(//1X,'      ACTIVITY ',I2,' FROM NODE ',I4,' TO NODE ',I4)
      WRITE(*,2091)
      WRITE(*,2092)
2091  FORMAT(1X,'      ')
2092  FORMAT(1X,'      is common to the following KEY EVENTS:')
C
      DO 2005  J3=1,NKEYEN
         IF (SUBM(J2,J3).NE.0.0)        THEN
            POINTER(J3)=1
            PERCENT(J2,J3)=1
            WRITE(*,2093)      KEYEVN(J3)
         ENDIF
2005  CONTINUE
2093  FORMAT(1X,I4)
C
2140  WRITE(*,2091)
      WRITE(*,2094)
      WRITE(*,2091)
      WRITE(*,2095)
      WRITE(*,2096)
      WRITE(*,2098)
2094  FORMAT(//1X,'WHAT      METHOD      OF SEPARATION      DO YOU WANT?')
2095  FORMAT(1X,'      PROBABILITY      METHOD      ----- 1')
2096  FORMAT(1X,'      USER GIVEN %'S      ----- 2')
2098  FORMAT(1X,'      **information**      ----- 10')
C
      READ(*,*)      METHOD
C
      IF (METHOD.EQ.10)      THEN
         CALL PCINFO
         GOTO 2089
      ENDIF
C
      IF (METHOD.LT.1.OR.METHOD.GT.2)      THEN
         WRITE(*,2091)
         WRITE(*,2144)
2144  FORMAT(5X,'value      OUT-OF-RANGE      --- try again')
         GOTO 2140
      ENDIF
C
C-----USER      DECIDING      HIS OWN SEPARATION      PERCENTAGES-----
C
      IF (METHOD.EQ.2)      THEN
2050  DO 2010  J3=1,NKEYEN
         IF (POINTER(J3).EQ.1)      THEN
            WRITE(*,2097)      KEYEVN(J3)
            READ(*,*)      PERCENT(J2,J3)
         ENDIF
2010  CONTINUE
C

```

```

      SU=0
      DO 2011 J3=1,NKEYEN
         PERCENT(J2,J3)=PERCENT(J2,J3)/100
         SU=SU+PERCENT(J2,J3)
2011   CONTINUE
C
      IF (SU.NE.1)      THEN
         WRITE(*,2099)
         GO TO 2050
      ENDIF
      ENDIF
C
2099  FORMAT(1X,'DOES      NOT ADD TO 1 --- TRY AGAIN')
2097  FORMAT(1X,'Input      percentage for KEY EVENT',13)
C
C-----PROBABILITY          METHOD-----
C
      IF (METHOD.EQ.1)      THEN
C
C---DETERMINE      KEY EVENT      THAT      HAS      SMALLEST      MEAN,      MARK      WITH      FLAG
C
         TEMP=100000000.00
         DO 2100 J3=1,NKEYEN
            IF (POINTER(J3).NE.0)      THEN
               IF (AVERG(J3).LT.TEMP)      THEN
                  TEMP=AVERG(J3)
                  FLAG=J3
               ENDIF
            ENDIF
2100   CONTINUE
C
C---DETERMINE      Pr { X(s)  <=  X(i)  }
C
         DO 2105 J3=1,NKEYEN
            IF (POINTER(J3).NE.0      .AND.      J3.NE.FLAG)      THEN
               Z=(AVERG(J3)-AVERG(FLAG))/(SQRT(STDV(FLAG)**2+STDV(J3)**2))
C
C---PHIZ      DENOTES      THE      Pr { X(s)  <=  X(i)  }
C
            CALL STDNOR(Z,PHIZ)
C
C---PLACE      NO      WEIGHT      ON      KEY      EVENT      i      IF      Pr { X(s)  <=  X(i)  }  >=  0.9
C---(THIS      IS      AN      ARBITRARY      SETTING)
C
            IF (PHIZ.GE.0.9)      THEN
               POINTER(J3)=0
               PERCENT(J2,J3)=0
            ENDIF
C
            ENDIF
2105   CONTINUE
C
C---DETERMINE      WEIGHT(I)      AS      SHOWN      IN      PREAMBLE      TO      THIS      SUBROUTINE

```

```

C---( SEE ABOVE )
C
      DO 2160 J5=1,NKEYEN
         IF (POINTER(J5).NE.1)          GOTO 2160
         W(J5)=1
      DO 2165 J6=1,NKEYEN
         IF (J6.EQ.J5.OR.POINTER(J6).NE.1)      GOTO 2165
C
         Z=(AVERG(J6)-AVERG(J5))/(SQRT(STDV(J6)**2+STDV(J5)**2))
         CALL STDNOR(Z,PHIZ)
C
         W(J5)=W(J5)*PHIZ
C
      2165 CONTINUE
      2160 CONTINUE
C
      WTOT=0.0
      DO 2030 J3=1,NKEYEN
         WTOT=WTOT+W(J3)
      2030 CONTINUE
C
      DO 2115 J3=1,NKEYEN
         IF (POINTER(J3).NE.0)      THEN
            W(J3)=W(J3)/WTOT
            PERCENT(J2,J3)=W(J3)
         ENDIF
      2115 CONTINUE
C
      WRITE(*,2189)      J2
      WRITE(3,2189)      J2
      WRITE(3,2191)
      WRITE(*,2191)
      DO 2120 J3=1,NKEYEN
         IF (PERCENT(J2,J3).EQ.0)      GO TO 2120
         WRITE(*,2190)      100*PERCENT(J2,J3),KEYEVN(J3)
         WRITE(3,2190)      100*PERCENT(J2,J3),KEYEVN(J3)
      2120 CONTINUE
      2191 FORMAT(1X,'PERCENTAGE      TO KEY EVENTS OF COMMON ACT.')
      2190 FORMAT(F6.2,1X,'PERCENT      TO KEY EVENT--',14)
      2189 FORMAT(1X,'ACTIVITY      ',12)
      ENDIF
C
      C---CONTINUE      ORIGINAL      DO LOOP OVER ACTIVITIES
C
      2002 CONTINUE
C
      RETURN
      END
C-----.
C
C      SUBROUTINE      S M C O R R
C
C      THIS SUBROUTINE      KEEPS TRACK OF THE SUM AND THE SUM OF SQUARES OF

```

```

C      THE COST AND DURATION OF THE KEY EVENTS TO BE USED LATER TO GET
C      VALUES OF SAMPLE CORRELATION AND A LEAST SQUARES FIT OF THE DATA.
C
C.....
C
C      SUBROUTINE     SMCORR(PCOST,SUBCO,KEYDUR,NKEYEN,SSUM,SSUMSQ,SUMXY)
C
C      INTEGER      NKEYEN
C      REAL        KEYDUR(10)
C      DOUBLE PRECISION   SSUM(21),SSUMSQ(21),SUMXY(11),SUBCO(11),PCOST
C
C      DO 3600 I=1,NKEYEN
C          SSUM(I)=SSUM(I)+KEYDUR(I)
C          SSUMSQ(I)=SSUMSQ(I)+KEYDUR(I)*KEYDUR(I)
C          SUMXY(I)=SUMXY(I)+KEYDUR(I)*SUBCO(I)
C          SSUM(I+10)=SSUM(I+10)+SUBCO(I)
C          SSUMSQ(I+10)=SSUMSQ(I+10)+SUBCO(I)*SUBCO(I)
3600    CONTINUE
C
C          SSUM(21)=SSUM(21)+PCOST
C          SSUMSQ(21)=SSUMSQ(21)+PCOST*PCOST
C          SUMXY(11)=SUMXY(11)+KEYDUR(NKEYEN)*PCOST
C
C      RETURN
C      END
C.....
C
C      SUBROUTINE     S S Z
C
C      THIS SUBROUTINE CALCULATES THE SAMPLE SIZE USING A LINEAR INTER-
C      POLATION BETWEEN ENDPOINTS (SEE SAMPLE SIZE INFO. FOR MORE)
C
C.....
C
C      SUBROUTINE     SSZ(X1,X2,Y1,Y2,RAL,VAL)
C      REAL      X1,X2,Y1,Y2,RAL,VAL
C
C      SLOPE=(Y2-Y1)/(X2-X1)
C      B=Y1-SLOPE*X1
C
C      VAL=(1-RAL-B)/SLOPE
C
C      RETURN
C      END
C.....
C
C      SUBROUTINE     S T D N O R
C
C      THIS SUBROUTINE COMPUTES THE Pr ( X <= x ) FOR A STANDARD
C      NORMAL VARIABLE.
C      THE PROBABILITY COMPUTED IS DENOTED BY PHIZ.

```

```

C-----.
C
C      SUBROUTINE      STDNOR(Z,PHIZ)
C
C      REAL      Z,PHIZ
C      DOUBLE PRECISION     PI
C      DATA    PI/3.141592653589793/
C
C      Y=Z/SQRT(2.0)
C      IF (Z.LE.0)      Y=-Y
C      S=0
C
C      DO 100 I=1,37
C          RI=I
C          S=S+EXP( RI*RI/25.)/RI*SIN(2*RI*Y/5.)
C 100   CONTINUE
C
C      S=S+Y/5.
C      S=2*S/PI
C      PHIZ=(1+S)/2.
C
C      IF (Z.GE.0.)      GOTO 1780
C      PHIZ=(1-S)/2.
C 1780  IF (Z.LE.8.3)      GOTO 1800
C      PHIZ=1
C 1800  IF (Z.GE.-8.3)      GOTO 1820
C      PHIZ=0
C
C 1820  RETURN
C      END
C-----.
C
C      SUBROUTINE      S U B N E T
C
C      THIS SUBROUTINE      FINDS      THE SUBNETWORKS      OF      THE KEY EVENTS      AND
C      *****COSTS      TO      THE KEY EVENTS.
C-----.
C
C      SUBROUTINE      SUBNET(NKEYEN,NACT,KEYEVN,NODEFI,NODEST,ACOST,ASCEND,
C      *                      SUBCO,SUBM,PERCENT,FLAGONE)
C
C      INTEGER      NKEYEN,NACT,KEYEVN(10),NODEFI(100),NODEST(100),
C      *                      ASCEND(100),FLAGONE
C      REAL       ACOST(100),SUBCO(11),SUBM(100,10),PERCENT(100,10)
C
C      INTEGER      LP(100)
C      REAL       SUBN(100,10)
C
C
C---INITIALIZE      SUBNETWORK      MATRIX      TO      ZERO
C
C      DO 1001 K=1,NKEYEN

```

```

      DO 1000  I=1,NACT
      SUBN(I,K)=0.0
1000  CONTINUE
1001  CONTINUE
C
C---FIND      SUBNETWORKS      OF THE KEY EVENTS AND STORE IN SUBN
C
      DO 1005  K=1,NKEYEN
      LZ = KEYEVN(K)
      DO 1010  I=1,NACT
      LP(I)=0
1010  CONTINUE
1100  KT=0
      DO 1015  I=1,NACT
      IF (NODEFI(I).NE.LZ)          GO TO 1015
      IF (KT.EQ.0)      GO TO 1105
      LP(I)=1
      GO TO 1015
1105  SUBN(I,K)=ACOST(I)
      KT=1
      LE=NODEST(I)
1015  CONTINUE
      LZ=LE
      IF (LZ.NE.ASCEND(1))        GO TO 1100
1110  DO 1020  I=1,NACT
      IF (LP(I).NE.0)      GO TO 1115
1020  CONTINUE
      GO TO 1005
1115  KS=0
      DO 1025  I=1,NACT
      IF (LP(I).EQ.0)      GO TO 1025
      IF (KS.EQ.1)      GO TO 1025
      SUBN(I,K)=ACOST(I)
      LP(I)=0
      LZ=NODEST(I)
      KS=1
1025  CONTINUE
      GO TO 1100
1005  CONTINUE
C
C---UPDATE      SUBGRAPHS      BY REMOVING      ACTIVITIES      IN KEY EVENTS THAT
C---HAVE      KEY EVENTS      AS SUBSETS      (STORE      IN SUBM)
C
      DO 1050  I=1,NACT
      DO 1050  K=1,NKEYEN
      SUBM(I,K)=SUBN(I,K)
1050  CONTINUE
C
      MKEYEN=NKEYEN-1
      DO 1055  J=1,MKEYEN
      L=J+1
      DO 1056  K=L,NKEYEN
      DO 1057  I=1,NACT

```

```

        IF  (SUBN(I,J).GT.SUBN(I,K))          GO TO 1056
1057    CONTINUE
        DO 1058  I=1,NACT
            IF  (SUBN(I,J).EQ.0)          GO TO 1058
            SUBM(I,K)=0.
1058    CONTINUE
1056    CONTINUE
1055    CONTINUE
C
C-----.
C
C---ON INITIAL CALL, I NEED TO RETURN HERE---
C
        IF  (FLAGONE.EQ.0)      RETURN
C-----.
C
        DO 1070  I=1,NACT
            TOTAL=0.
            DO 1075  K=1,NKEYEN
                TOTAL=TOTAL+SUBM(I,K)
1075    CONTINUE
C
C---IF THE ACTIVITY IS COMMON TO MULTIPLE KEY EVENTS, WE NOW SPLIT
C---THE COST ACCORDING TO OUR PREVIOUS DECISION
C
        IF  (TOTAL.GT.ACOST(I))      THEN
            DO 1077  K=1,NKEYEN
                SUBM(I,K)=SUBM(I,K)*PERCENT(I,K)
1077    CONTINUE
            ENDIF
1070    CONTINUE
C
        WRITE(*,*)  'COST PERCENTAGES      TO KEY EVENTS:'
        WRITE(*,*)  ' '
        WRITE(*,1090)      (K,K=1,NKEYEN)
1090    FORMAT(/4X,'NS          NF',10('   KEY(''I2,'')'))
        DO 1076  I=1,NACT
            WRITE(*,1091)      NODEST(I),NODEFI(I),(SUBM(I,K),K=1,NKEYEN)
1091    FORMAT(1X,215,10(F10.2))
1076    CONTINUE
C
C
1081    RETURN
        END
C-----.
C
C     SUBROUTINE U P P A Y
C
C     UPDATE ARRAY PAY AND VAR. CAPITL CONTAINING THE AMOUNT OF
C     COST OBTAINED IN THE PERIOD OF THE KEY EVENT'S REALIZATION.
C
C-----.

```

```

SUBROUTINE      UPPAY(KEYDUR,PAY,MXPERD,CYCLE,NMCS,NKEYEN,SUBCO,CAPITL)
C
      INTEGER      NKEYEN,MXPERD,CYCLE,NMCS
      REAL         KEYDUR(10),PAY(10,100),CAPITL
      DOUBLE       PRECISION    SUBCO(11)
C
      REAL         TPAY(10,100),TDURAT
C
C----INITIALIZE      ARRAY      TPAY
C
      DO 1204  K1=1,NKEYEN
      DO 1205  K2=1,MXPERD
         TPAY(K1,K2)=0.
1205  CONTINUE
1204  CONTINUE
C
      DO 1200  K2=1,NKEYEN
         IMARK=KEYDUR(K2)/CYCLE
         RMARK=KEYDUR(K2)/CYCLE
         IF ((RMARK-IMARK).EQ.0.00)           THEN
            TPAY(K2,IMARK)=TPAY(K2,IMARK)+SUBCO(K2)
         ELSE
            TPAY(K2,IMARK+1)=TPAY(K2,IMARK+1)+SUBCO(K2)
         ENDIF
1200  CONTINUE
C
C----UPDATE      VALUES      FOR      MONTE      CARLO      SIM.----
C
      CAPITL=CAPITL+SUBCO(NKEYEN+1)/NMCS
      DO 1209  K2=1,NKEYEN
      DO 1210  K1=1,MXPERD
         PAY(K2,K1)=PAY(K2,K1)+TPAY(K2,K1)/NMCS
1210  CONTINUE
1209  CONTINUE
C
      RETURN
END
C-----
C
C      SUBROUTINE      X E X P E C
C
C      THIS SUBROUTINE      DETERMINES      THE      MEAN      AND      VARIANCE      OF      THE
C      ACTIVITIES      FOR      USE      IN      SUBROUTINE      INITIALIZE.
C
C-----
C
      SUBROUTINE      XEXPEC(XEXP,XSTD,NACT,P1,P2,P3,P4,DNUM,DIST,DURA,NOP)
C
      INTEGER      DNUM(100),NOP(100),NACT
      REAL        P1(100),P2(100),P3(100),P4(100),DIST(100,30),DURA(100,30),
*          XEXP(100),XSTD(100)
C
      DO 1950  I=1,NACT

```

```

Y1=P1(I)
Y2=P2(I)
Y3=P3(I)
Y4=P4(I)
Y5=Y4-Y3
GOTO (1952,1953,1954,1955,1956,1957,1958),DNUM(I)

C
C --- UNIFORM
C
1952   X=(Y3+Y4)/2.0
        ST=SQRT(Y5*Y5/12.0)
        GOTO 1959

C
C --- TRIANGULAR
C
1953   X=(Y1+Y3+Y4)/3.0
        ST=SQRT((Y3*(Y3-Y1)+Y4*Y5+Y1*(Y1-Y4))/18.0)
        GOTO 1959

C
C --- NORMAL
C
1954   X=Y1
        ST=Y2
        GOTO 1959

C
C --- EXPONENTIAL
C
1955   X=Y1
        ST=Y1
        GOTO 1959

C
C --- GAMMA
C
1956   X=Y1*Y2
        ST=SQRT(X*Y2)
        GOTO 1959

C
C --- BETA
C
1957   X=Y3+Y5*Y1/(Y1+Y2)
        ST=SQRT(Y5*Y5*Y1*Y2/((Y1+Y2)**2*(Y1+Y2+1)))
        GOTO 1959

C
C --- DISCRETE
C
1958   X=0
        X2=0
        DO 1951 I1=1,NOP(I)
             X=X+DIST(I,I1)*DURA(I,I1)
             X2=X2+DIST(I,I1)*DURA(I,I1)**2
1951   CONTINUE
        ST=SQRT(X2-X*X)
C

```

```
1959      XEXP(I)=X
          XSTD(I)=ST
1950  CONTINUE
      RETURN
      END
```

Appendix 9.4. Program Listing of CASH

```

OPEN(UNIT=2,FILE='CASHFLOW.DAT',STATUS='OLD')
OPEN(UNIT=3,FILE='CASHOUT.OUT',STATUS='NEW')

C
  IFLAGG=0
  WRITE(*,1)
1  FORMAT(25(/))
  WRITE(*,2)
2  FORMAT(/20X,'           PROGRAM          CASH',////,
     &20X,'           WRITTEN BY',////,
     &20X,'           RUSSELL      S.    VOGTMANN',///)
  PAUSE
  WRITE(*,1)

C -----
C   INPUT   VALUES   FROM FILE CASHFLOW.DAT
C -----
  WRITE(*,*) 'INPUTTING   VALUES   FROM FILE CASHFLOW.DAT'
  READ(2,90) NCYCLE
  READ(2,90) MXPERD
  READ(2,91) (SDISBUR(I),I=1,MXPERD)

90 FORMAT(10I5)
91 FORMAT(5E13.7)
  READ(2,90) NKEYEN
  READ(2,90) (IKEY(I),I=1,NKEYEN)
  DO 10 I=1,NKEYEN
    READ(2,91) (PAY(I,J),J=1,MXPERD)
10 CONTINUE
  READ(2,91) STPERC,PINIT
  DO 11 I=1,NKEYEN
    READ(2,91) DMEAN(I),DSTD(I)
    READ(2,91) RMEAN(I),RSTD(I)
11 CONTINUE
  READ(2,91) RMEAN(11),RSTD(11)
  DO 12 I=1,NKEYEN
    READ(2,92) LL(I),NRR(I),NCELLS(I),WIDTH(I)
    READ(2,91) (DF(I,J),J=1,(NCELLS(I)+2))
    READ(2,92) LL(I+10),NRR(I+10),NCELLS(I+10),WIDTH(I+10)
    READ(2,91) (DF(I+10,J),J=1,(NCELLS(I+10)+2))
12 CONTINUE
  READ(2,92) LL(22),NRR(22),NCELLS(22),WIDTH(22)
  READ(2,91) (DF(22,J),J=1,(NCELLS(22)+2))
92 FORMAT(1I0,I10,I10,F15.5)
  DO 13 I=1,NKEYEN
    READ(2,91) CORR(I),BHATO(I),Bhat1(I)
13 CONTINUE
  READ(2,91) CORR(11),BHATO(11),Bhat1(11)
  DO 14 I=1,NKEYEN
    READ(2,91) FRACN(I)
14 CONTINUE

C-----
  DO 300 I=1,10
    COST(I)=0.0
    DURN(I)=0.0
    PENALTY(I)=0.0

```

```

300 CONTINUE
C
C---DETERMINE THE EXPECTED TOTAL CASH "INFLOW" PER PERIOD
C
240 DO 244 I=1,100
      TPAY(I)=0.0
244 CONTINUE
C
      DO 242 I=1,MXPERD
      DO 241 J=1,NKEYEN
          TPAY(I)=TPAY(I)+PAY(J,I)
241 CONTINUE
242 CONTINUE
C
C---CALCULATE CDF'S AND STORE IN CDF
C
      CALL CUMDIST
      WRITE(*,1)
C
1000 WRITE(*,4)
4 FORMAT(/1X,'INPUT OPTION YOU WANT TO TAKE:',//,
&10X,'1. VIEW CASH FLOW ARRAYS',//,
&10X,'2. VIEW DISTRIBUTION FUNCTION INFORMATION',//,
&10X,'3. PERFORM DETERMINISTIC CASH FLOW PROBLEM',//,
&10X,'4. PERFORM PROBABILISTIC CASH FLOW PROBLEM',//,
&10X,'5. PROGRAM INFORMATION',//,
&10X,'6. -----EXIT PROGRAM-----',//)
      READ(*,*) NOPTION
      IF (NOPTION.LT.1.OR.NOPTION.GT.6) THEN
          WRITE(*,1)
          GOTO 1000
      ENDIF
C
      IF (NOPTION.EQ.1) CALL VIEW
      IF (NOPTION.EQ.2) CALL DISTFN(IFLAGG)
      IF (NOPTION.EQ.3) CALL DETERM(NOPTION)
      IF (NOPTION.EQ.4) CALL PROBAB(NOPTION,IFLAGG)
      IF (NOPTION.EQ.5) CALL HELPMAIN
      IF (NOPTION.EQ.6) STOP
      WRITE(*,1)
      GOTO 1000
C
      STOP
      END
C-----
C
C     SUBROUTINE C F H E L P
C
C     THIS SUBROUTINE PROVIDES INFORMATION ON THE CASH FLOW ARRAYS
C-----
C
SUBROUTINE CFHELP

```

```

C
      WRITE(*,1)
1 FORMAT(25(/))
      WRITE(*,2)
2 FORMAT(5X,'THE EXPECTED CASH FLOW PER PERIOD IS CALCULATED BY',//,
*5X,'PROGRAM AN-COST BY MEANS OF MONTE CARLO SIMULATION',//,
*5X,'IF THE USER HAS DETERMINED A PERCENTAGE OF COST TO RECEIVE',//,
*5X,'AT THE PROJECT START, IT IS DENOTED AS OCCURRING IN PERIOD',//,
*5X,'ZERO.',///)
      PAUSE
C
      RETURN
      END
C-----
C
C      SUBROUTINE      C F L O W
C
C      THIS SUBROUTINE      PERFORM      CASH      FLOW      CALCULATIONS
C
C-----
C
      SUBROUTINE      CFLW(PROPIT,RATIO,CASH,TCAPITAL,SDISBUR,PAY,ALPHA,
*                           BETA,RATE,DESI,POWER,MXPERD,FLAG2,CTERM,
*                           TCAPINIT,CMODEL,RMEAN,TPAY)
C
      INTEGER      MXPERD,FLAG2,CMODEL
      REAL        RATIO,CASH,TCAPITAL,SDISBUR(100),PAY(10,100),ALPHA,BETA,
*                  RATE,POWER,DESI,PROFIT,CTERM,TCAPINIT,RMEAN(11),TPAY(100)
C
      REAL        TIAF,TIBA,RETEN,REten
C
      IF (FLAG2.EQ.1)      THEN
          WRITE(3,1900)      RATIO
1900      FORMAT(/3X,'RATIO      (ACTIVITY      WORTH      / ACTIVITY      COST      ) =',F8.4)
      ENDIF
C
      TIAF=0.00
      TIBA=0.00
      RETEN=0.00
      TREten=0.00
      DO 1510  I=1,MXPERD+1
C
C-----
C
      IF (I.EQ.1)      THEN
          CASH=TCAPITAL-SDISBUR(I)
          CALL  INTRT(I,CASH,POWER,ALPHA,BETA,TIAF,TIBA,RETEN,FLAG2)
          GO TO 1510
      ENDIF
C
C-----
C
      IF (I.EQ.MXPERD+1)      THEN

```

```

CASH=CASH+TPAY(I-1)+TRETN
CTERM=CASH
IF (FLAG2.EQ.1) THEN
  WRITE(3,1991) CASH
1991  FORMAT(25X,'TERMINAL' CASH POSITION =',F10.3)
ENDIF
GO TO 1510
END IF

C
C-----
C
RETN=TPAY(I-1)*RATIO*RATE
TRETN=TRETN+RETN
CASH=CASH+TPAY(I-1)*RATIO*(1-RATE)*SDISBUR(I)
CALL INTRT(I,CASH,POWER,ALPHA,BETA,TIAF,TIBA,TRETN,FLAG2)
IF (FLAG2.EQ.1) THEN
  WRITE(3,1980) TRETN,RETN
1980  FORMAT(/15X,'CUMULATIVE' RETENTION =',F10.3,3X,'RETENTION=',F9.3/)
ENDIF

C
C-----
C
1510 CONTINUE
IF (CMODEL.EQ.1) PROFIT=(CASH-TCAPINIT)/TCAPINIT
IF (CMODEL.EQ.2) PROFIT=(CASH-TCAPINIT)/RMEAN(11)
IF (FLAG2.EQ.1) THEN
  WRITE(3,1995) PROFIT
1995  FORMAT(20X,'PROFIT' =',F10.3/)
ENDIF

C
1500 CONTINUE
C
RETURN
END

C-----
C
FUNCTION CUM(JJ,I)
C
THIS FUNCTION CALCULATES THE PROBABILITY THAT THE KEY EVENT JJ
IS REALIZED IN PERIOD I. IT USES A LINEAR INTERPOLATION.
C
C-----
C
REAL FUNCTION CUM(NEVENT,PERIOD)
C
COMMON/CFMV/SDISBUR(100),PAY(10,100),RMEAN(11),PINIT,MXPERD,NKEYEN
*,IKEY(10),TPAY(100),DMEAN(10),DF(22,102),LL(22),NRR(22),NCELLS(22)
*,WIDTH(22),DSTD(10),RSTD(11),CDF(22,102),CORR(11),BHATO(11)
*,BHAT1(11),FRACN(10)
COMMON/CFP/ALPHA,BETA,POWER,RATE,DESIRE,NCYCLE,CAPITAL,TOL,CMODEL
COMMON/DCV/COST(11),DURN(10),STPERC,PENALTY(10),PERCNT(22,20)
INTEGER NEVENT,PERIOD,RLEFT,RIGHT

```

```

      DOUBLE PRECISION V1,V2,SLOPE,B
C
      RLEFT=NCYCLE*(PERIOD-1)
      RIGHT=NCYCLE*PERIOD
C
      CUM=0.0
      V1=0.0
      V2=0.0
      SLOPE=0.0
      B=0.0
C
      IF (RLEFT.LT.LL(NEVENT)-WIDTH(NEVENT))           THEN
          V1=0.0
          GOTO 4100
      ENDIF
      IF (RLEFT.GT.NRR(NEVENT)+WIDTH(NEVENT))           THEN
          V1=1.0
          GOTO 4100
      ENDIF
C
      DO 4000 K=1,NCELLS(NEVENT)+2
          P1=LL(NEVENT)+WIDTH(NEVENT)*(K-2)
          P2=LL(NEVENT)+WIDTH(NEVENT)*(K-1)
          IF (RLEFT.GT.P1.AND.RLEFT.LE.P2)           THEN
              IF (K.EQ.1)     THEN
                  SLOPE=(CDF(NEVENT,1))/WIDTH(NEVENT)
              ELSE
                  SLOPE=(CDF(NEVENT,K)-CDF(NEVENT,K-1))/WIDTH(NEVENT)
              ENDIF
              B=CDF(NEVENT,K)-SLOPE*P2
              V1=SLOPE*RLEFT+B
              GOTO 4100
          ENDIF
      4000 CONTINUE
C
      4100 IF (RIGHT.LT.LL(NEVENT)-WIDTH(NEVENT))           THEN
          V2=0.0
          GOTO 4300
      ENDIF
      IF (RIGHT.GT.NRR(NEVENT)+WIDTH(NEVENT))           THEN
          V2=1.0
          GOTO 4300
      ENDIF
C
      DO 4200 K=1,NCELLS(NEVENT)+2
          P1=LL(NEVENT)+WIDTH(NEVENT)*(K-2)
          P2=LL(NEVENT)+WIDTH(NEVENT)*(K-1)
          IF (RIGHT.GT.P1.AND.RIGHT.LE.P2)           THEN
              IF (K.EQ.1)     THEN
                  SLOPE=CDF(NEVENT,1)/WIDTH(NEVENT)
              ELSE
                  SLOPE=(CDF(NEVENT,K)-CDF(NEVENT,K-1))/WIDTH(NEVENT)
              ENDIF

```

```

      B=CDF(NEVENT,K)-SLOPE*p2
      V2=SLOPE*RIGHT+B
      GOTO 4300
    ENDIF
  4200 CONTINUE
C
  4300 CUM=V2-V1
      RETURN
    END
C-----
C
C     SUBROUTINE      C U M D I S T
C
C     THIS SUBROUTINE      CALCULATES      THE CUMULATIVE      DIST. FUNC.'S
C
C-----
C
C     SUBROUTINE      CUMDIST
C
COMMON/CFMV/SDISBUR(100),PAY(10,100),RMEAN(11),PINIT,MXPERD,NKEYEN
*,IKEY(10),TPAY(100),DMEAN(10),DF(22,102),LL(22),NRR(22),NCELLS(22)
*,WIDTH(22),DSTD(10),RSTD(11),CDF(22,102),CORR(11),BHATO(11)
*,BHAT1(11),FRACN(10)
      DOUBLE PRECISION SUM
C
      MARK1=1
      MARK2=0
C
  3000 DO 3002 I=MARK1,NKEYEN+MARK2
      SUM=0.
      DO 3005 J=1,NCELLS(I)+2
          SUM=SUM+DF(I,J)
          CDF(I,J)=SUM
  3005 CONTINUE
  3002 CONTINUE
C
      IF (MARK1.EQ.1)      THEN
          MARK1=11
          MARK2=10
          GOTO 3000
      ENDIF
C
      IF (MARK1.EQ.11)      THEN
          MARK1=22
          MARK2=22-NKEYEN
          GOTO 3000
      ENDIF
C
      RETURN
    END
C-----
C
C     SUBROUTINE      D C F H E L P

```

```

C
C      THIS SUBROUTINE      PROVIDES      INFORMATION      ON THE CASH FLOW CALCULATIONS
C      IN THE CASE OF A DETERMINISTIC      NETWORK.

C
C-----.
C
C      SUBROUTINE      DCFHELP
C
C
        WRITE(*,1)
1 FORMAT(25(/))
        WRITE(*,2)
2 FORMAT(5X,'THIS      PORTION      OF THE PROGRAM      DOES CASH FLOW CALCULA-/,,
*5X,'TIONS      IN THE CASE OF A DETERMINISTIC      NETWORK.',//,
*5X,'YOU      WILL BE ASKED TO INPUT:',//,
*10X,'1.      INTEREST      RATE ON MONEY DEPOSITED',/,
*10X,'2.      INTEREST      RATE ON MONEY BORROWED',/,
*10X,'3.      RETENTION      RATE',/,
*10X,'4.      INITIAL      CAPITAL',/,
*10X,'5.      DESIRED      PROFIT      PERCENTAGE',/,
*10X,'6.      IF PROFIT      IS DEFINED      AS A FUNCTION      OF PROJECT      COST',/,
*10X,'      OR AS A FUNCTION      OF CAPITAL',/,
*10X,'7.      A TOLERANCE      LEVEL FOR USE IN THE BISECTION      METHOD',//)
        PAUSE
C
        WRITE(*,10)
10 FORMAT(5(/))
        WRITE(*,3)
3 FORMAT(5X,'THIS      CALCULATION      PROCEDURE      USES THE BISECTION',/,
*5X,'METHOD      TO CONVERGE      TO THE MARKUP      OF ACTIVITY      COST THAT',/,
*5X,'WILL      RESULT      IN THE DESIRED      PROFIT      PERCENTAGE.',//,
*5X,'YOU      MAY RUN AS MANY ALTERNATIVES      AS YOU LIKE.      THE RESULTS',/,
*5X,'WILL      BE SENT TO THE SCREEN,      AND TO AN OUTPUT      FILE NAMED',/,
*5X,'"CASHOUT.OUT"      RESIDING      ON THE DEFAULT      DRIVE.',//)
        PAUSE
C
        RETURN
        END
C-----.
C
C      SUBROUTINE      D E T E R M
C
C      THIS SUBROUTINE      DOES CASH FLOW CALCULATIONS      FOR DETERMINISTIC
C      PROBLEMS      AND CALCULATES      A FaRM.      IT CONVERGES      TO THE VALUE      USING
C      THE BISECTION      METHOD.

C-----.
C
C      SUBROUTINE      DETERM(NOPTION)
C
COMMON/CFMV/SDISBUR(100),PAY(10,100),RMEAN(11),PINIT,MXPERD,NKEYEN
*,IKEY(10),TPAY(100),DMEAN(10),DF(22,102),LL(22),NRR(22),NCELLS(22)
*,WIDTH(22),DSTD(10),RSTD(11),CDF(22,102),CORR(11),BHATO(11)
*,BHTA1(11),FRACN(10)

```

```

COMMON/CFP/ALPHA,BETA,POWER,RATE,DESIRE,NCYCLE,CAPITAL,TOL,CMODEL
      INTEGER     FLAG2,CMODEL
C
1549  WRITE(*,1550)
1550  FORMAT(25(/))
      WRITE(*,1551)
1551  FORMAT(//10X,'1.          PROCEED WITH CASH FLOW CALCULATIONS',//,
*10X,'2.      DETERMINISTIC CASH FLOW INFORMATION',//,
*10X,'3.      RETURN TO MAIN MENU',//)
      WRITE(*,1552)
1552  FORMAT(5X,'ENTER CHOICE')
      READ(*,*) ICHOICE
      IF (ICHOICE.EQ.2)      THEN
          CALL DCFHELP
          GOTO 1549
      ENDIF
      IF (ICHOICE.EQ.3)      RETURN
C
      CALL INPUT(NOPTION,ISTOP,IFLAGG)
C
      POWER=NCYCLE/365.0
      DESI=DESIRE/100.0
C
C---THE FOLLOWING IS A TESTING OF VALUES TO GET A RIGHT END STARTING
C---POINT FOR THE BISECTION METHOD
C
      TCAPINIT=CAPITAL
      TCAPITAL=CAPITAL+PINIT
      FLAG2=0
      TESTVAL=2
520   CALL CFLW(PROFIT,TESTVAL,CASH,TCAPITAL,SDISBUR,PAY,ALPHA,BETA,
      *           RATE,DESI,POWER,MXPERD,FLAG2,CTERM,TCAPINIT,CMODEL,
      *           RMEAN,TPAY)
C
      IF (PROFIT.GT.DESI)      THEN
          RATIO2=TESTVAL
          GO TO 530
      ELSE
          TESTVAL=TESTVAL+0.5
          G TO 520
      ENDIF
C
C---NOW I USE BISECTION TO CONVERGE TO THE FaRM
C
530   RATIO1=0.50
      CALL CFLW(PROFT1,RATIO1,CASH,TCAPITAL,SDISBUR,PAY,ALPHA,BETA,
      *           RATE,DESI,POWER,MXPERD,FLAG2,CTERM,TCAPINIT,
      *           CMODEL,RMEAN,TPAY)
C
C---THE FOLLOWING IS BASICALLY A WHILE LOOP FOR THE BISECTION
C
600   RATIO=RATIO1+(RATIO2-RATIO1)/2.0
C

```

```

      CALL  CFLOW(PROFIT,RATIO,CASH,TCAPITAL,SDISBUR,PAY,ALPHA,BETA,
      *          RATE,DESI,POWER,MXPERD,FLAG2,CTERM,TCAPINIT,CMODEL,
      *          RMEAN,TPAY)
C
      IF  (ABS(PROFIT-DESI).LT.TOL)           THEN
         CALL  DETOUT(NOPTION,RATIO)
         RETURN
      ENDIF
C
      IF  ((DESI-PROFT1)*(DESI-PROFIT).LT.0.00)           THEN
         RATIO2=RATIO
      ELSE
         RATIO1=RATIO
         PROFT1=PROFIT
      ENDIF
C
      GO TO 600
C
      RETURN
      END
C-----.
C
C      SUBROUTINE      D E T O U T
C
C      THIS SUBROUTINE      OUTPUTS      DATA      TO FILE      "CASHOUT.OUT"
C
C-----.
C
      SUBROUTINE      DETOUT(NOPTION,RATIO)
C
      COMMON/CFMV/SDISBUR(100),PAY(10,100),RMEAN(11),PINIT,MXPERD,NKEYEN
      *,IKEY(10),TPAY(100),DMEAN(10),DF(22,102),LL(22),NRR(22),NCELLS(22)
      *,WIDTH(22),DSTD(10),RSTD(11),CDF(22,102),CORR(11),BHATO(11)
      *,BHAT1(11),FRACN(10)
      COMMON/CFP/ALPHA,BETA,POWER,RATE,DESIRE,NCYCLE,CAPITAL,TOL,CMODEL
      REAL      RATIO
      INTEGER     FLAG2,NOPTION,CMODEL
C
1555  FLAG2=1
      TCAPINIT=CAPITAL
      TCAPITAL=CAPITAL+PINIT
      CALL  CFLOW(PROFIT,RATIO,CASH,TCAPITAL,SDISBUR,PAY,ALPHA,BETA,
      *          RATE,DESI,POWER,MXPERD,FLAG2,CTERM,TCAPINIT,CMODEL,
      *          RMEAN,TPAY)
      TWORTH=RMEAN(11)*RATIO
      WRITE(3,1900)
      WRITE(*,1900)
1900  FORMAT(10X,'*****DETERMINISTIC'                   RESULTS*****',//)
      WRITE(3,1901)      DESIRE
      WRITE(*,1901)      DESIRE
1901  FORMAT(2X,'IN      ORDER    TO MAKE',F6.2,'%      PROFIT    IN THIS PROJECT')
      WRITE(3,1902)      RATIO
      WRITE(*,1902)      RATIO

```

```

1902 FORMAT(/2X,'THE      BIDDING      SHOULD      BE',F8.4,'      TIMES      OF      THE')
1903      WRITE(3,1903)      RMEAN(11),TWORTH
1903      WRITE(*,1903)      RMEAN(11),TWORTH
1903 FORMAT(/2X,'PROJECT      COST      =',F12.4,'      THAT      IS',F12.4,)
1904      WRITE(3,1904)
1904      WRITE(*,1904)
1904 FORMAT(/2X,'UNDER      THE      CONSTRAINTS:      ')
1905      WRITE(3,1905)      CAPITAL
1905      WRITE(*,1905)      CAPITAL
1905 FORMAT(/8X,'INITIAL      CAPITAL      =',F10.2)
1906      WRITE(3,1906)      ALPHA
1907      WRITE(3,1907)      BETA
1908      WRITE(3,1908)      RATE
1906      WRITE(*,1906)      ALPHA
1907      WRITE(*,1907)      BETA
1908      WRITE(*,1908)      RATE
1906 FORMAT(/8X,'INTEREST      RATE      ON      MONEY      DEPOSIT      =',F6.4)
1907 FORMAT(/8X,'INTEREST      RATE      ON      MONEY      BORROWT      =',F6.4)
1908 FORMAT(/8X,'RETENTION      RATE      =      ',F6.4)
C
C      RETURN
C      END
C-----
C
C      SUBROUTINE      D I S T F N
C
C      THIS SUBROUTINE      ALLOWS      THE      USER      TO      VIEW      THE      DISTRIBUTION      FUNC.'S
C      OF DURATION      AND      COST      OF      THE      KEY      EVENTS      OF      THE      NETWORK.      IT      ALSO
C      WILL      DISPLAY      THE      CORRELATION      COEFFICIENT      BETWEEN      THE      DURATION      AND
C      COST      OF      THE      KEY      EVENTS,      AS      WELL      AS      DETERMINE      PERCENTILES      OF      THE
C      DISTRIBUTIONS.
C
C-----
C
C      SUBROUTINE      DISTFN(IFLAGG)
C
COMMON/CFMV/SDISBUR(100),PAY(10,100),RMEAN(11),PINIT,MXPERD,NKEYEN
*,IKEY(10),TPAY(100),DMEAN(10),DF(22,102),LL(22),NRR(22),NCELLS(22)
*,WIDTH(22),DSTD(10),RSTD(11),CDF(22,102),CORR(11),BHATO(11)
*,BHAT1(11),FRACN(10)
COMMON/DCV/COST(11),DURN(10),STPERC,PENALTY(10),PERCNT(22,20)
REAL LD,LC
CHARACTER*1      SFLAG
C
799  WRITE(*,800)
800  FORMAT(25(/))
     WRITE(*,801)
801  FORMAT(1X,'DISTRIBUTION      INFORMATION:',//,
     &5X,'1.      DISPLAY      DURATION/COST      DIST.',S1',/,
     &5X,'2.      DISPLAY      CORRELATION/REGRESSION      DATA',/,/
     &5X,'3.      DISPLAY      PERCENTILES',/,/
     &5X,'4.      DISPLAY      COST      FRACTIONS      AT      KEY      EVENTS',/,/
     &5X,'5.      --RETURN      TO      MAIN      MENU--',/,

```

```

&5X,'6.      DISTRIBUTION      INFORMATION',//,
&5X,'7.      EXIT      PROGRAM',//,
&1X,'ENTER      CHOICE',//)

C
      READ(*,*)      NV
      GOTO  (810,850,870,900,804,806,807),NV
C
C---RETURN      TO MAIN      MENU
C
      804  RETURN
C
C---CALL      SUBROUTINE      ON DISTRIBUTION      INFORMATION
C
      806  CALL  DTHELP
      WRITE(*,800)
      GOTO  799
C
C---EXIT      PROGRAM
C
      807  STOP
C
C---DISPLAY      COST      FRACTIONS      AT KEY      EVENTS
C
      900  WRITE(*,800)
      WRITE(*,903)
      903  FORMAT(5X,'THE      SIMULATION      RESULTED      IN THE FOLLOWING      FRACTIONS',//,
      *5X,'OF      COST      AT THE KEY      EVENTS:',//,
      *20X,'KEY      EVENT                  FRACTION      OF      COST',//)
      ITEMPI=0
      WRITE(*,904)      ITEMPI,STPERC
      904  FORMAT(20X,I5,15X,F5.2)
      DO 901  I=1,NKEYEN
          WRITE(*,902)      IKEY(I),FRACN(I)
      902  FORMAT(20X,I5,15X,F5.2)
      901  CONTINUE
      PAUSE
      WRITE(*,800)
      GOTO  799
C
C---WRITE      EMPIRICAL      DENSITIES      TO SCREEN
C
      810  WRITE(*,800)
      CALL  DWRITE
      PAUSE
      GOTO  799
C
C---WRITE      INFORMATION      ON CORRELATION      AND LEAST      SQUARES      ESTIMATORS
C
      850  WRITE(*,800)
      WRITE(*,851)
      851  FORMAT(1X,'INPUT      NUMBER      OF KEY      EVENT      TO DISPLAY      CORRELATION',//,
      &1X,'LEAST      SQUARES      DATA (0 FOR TOTAL      COST      VS.      PROJECT      DURATION)',//)
      READ(*,*)      NKEY

```

```

        IF (NKEY.EQ.0)      GOTO 860
        IF (NKEY.LT.IKEY(1).OR.NKEY.GT.IKEY(NKEYEN))          THEN
            WRITE(*,*)      'OUT OF RANGE --- RETURN TO MAIN'
            RETURN
        ENDIF
C
        DO 252 I=1,NKEYEN
            IF (IKEY(I).EQ.NKEY)      NNN=I
252    CONTINUE
C
        IF (CORR(NNN).EQ.-9999.)          THEN
            WRITE(*,800)
            WRITE(*,856)
856    FORMAT(5X,'NETWORK      IS DETERMINISTIC!!!',//,
&5X,'THIS ANALYSIS IS NOT APPLICABLE.')
            PAUSE
            GOTO 799
        ELSE
            WRITE(*,800)
            WRITE(*,852)      IKEY(NNN)
852    FORMAT(20X,'***** KEY EVENT',I5,' *****',//)
            WRITE(*,853)      BHATO(NNN),BHAT1(NNN),CORR(NNN)
853    FORMAT(10X,'SAMPLE      REGRESSION FUNCTION:',//,
&15X,'COST = ',F12.2,' + ',F12.2,' * DURATION',//,
&10X,'SAMPLE      CORRELATION COEFFICIENT= ',F4.2,/)
            PAUSE
            GOTO 799
        ENDIF
C
860    IF (CORR(11).EQ.-9999.)          THEN
            WRITE(*,800)
            WRITE(*,856)
            PAUSE
            GOTO 799
        ELSE
            WRITE(*,800)
            WRITE(*,854)
854    FORMAT(20X,'*****TOTAL COST VS. PROJECT DURATION*****',//)
            WRITE(*,855)      BHATO(11),BHAT1(11),CORR(11)
855    FORMAT(10X,'SAMPLE      REGRESSION FUNCTION:',//,
&15X,'TOTAL COST = ',F10.2,' + ',F10.2,' * PROJECT DURATION',//,
&10X,'SAMPLE      CORRELATION COEFFICIENT= ',F4.2,/)
            PAUSE
            GOTO 799
        ENDIF
C
C---DETERMINE      PERCENTILES      OF DISTRIBUTIONS      AND WRITE TO SCREEN
C
870    IF (IFLAGG.EQ.0)      CALL PRCNTL(IFLAGG)
875    WRITE(*,800)
            WRITE(*,876)
876    FORMAT(5X,'THIS      PORTION OF THE PROGRAM WILL DISPLAY',//,
&2X,'PERCENTILES      OF THE DISTRIBUTIONS.',//)

```

```

C
CALL PWRITE
GOTO 799
C
RETURN
END
C-----
C
C      SUBROUTINE      D T H E L P
C
C      THIS SUBROUTINE      PROVIDES      INFORMATION      ON THE EMPIRICAL      DISTRIBUTI-
C      TIONS      OF      THE      KEY      EVENTS      DETERMINED      IN PROGRAM      AN-COST.
C
C-----
C
SUBROUTINE      DTHHELP
C
100 WRITE(*,1)
1 FORMAT(25(/))
WRITE(*,2)
2 FORMAT(5X,'CHOOSE      INFORMATION      OPTION',//,
*10X,'1.      REALIZATION      TIME & COST DISTRIBUTIONS',//,
*10X,'2.      SAMPLE      REGRESSION      FUNCTION & CORRELATION      COEF',//,
*10X,'3.      DISTRIBUTION      PERCENTILES',//,
*10X,'4.      COST      FRACTIONS      AT KEY EVENTS',//,
*10X,'5.      RETURN      TO DISTRIBUTION      MENU',//)
READ(*,*)      NC
C
IF (NC.EQ.5)      RETURN
IF (NC.LT.1.OR.NC.GT.4)      THEN
      WRITE(*,*)      'OUT      OF      RANGE      ---      RETURN      TO DIST.      MENU'
      RETURN
ENDIF
C
GOTO (10,20,30,40),NC
C
10 WRITE(*,1)
WRITE(*,11)
11 FORMAT(5X,'THE      REALIZATION      TIME AND COST DISTRIBUTIONS      WERE',//,
*5X,'DETERMINED      VIA      MONTE      CARLO      SAMPLING      BY PROGRAM      AN-COST.'//,
*5X,'THE      COST      DISTRIBUTIONS      ARE      THE      COST      OF      THE      SUBGRAPHS      OF',//,
*5X,'THE      KEY      EVENTS.      IF      THERE      WERE      COMMON      ACTIVITIES      TO      MORE',//,
*5X,'THAN      ONE      KEY      EVENT,      IT'S      COST      WAS      SEPARATED      BY      AN      ALGO',//,
*5X,'RITHM      THAT      ASSIGNED      MORE      WEIGHT      TO      THE      KEY      EVENT      THAT',//,
*5X,'WAS      REALIZED      EARLIEST      AND      HAD      LOWER      VARIANCE.'//)
PAUSE
GOTO 100
C
20 WRITE(*,1)
WRITE(*,21)
21 FORMAT(5X,'THE      SAMPLE      REGRESSION      FUNCTION      IS      DETERMINED      VIA',//,
*5X,'LEAST      SQUARES,      AND      THE      SAMPLE      CORRELATION      COEFFICIENT      IS',//,
*5X,'CALCULATED      IN      THE      STANDARD      MANNER      OVER      THE      INDIVIDUAL',//,

```

```

*5X,'NETWORK      REALIZATIONS      IN THE MONTE CARLO SIMULATION.',//,
*5X,'THESE      VALUES      WILL      GIVE      AN      INDICATION      OF      THE      RELATIONSHIP',//,
*5X,'BETWEEN      THE      COST      AND      REALIZATION      TIME      OF      THE      KEY      EVENTS',//,
*5X,'AND      MAY      BE      HELPFUL      WHEN      PREPARING      A      BID      PACKAGE.',//)
PAUSE
GOTO 100
C
30 WRITE(*,1)
WRITE(*,31)
31 FORMAT(5X,'THE      PERCENTILES      OF      THE      DISTRIBUTIONS      ARE      CALCULATED',//,
*5X,'BY      LINEAR      INTERPOLATION      OF      THE      CUMULATIVE      DISTRIBUTION',//,
*5X,'FUNCTIONS.',//,
*5X,'A      VALUE      OF      -1      INDICATES      THAT      A      VALUE      COULD      NOT      BE      PROPERLY',//,
*5X,'COMPUTED      BECAUSE      THE      RANGE      OF      THE      EMPIRICAL      DISTRIBUTION',//,
*5X,'WAS      TOO      NARROW',//)
PAUSE
GOTO 100
C
40 WRITE(*,1)
WRITE(*,41)
41 FORMAT(5X,'THE      FRACTION      OF      TOTAL      PROJECT      COST      THAT      IS      RECEIVED',//,
*5X,'AT      EACH      KEY      EVENT      IS      THE      AVERAGE      OVER      ALL      MONTE      CARLO      SAM-',//,
*5X,'PLES.      NOTE:      THIS      FRACTION      IS      AFTER      THE      PERCENTAGE      IS      ',//,
*5X,'TAKEN      OUT      TO      RECEIVE      AT      THE      PROJECT      START.',//)
PAUSE
GOTO 100
C
RETURN
END
C-----
C
C      SUBROUTINE      D W R I T E
C
C      THIS      SUBROUTINE      WRITE'S      THE      DISTRIBUTIONS      TO      THE      SCREEN
C
C-----
C
SUBROUTINE      DWRITE
C
COMMON/CFMV/SDISBUR(100),PAY(10,100),RMEAN(11),PINIT,MXPERD,NKEYEN
*,IKEY(10),TPAY(100),DMEAN(10),DF(22,102),LL(22),NRR(22),NCELLS(22)
*,WIDTH(22),DSTD(10),RSTD(11),CDF(22,102),CORR(11),BHATO(11)
*,BHAT1(11),FRACN(10)
COMMON/DC/COST(11),DURN(10),STPERC,PENALTY(10),PERCNT(22,20)
REAL LC,LD,RC,RD
CHARACTER*1 SFLAG
C
WRITE(*,811)
811 FORMAT(1X,'INPUT      NUMBER      OF      KEY      EVENT      TO      DISPLAY      DIST.      FUNC.'S',
&1X,'(0,      FOR      TOTAL      COST)',//)
READ(*,*) NKEY
IF (NKEY.EQ.0)      GOTO 830
IF (NKEY.LT.IKEY(1).OR.NKEY.GT.IKEY(NKEYEN))      THEN

```

```

        WRITE(*,*)      'OUT OF RANGE   --- RETURN TO MENU'
        RETURN
    ENDIF
C
    DO 230 I=1,NKEYEN
        IF (IKEY(I).EQ.NKEY)          NNN=I
230  CONTINUE
C
    WRITE(*,800)
800  FORMAT(25(/))
    WRITE(*,812)
    WRITE(*,813)
812  FORMAT(20X,'DURATION',28X,'COST')
813  FORMAT(11X,'LEFT',4X,'RIGHT',4X,'PROB.',14X,'LEFT',4X,'RIGHT',4X,
  &'PROB.',//)
    LD=0
    RD=0
    LC=0
    RC=0
    ILIMIT=MAX(NCELLS(NNN)+2,NCELLS(NNN+10)+2)
    DO 820 I=1,ILIMIT
        IF (MOD(I,15).EQ.0)         THEN
            WRITE(*,*)      'Hit Return for more.'
            READ(*,893)      SFLAG
893  FORMAT(A1)
        ENDIF
        IF (I.EQ.1)      THEN
            WRITE(*,814)      LL(NNN),DF(NNN,I),LL(NNN+10),DF(NNN+10,I)
            LD=LL(NNN)
            RD=LD+WIDTH(NNN)
            LC=LL(NNN+10)
            RC=LC+WIDTH(NNN+10)
            GOTO 820
        ELSE IF (I.EQ.ILIMIT)      THEN
            IF (NCELLS(NNN).EQ.NCELLS(NNN+10))           THEN
                WRITE(*,815)      NRR(NNN),DF(NNN,I),NRR(NNN+10),DF(NNN+10,I)
            ELSE IF (NCELLS(NNN).GT.NCELLS(NNN+10))        THEN
                WRITE(*,821)      NRR(NNN),DF(NNN,I)
            ELSE
                WRITE(*,822)      NRR(NNN+10),DF(NNN+10,I)
            ENDIF
            WRITE(*,*)      'Hit return to continue'
            READ(*,893)      SFLAG
            GOTO 820
        ELSE
            IF (NCELLS(NNN)+2.GT.I.AND.NCELLS(NNN+10)+2.GT.I)      THEN
                WRITE(*,816)      LD,RD,DF(NNN,I),LC,RC,DF(NNN+10,I)
            ELSE IF (NCELLS(NNN)+2.EQ.I)           THEN
                WRITE(*,823)      NRR(NNN),DF(NNN,I),LC,RC,DF(NNN+10,I)
            ELSE IF (NCELLS(NNN)+2.LT.I)           THEN
                WRITE(*,824)      LC,RC,DF(NNN+10,I)
            ELSE IF (NCELLS(NNN+10)+2.EQ.I)        THEN
                WRITE(*,825)      LD,RD,DF(NNN,I),NRR(NNN+10),DF(NNN+10,I)

```

```

        ELSE IF (NCELLS(NNN+10)+2.LT.I)      THEN
          WRITE(*,826)      LD, RD, DF(NNN,I)
        ENDIF
        LD=RD
        RD=RD+WIDTH(NNN)
        LC=RC
        RC=RC+WIDTH(NNN+10)
      ENDIF
820  CONTINUE
814  FORMAT(11X,'----',2X,15,5X,F6.4,16X,'----',2X,15,5X,F6.4)
815  FORMAT(7X,15,9X,'----',2X,F6.4,12X,15,6X,'----'
821  FORMAT(7X,15,9X,'----',2X,F6.4,/,)
822  FORMAT(45X,15,6X,'----',5X,F6.4,/,)
816  FORMAT(7X,F8.2,2X,F8.2,2X,F6.4,12X,F8.2,2X,F8.2,2X,F6.4)
823  FORMAT(7X,15,8X,'----',2X,F6.4,12X,F8.2,2X,F8.2,2X,F6.4)
824  FORMAT(45X,F8.2,2X,F8.2,2X,F6.4)
825  FORMAT(7X,F8.2,2X,F8.2,2X,F6.4,12X,15,5X,'----',2X,F6.4)
826  FORMAT(7X,F8.2,2X,F8.2,2X,F6.4)

C
C---ECHO    MEANS    AND    STANDARD    DEVIATIONS    OF    DURATION    AND    COST
C
      WRITE(*,818)      DMEAN(NNN),RMEAN(NNN)
      WRITE(*,819)      DSTD(NNN),RSTD(NNN)
818  FORMAT(////,,5X,'      MEAN = ',F10.2,20X,'MEAN      =',F10.2)
819  FORMAT(5X,'STD      DEV. = ',F10.2,20X,'STD      DEV. =',F10.2,/,)
      RETURN

C
C---DISTRIBUTIONS      FOR    TOTAL    COST    DISTRIBUTION
C
830  WRITE(*,800)
831  WRITE(*,832)
832  WRITE(*,833)
832  FORMAT(20X,'COST')
833  FORMAT(11X,'LEFT',4X,'RIGHT',4X,'PROB.'/,)
      LC=0
      RC=0
      ILIMIT=NCELLS(22)+2
      DO 840 I=1,ILIMIT
        IF (MOD(I,15).EQ.0)      THEN
          WRITE(*,*)      'Hit Return for more.'
          READ(*,893)      SFLAG
        ENDIF
        IF (I.EQ.1)      THEN
          WRITE(*,834)      LL(22),DF(22,I)
          LC=LL(22)
          RC=LC+WIDTH(22)
          GOTO 840
        ELSE IF (I.EQ.ILIMIT)      THEN
          WRITE(*,835)      NRR(22),DF(22,I)
          WRITE(*,*)      'Hit return to continue'
          READ(*,893)      SFLAG
          GOTO 840
        ELSE

```

```

        WRITE(*,836)      LC,RC,DF(22,1)
        LC=RC
        RC=RC+WIDTH(22)
    ENDIF
840  CONTINUE
834  FORMAT(8X,'----',5X,I5,5X,F6.4)
835  FORMAT(7X,I5,9X,'----',2X,F6.4,/)
836  FORMAT(7X,F8.2,2X,F8.2,2X,F6.4)

C
C---ECHO    MEAN    AND    STANDARD    DEVIATION    OF    TOTAL    COST
C
        WRITE(*,838)      RMEAN(11),RSTD(11)
838  FORMAT(////,5X,'     MEAN   = ',F10.2,7X,'STD.       DEV.   = ',F10.2)
C
        RETURN
END

C-----
C
C      SUBROUTINE      H E L P M A I N
C
C      THIS      SUBROUTINE      PROVIDES      GENERAL      INFORMATION      ABOUT      PROGRAM      CASH
C-----
C
SUBROUTINE      HELPMAIN
C
        WRITE(*,1)
1  FORMAT(25(/))
        WRITE(*,2)
2  FORMAT(15X,'P      R O G R A M      C A S H',///,
*5X,'THIS      PROGRAM      IS      DESIGNED      TO      ASSIST      THE      PROJECT      MANAGER      IN',//,
*5X,'DETERMINING      A      BID      PACKAGE      FOR      PROJECTS      THAT      CAN      BE      MODELED',//,
*5X,'BY      DIRECTED      ACYCLIC      NETWORKS.',//)
        PAUSE
        WRITE(*,3)
3  FORMAT(//5X,'BEFORE      THIS      PROGRAM      CAN      BE      RUN,      YOU      NEED      TO      RUN',//,
*5X,'PROGRAM      AN-COST.      AN-COST      WILL      CREATE      FILE      CASHFLOW.DAT',//,
*5X,'WITH      THE      NECESSARY      DATA.',//)
        PAUSE
        WRITE(*,1)
        WRITE(*,4)
4  FORMAT(5X,'THIS      PROGRAM      ALLOWS      THE      FOLLOWING:',//,
*10X,'1.      VIEWING      OF      CASH      FLOW      ARRAYS',//,
*10X,'2.      VIEWING      OF      KEY      EVENT      DISTRIBUTION      INFORMATION',//,
*10X,'     ---REALIZATION      TIME      DISTRIBUTION',//,
*10X,'     ---COST      DISTRIBUTION',//,
*10X,'     ---REGRESSION      FUNCTION      AND      CORRELATION      COEF.',//,
*10X,'             (DURATION      vs.      COST)',//,
*10X,'     ---PERCENTILES      OF      DISTRIBUTIONS',//,
*10X,'     ---FRACTION      OF      PROJECT      COST      AT      KEY      EVENTS',//,
*10X,'3.      DETERMINISTIC      CASH      FLOW      CALCULATIONS',//,
*10X,'4.      PROBABILISTIC      CASH      FLOW      CALCULATIONS',//,

```

```

*5X,'NOTE:      FOR MORE INFORMATION      ON ANY OF THESE TOPICS,/,/
*5X,'      CHOOSE INFORMATION      ON SUB-MENUS.//'
PAUSE
WRITE(*,1)
C
RETURN
END
C-----
C
C      SUBROUTINE      I N P U T
C
C      THIS SUBROUTINE      OBTAINS      NEEDED      INPUT      VALUES
C
C-----
C
SUBROUTINE      INPUT(NOPTION,ISTOP,IFLAGG)
C
COMMON/CFMV/SDISBUR(100),PAY(10,100),RMEAN(11),PINIT,MXPERD,NKEYEN
*,IKEY(10),TPAY(100),DMEAN(10),DF(22,102),LL(22),NRR(22),NCELLS(22)
*,WIDTH(22),DSTD(10),RSTD(11),CDF(22,102),CORR(11),BHAT(11)
*,BHAT1(11),FRACN(10)
COMMON/CFP/ALPHA,BETA,POWER,RATE,DESIRE,NCYCLE,CAPITAL,TOL,CMODEL
COMMON/DCV/COST(11),DURN(10),STPERC,PENALTY(10),PERCNT(22,20)
INTEGER      CMODEL
CHARACTER*1      NCHAR
C
WRITE(*,325)
325 FORMAT(25(/))
WRITE(*,300)
300 FORMAT(5(/),1X,'INPUT      INTEREST      RATE      ON      MONEY      DEPOSITED')
READ(*,*)      ALPHA
WRITE(*,301)
301 FORMAT(5(/),1X,'INPUT      INTEREST      RATE      ON      MONEY      BORROWED')
READ(*,*)      BETA
WRITE(*,302)
302 FORMAT(5(/),1X,'INPUT      RETENTION      RATE')
READ(*,*)      RATE
IF(NOPTION.EQ.3)      THEN
      WRITE(*,303)
303 FORMAT(5(/),1X,'INPUT      DESIRED      PROFIT      PERCENTAGE')
READ(*,*)      DESIRE
ENDIF
WRITE(*,304)
304 FORMAT(5(/),1X,'INPUT      INITIAL      CAPITAL')
READ(*,*)      CAPITAL
IF (NOPTION.EQ.3)      THEN
      WRITE(*,305)
305 FORMAT(5(/),1X,'INPUT      TOLERANCE      LEVEL      FOR      BISECTION      METHOD')
READ(*,*)      TOL
310 WRITE(*,306)
306 FORMAT(5(/),1X,'INPUT      PROFIT      MODEL      THAT      YOU      WANT      TO      BE      USED',//,
&5X,'1.      PROFIT      = f(CAPITAL)',//,
&5X,'2.      PROFIT      = f(PROJECT      COST)',//)

```

```

        READ(*,*)      CMODEL
        IF (CMODEL.LT.1.OR.CMODEL.GT.2)          GOTO 310
        ENDIF

C
C---IF DETERMINISTIC      PROBLEM,      RETURN
C
        IF (NUPTION.EQ.3)      RETURN
C
        WRITE(*,319)
319  FORMAT(//,1X,'YOU      WILL      NOW      BE      ASKED      TO      INPUT      THE      COST      THAT',//,
&1X,'YOU      WILL      REQUIRE      AT      THE      KEY      NODES,      AND      THE      DELIVERY',//,
&1X,'DATES      OF      THE      KEY      NODES.',//,
&5X,'NOTE:      INPUT      THE      COST      FOR      THE      ENTIRE      SUBGRAPH      OF      THE',//,
&5X,'      KEY      EVENT.      THE      PROGRAM      WILL      REMOVE      THE      ALLOTTED',//,
&5X,'      PERCENTAGE      TO      RECEIVE      AT      THE      PROJECT      START.',//)
        PAUSE

C
        DO 320  II=1,NKEYEN
326      WRITE(*,325)
        WRITE(*,330)      IKEY(II)
330      FORMAT(/20X,'FOR      KEY      EVENT      ',I3,'.....',//)
        WRITE(*,327)
327      FORMAT(5X,'DO      YOU      WANT      TO      EXAMINE      THE      FOLLOWING      BEFORE',//,
&5X,'PROCEEDING      WITH      THE      INPUT:',//,
&10X,'1.      EMPIRICAL      DENSITIES',//,
&10X,'2.      PERCENTILES      OF      DISTRIBUTIONS',//,
&10X,'3.      PROCEED      WITH      INPUT',//,
&10X,'4.      ---RETURN      TO      MAIN      MENU---',//)
        READ(*,*)      IVAL
        IF (IVAL.EQ.4)      RETURN
        IF (IVAL.LT.1.OR.IVAL.GT.3)      THEN
            WRITE(*,*)      'VALUE      OUT      OF      RANGE      ---      RETURN      TO      MAIN      MENU'
            RETURN
        ENDIF
        IF (IVAL.EQ.1)      THEN
            CALL  DWRITE
            GOTO 326
        ELSE  IF (IVAL.EQ.2)      THEN
            IF (IFLAGG.EQ.0)      CALL  PRCNTL(IFLAGG)
            CALL  PWRITE
            GOTO 326
        ENDIF

C
        WRITE(*,321)      IKEY(II)
321      FORMAT(//,1X,'INPUT      DURATION      AND      COST      DECIDED      ON      AT      KEY      NODE',I3)
        READ(*,*)      DURN(II),COST(II)
        WRITE(*,322)      IKEY(II)
322      FORMAT(//,1X,'INPUT      THE      LATE      PENALTY      FOR      KEY      EVENT',I4,/,
&1X,'PER      PERIOD',//)
        READ(*,*)      PENALTY(II)
320      CONTINUE

C
        TESUM=0.0

```

```

DO 323 I=1,NKEYEN
    TESUM=TESUM+COST(I)
323 CONTINUE
C      COST(11)=TESUM*STPERC
C
C      RETURN
C      END
C-----
C
C      SUBROUTINE      I N T R T
C
C      THIS      SUBROUTINE      CALCULATES      INTEREST      IN      EACH      PERIOD
C
C-----
```

SUBROUTINE INTRT(I,CASH,POWER,ALPHA,BETA,TIAF,TIBA,TRETEN,FLAG2)

```

C
C      INTEGER      I,FLAG2
C      REAL        CASH,POWER,ALPHA,BETA,TIAF,TIBA,TRETEN
C
C      REAL        GA,GB
C
TRETEN=TRETEN*(1+ALPHA)**POWER
IF (CASH.GE.0.00)      THEN
    GA=CASH*(1+ALPHA)**POWER-CASH
    TIAF=TIAF+GA
    CASH=CASH+GA
    IF (FLAG2.EQ.1)      THEN
        WRITE(3,1300)      I,GA,CASH
1300   FORMAT(3X,'I      =',15.5X,'IAF      =',F10.3,5X,'CASH      =',F10.3)
    ENDIF
ELSE
    GB=-1.0*CASH*(1+BETA)**POWER+CASH
    TIBA=TIBA+GB
    CASH=CASH-GB
    IF (FLAG2.EQ.1)      THEN
        WRITE(3,1305)      I,GB,CASH
1305   FORMAT(8X,'I      =',15.5X,'IBA      =',F10.3,5X,'CASH      =',F10.3)
    ENDIF
ENDIF
RETURN
END
C-----
```

SUBROUTINE P C F H E L P

```

C
C      THIS      SUBROUTINE      PROVIDES      INFORMATION      ON      THE      CASH      FLOW      CALCULATIONS
C      IN      A      PROBABILISTIC      PROBLEM.
C
C-----
```

SUBROUTINE PCFHELP

```

      WRITE(*,1)
1 FORMAT(25())
      WRITE(*,2)
2 FORMAT(5X,'THIS      PORTION      OF THE PROGRAM      DOES CASH FLOW CALCULAT-/,,
*5X,'TIONS      IN THE CASE OF A PROBABILISTIC      NETWORK.',//,
*5X,'YOU      WILL BE ASKED TO INPUT:',//,
*10X,'1.      INTEREST      RATE ON MONEY DEPOSITED',/,
*10X,'2.      INTEREST      RATE ON MONEY BORROWED',/,
*10X,'3.      RETENTION      RATE',/,
*10X,'4.      INITIAL      CAPITAL',/,
*10X,'5.      AMOUNT      OF MONEY TO BE RECEIVED      AT EACH KEY EVENT',/,
*10X,'6.      DUE DATE OF EACH KEY EVENT',/,
*10X,'7.      LATE PENALTY (PER PERIOD) FOR EACH KEY EVENT',/)
      PAUSE
C
      WRITE(*,10)
10 FORMAT(5())
      WRITE(*,3)
3 FORMAT(5X,'THE      DISTRIBUTION      INFORMATION      WILL BE AVAILABLE      TO',/,
*5X,'YOU      WHEN INPUTTING 5-7, ABOVE.',///,
*5X,'THE      RESULT      WILL BE AN EXPECTED      PROFIT      FOR THE GIVEN VALUES',/,
*5X,'OF 1-7, ABOVE.',/,
*5X,'YOU      MAY RUN AS MANY ALTERNATIVES      AS YOU LIKE TO DETERMINE',/,
*5X,'THE      BID PACKAGE THAT YOU WILL MAKE.      THE OUTPUT      WILL BE ',/,
*5X,'SENT      TO THE SCREEN,      AND ALSO TO A FILE NAMED "CASHOUT.OUT"',/,
*5X,'WHICH      WILL BE ON THE DEFAULT      DRIVE.',///)
      PAUSE
C
      RETURN
      END
C-----
C
C      SUBROUTINE      P R C N T L
C
C      THIS SUBROUTINE      CALCULATES      THE PERCENTILES      OF THE DISTRIBUTIONS.
C      IT USES A LINEAR      INTERPOLATION      BETWEEN ENDPOINTS      OF THE EMPIRICAL
C      DISTRIBUTIONS.
C-----
C
SUBROUTINE      PRCNTL(IFLAGG)
COMMON/DCV/COST(11),DURN(10),STPERC,PENALTY(10),PERCNT(22,20)
COMMON/CFMV/SDISBUR(100),PAY(10,100),RMEAN(11),PINIT,MXPERD,NKEYEN
*,IKEY(10),TPAY(100),DMEAN(10),DF(22,102),LL(22),NRR(22),NCELLS(22)
*,WIDTH(22),DSTD(10),RSTD(11),CDF(22,102),CORR(11),BHATO(11)
*,BHTA1(11),FRACN(10)
C
      WRITE(*,*)      'WORKING'
      IFLAGG=1
      DO 2000  I=1,22
      DO 2005  J=1,20
         PERCNT(I,J)=0.0
2005  CONTINUE

```

```

2000  CONTINUE
C
    MARK1=1
    MARK2=0
C
C---DETERMINE      PERCENTILES      THAT      ARE      MULTIPLES      OF      .05
C
2006  DO 2008  IN=MARK1,NKEYEN+MARK2
    DO 2010  IP=1,20
        RIP=IP*5/100.0
    DO 2012  ID=1,NCELLS(IN)+2
        IF (ID.EQ.1.AND.CDF(IN,ID).GT.RIP)           THEN
            PERCNT(IN,IP)=-1
            GOTO 2010
        ENDIF
        IF (CDF(IN,NCELLS(IN)+2).LT.RIP.AND.ID.EQ.NCELLS(IN)+2)   THEN
            PERCNT(IN,IP)=-1
            GOTO 2010
        ENDIF
        IF (CDF(IN,ID).LT.RIP)           GOTO 2012
        IF (CDF(IN,ID).EQ.RIP)           THEN
            PERCNT(IN,IP)=LL(IN)+WIDTH(IN)*(ID-1)
            GOTO 2010
        ENDIF
        SLOPE=(CDF(IN,ID)-CDF(IN,ID-1))/WIDTH(IN)
        B=CDF(IN,ID)-SLOPE*(LL(IN)+WIDTH(IN)*(ID-1))
        IF (SLOPE.EQ.0.)           THEN
            PERCNT(IN,IP)=LL(IN)+WIDTH(IN)*(ID-1)
        ELSE
            PERCNT(IN,IP)=(RIP-B)/SLOPE
        ENDIF
        GOTO 2010
2012  CONTINUE
2010  CONTINUE
2008  CONTINUE
C
    IF (MARK1.EQ.1)      THEN
        MARK1=11
        MARK2=10
        GOTO 2006
    ENDIF
C
    IF (MARK1.EQ.11)      THEN
        MARK1=22
        MARK2=22-NKEYEN
        GOTO 2006
    ENDIF
C
    RETURN
END
C-----
C
C      SUBROUTINE      P R O B A B

```

```

C
C      THIS SUBROUTINE      DOES CASH FLOW CALCULATIONS      IF THE NETWORK IS
C      PROBABILISTIC.      NOTE: IN THIS CASE IT SIMPLY CALCULATES THE
C      EXPECTED PROFIT FOR THE VALUES WHICH ARE GIVEN IN THE BID PACKAGE
C
C-----.
C
C      SUBROUTINE      PROBAB(NOPTION,IFLAGG)
C
COMMON/CFMV/SDISBUR(100),PAY(10,100),RMEAN(11),PINIT,MXPERD,NKEYEN
*,IKEY(10),TPAY(100),DMEAN(10),DF(22,102),LL(22),NRR(22),NCELLS(22)
*,WIDTH(22),DSTD(10),RSTD(11),CDF(22,102),CORR(11),BHATO(11)
*,BHAT(11),FRACN(10)
COMMON/CFP/ALPHA,BETA,POWER,RATE,DESIRE,NCYCLE,CAPITAL,TOL,CMODEL
COMMON/DCV/COST(11),DURN(10),STPERC,PENALTY(10),PERCNT(22,20)
INTEGER      NPERD(10),FLAG2,CMODEL
REAL        TIAF,TIBA,TRETN,RETEN,RATIO(10),DUMPAY(100)
C
1549  WRITE(*,1550)
1550  FORMAT(25(//))
      WRITE(*,1551)
1551  FORMAT(///10X,'1.      PROCEED WITH CASH FLOW CALCULATIONS',//,
*10X,'2.      PROBABILISTIC CASH FLOW INFORMATION',//,
*10X,'3.      RETURN TO MAIN MENU',//)
      WRITE(*,1552)
1552  FORMAT(5X,'ENTER      CHOICE')
      READ(*,*)  ICHOICE
      IF (ICHOICE.EQ.2)      THEN
          CALL PCFHELP
          GOTO 1549
      ENDIF
      IF (ICHOICE.EQ.3)      RETURN
C
      ISTOP=0
      CALL INPUT(NOPTION,ISTOP,IFLAGG)
      IF (ISTOP.EQ.1)      RETURN
C
      POWER=NCYCLE/365.0
      DESI=DESIRE/100.0
      TPINIT=0.0
C
C---COMPUTE      THE RATIO OF WHAT WE ASK FOR AT A KEY EVENT AND WHAT THE
C---EXPECTED      COST IS OF THE SUBGRAPH OF THE KEY EVENT. ALSO CALCULATE
C---THE      RATIO OF THE COST WE WANT TO RECEIVE AT THE PROJECT START TO
C---WHAT      THE EXPECTED VALUE IS
C
      DO 1590  JJ=1,100
          DUMPAY(JJ)=0.0
1590  CONTINUE
      DO 1591  JJ=1,NKEYEN
          RATIO(JJ)=0.0
          NPERD(JJ)=0.0
1591  CONTINUE

```

```

C
      DO 1600  JJ=1,NKEYEN
      RATIO(JJ)=COST(JJ)/RMEAN(JJ)
1600  CONTINUE
      IF (PINIT.GT.0.)      THEN
          RATIO(11)=COST(11)/PINIT
          TPINIT=RATIO(11)*PINIT
      ENDIF
C
C---ALTER    INCOME    ARRAYS    ACCORDINGLY
C
      DO 1605  J=1,NKEYEN
      DO 1610  JJ=1,MXPERD
          PAY(J,JJ)=PAY(J,JJ)*RATIO(J)
1610  CONTINUE
1605  CONTINUE
C
C---DETERMINE    TOTAL    INCOME    IN    ALL    PERIODS    FOR    ALL    KEY    EVENTS
C
      DO 1616  I=1,MXPERD
      DO 1617  J=1,NKEYEN
          DUMPAY(I)=DUMPAY(I)+PAY(J,I)
1617  CONTINUE
1616  CONTINUE
C
C---CALCULATE    THE    PERIOD    IN    WHICH    WE    PROMISE    DELIVERY    AT    EACH    KEY    EVENT
C
      DO 1615  JJ=1,NKEYEN
      IF((DURN(JJ)/NCYCLE).EQ.INT(DURN(JJ)/NCYCLE))        THEN
          NPERD(JJ)=DURN(JJ)/NCYCLE
      ELSE
          NPERD(JJ)=DURN(JJ)/NCYCLE+1
      ENDIF
1615  CONTINUE
C
      CASH=0.0
      TIAF=0.00
      TIBA=0.00
      TRETEN=0.00
      FLAG2=1
      DO 1510  I=1,MXPERD+1
C
C---INITIAL    PERIOD
C
      IF (I.EQ.1)      THEN
          CASH=CAPITAL+TPINIT*SDISBUR(I)
          CALL  INTRTC(I,CASH,POWER,ALPHA,BETA,TIAF,TIBA,TRETEN,FLAG2)
          WRITE(*,1950)      I,CASH
1950      FORMAT(1X,'PERIOD',13,2X,'CASH           =',F10.2)
          GO TO 1510
      ENDIF
C
C---AFTER    LAST    PERIOD

```

```

C
      IF (I.EQ.MXPERD+1)      THEN
          CASH=CASH+DUMPAY(I-1)+TRETN
          DO 1520  JJ=1,NKEYEN
              IF (NPERD(JJ).LT.I)      CASH=CASH-PENALTY(JJ)*CUM(JJ,I)
1520      CONTINUE
          CTERM=CASH
          WRITE(*,1991)      CASH
          WRITE(3,1991)      CASH
1991      FORMAT(25X,'TERMINAL'      CASH POSITION      =' ,F10.3)
          GO TO 1510
          END IF
C
C---ALL PERIODS BETWEEN BEGINNING AND END
C
      RETEN=DUMPAY(I-1)*RATE
      TRETN=TRETN+RETEN
      CASH=CASH+DUMPAY(I-1)*(1-RATE)-SDISBUR(I)
      DO 1530  JJ=1,NKEYEN
          IF (NPERD(JJ).LT.I)      CASH=CASH-PENALTY(JJ)*CUM(JJ,I)
1530      CONTINUE
      CALL INTRT(I,CASH,POWER,ALPHA,BETA,TIAF,TIBA,TRETN,FLAG2)
      WRITE(*,1980)      TRETN,RETEN
1980      FORMAT(/15X,'CUMULATIVE'      RETENTION      =' ,F10.3,3X,'RETENTION=' ,
*           F9.3/)
      WRITE(*,1951)      I,CASH
1951      FORMAT(1X,'PERIOD',I3,2X,'CASH'      =' ,F10.2)
C
C -----
C
1510      CONTINUE
      PROFIT=(CASH-CAPITAL)/RMEAN(11)
C
      WRITE(*,1901)
      WRITE(3,1901)
1901      FORMAT(//5X,'-----BID'      PACKAGE-----',//)
      WRITE(*,1902)      COST(11)
      WRITE(3,1902)      COST(11)
1902      FORMAT(1X,F10.2,'RECEIVED'      AT PROJECT START')
      DO 1910  I=1,NKEYEN
          WRITE(*,1911)      IKEY(I),COST(I),DURN(I),PENALTY(I)
          WRITE(3,1911)      IKEY(I),COST(I),DURN(I),PENALTY(I)
1910      CONTINUE
          FORMAT(//5X,'KEY'      EVENT',15,/,
*           5SX,B10.2 LEVEL      =' ,F10.2,/,
*           5SX,B10.2 EVERY DATE      =' ,F10.2,/,
*           5SX,B10.2 PENALTY      =' ,F10.2,///)
          PROFIT
          PROFIT
          PROFIT      PROFIT      PROFIT      =',F12.3/)
          RMEAN(11)
          RMEAN(11)

```

```

1903 FORMAT(//10X,'EXPECTED           PROJECT    COST   = ',F12.2,/)
      WRITE(*,1904)
      WRITE(3,1904)
1904 FORMAT(/2X,'UNDER          THE  CONSTRAINTS:   ')
      WRITE(*,1905)    CAPITAL
      WRITE(3,1905)    CAPITAL
1905 FORMAT(/8X,'INITIAL        CAPITAL   = ',F10.2)
      WRITE(*,1906)    ALPHA
      WRITE(*,1907)    BETA
      WRITE(*,1908)    RATE
      WRITE(3,1906)    ALPHA
      WRITE(3,1907)    BETA
      WRITE(3,1908)    RATE
1906 FORMAT(/8X,'INTEREST       RATE  ON MONEY DEPOSIT   = ',F6.4,'%')
1907 FORMAT(/8X,'INTEREST       RATE  ON MONEY BORROWT  = ',F6.4,'%')
1908 FORMAT(/8X,'RETENTION      RATE   = ',F6.4,'%')
      RETURN
      END
C-----
C
C      SUBROUTINE      P W R I T E
C
C      THIS SUBROUTINE      WRITES      THE PERCENTILES      TO THE SCREEN
C
C-----
C
      SUBROUTINE      PWRITE
      COMMON/DCV/COST(11),DURN(10),STPERC,PENALTY(10),PFRONT(22,2)
      COMMON/CFMV/SDISBUR(100),PAY(10,100),RMEAN(11),PFRONT,MXPERC,NKEYEN
      * ,IKEY(10),TPAY(100),DMEAN(10),DF(22 02),L(22),NRR(22),MCFL,SY2
      * ,WIDTH(22),DSTD(10),RSTD(11),CDF(2 ,102),CORR(11),BHAT(11)
      * ,BHAT1(11),FRACN(10)
C
      WRITE(*,878)
878  FORMAT(5X,'ENTER      NUMBER      OF KEY EVENT CENTER      F S Y A')
      READ(*,*)      NKEY
      IF (NKEY.EQ.0)      GOTO 885
      IF (NKEY.LT.IKEY(1).OR.NKEY.GT.IKEY(NKEYEN))      THEN
          WRITE(*,*)      'OUT OF RANGE'      RETURN      TO MAIN
          RETURN
      ENDIF
C
      DO 231  I=1,NKEYEN
          IF ((IKEY(I).EQ.NKEY))      MNM=1
231  CONTINUE
C
885  IF (NKEY.EQ.0)      THEN
          WRITE(*,887)
          WRITE(*,888)
      ELSE
          WRITE(*,886)      IKEY(MNM)
          WRITE(*,889)
          WRITE(*,890)

```



```

&10X,'3.      EXPECTED "OUTFLOW"    VS. TOTAL "INFLOW",/,
&10X,'4.      --RETURN TO MAIN MENU--',//,
&10X,'5.      CASH FLOW INFORMATION',//,
&10X,'6.      EXIT PROGRAM'//)
READ(*,*) NV
IF (NV.EQ.6) STOP
IF (NV.LT.1.OR.NV.GT.5) THEN
  WRITE(*,*) 'VALUE OUT OF RANGE'
  WRITE(*,*) '---RETURN TO MAIN---'
  RETURN
ENDIF
C
IF (NV.EQ.4) RETURN
C
IF (NV.EQ.5) THEN
  CAL1 CFHELP
  GOTO 222
ENDIF
C
IF (NV.EQ.2) THEN
  WRITE(*,*) 'DUE TO WHICH KEY EVENT? (0 IF TOTAL "INFLOW")'
  READ(*,*) NKEY
  IF (NKEY.EQ.0) GOTO 240
  IF (NKEY.LT.IKEY(1).OR.NKEY.GT.IKEY(NKEYEN)) THEN
    WRITE(*,*) 'OUT OF RANGE --- RETURN TO MAIN'
    RETURN
  ENDIF
  DO 230 I=1,NKEYEN
    IF (IKEY(I).EQ.NKEY)      NNN=I
  230 CONTINUE
ENDIF
C
240 IF (N. 0.1.OR.NV.EQ.2) THEN
C
  WRITE(*,290)
290  FORMAT(//12X,'PERIOD',//)
  J1=0
  IF (NV.EQ.2.AND.NKEY.EQ.0)      WRITE(*,292) J1,PINIT
  FORMAT(10X,15,8X,F12.2)
  DO 210 I=1,MXPERD
    IF ((MOD(I,15)).EQ.0)      THEN
      WRITE(*,*) 'Hit Return for more.'
      READ(*,295) NCHAR
    ENDIF
    IF (NV.EQ.1)      WRITE(*,291) I,SDISBIR(I)
    IF (NV.EQ.2 AND NKEY.NE.0)      WRITE(*,291) I,PAY(NNN,I)
    IF (NV.EQ.2 AND NKEY.EQ.0)      WRITE(*,291) I,TPAY(I)
  210 CONTINUE
291  FORMAT(10X,15,8X,F12.2)
C
  ELSE IF (NV.EQ.3) THEN
    WRITE(*,296)

```

```
250    FORMAT(//12X,'PERIOD          "OUTFLOW"           "INFLOW"',//)
       JI=0
       WRITE(*,251)   JI,PINIT
251    FORMAT(12X,I4,20X,F11.2)
       DO 255  I=1,MXPED
          IF  (MOD(I,15).EQ.0)      THEN
             WRITE(*,*)  'Hit Return for more.'
             READ(*,295)  NCHAR
          ENDIF
          WRITE(*,260)  I,SDISBUR(I),TPAY(I)
260    FORMAT(12X,I4,6X,F11.2,3X,F11.2)
255    CONTINUE
          ENDIF
C
          PAUSE
          GOTO 222
295  FORMAT(A1)
299  FORMAT(25(/))
C
          RETURN
          END
C-----
```

E N D

3 - 81

D T / C